



Eaton Metered Input rack PDU, 1U, Input C20, 3.7 kW max, 16A, 200-240V, Outlets 8XC13



Catalog No. EMIH28

Similar to illustration

Delivery program

| | | | |
|-----------------------------------|--|--|---|
| Type | | | Rack PDU |
| Input Connection | | | C20 |
| Cord Length | | | 3m |
| Input Voltage | | | 200-240V |
| Phase | | | Single-phase |
| Frequency Rating | | | 50/60 Hz |
| Ethernet Interface | | | Yes |
| Serial Interface | | | Yes |
| Form Factor | | | 1U |
| Outlet Control | | | No |
| Operating Temperature | | | 0° to 60°C (32° to 140°F) |
| Outlets | | | 8XC13 |
| Number of Outputs C13 | | | 8 |
| Number of Outputs C19 | | | 0 |
| Amperage Rating | | | 16A |
| Mounting Direction | | | Horizontal |
| ETIM Class | | | EC002762 |
| Fitted With: | | | Mounting material Display Ampere Meter |
| Electrical Connection | | | Connecting cord with plug |
| Evaluation | | | At distance |
| Mounting Dimension (metrical) | | | 444.5 |
| Mounting Dimension (standardised) | | | 482.6 mm (19 inch) |
| Switchable | | | No |
| Over Voltage Category | | | 2 |
| Wattage | | | 3.84 kW max |
| Communication | | | HTTP, HTTPS, SSL, Telnet, FTP, SNMP, SMTP, DNS, DHCP, LDAP, RADIUS |
| SNMP | | | Yes |
| Mass Configuration | | | Yes |
| Package Contents | | | PDU mounting accessories network cable configuration cable splitter for daisy-chaining Quickstart Safety Instructions |
| Number of Outputs C20 | | | 0 |
| Num of Outputs PC (SCHUKO) | | | 0 |
| Number of Outputs (Other) | | | 0 |

| | | |
|----------------------------------|--|-------|
| Number of Outlets with Earth Pin | | 8 |
| Color | | Black |

Technical data ETIM 7.0

| | | |
|--|----|---------------------------|
| Domestic switching devices (EG000013) / Power distribution unit (PDU) (EC002762) | | |
| Electric engineering, automation, process control engineering / Electrical installation, device / Low-voltage distribution system (mobile) / Low-voltage distribution systems (mobile, unspecified) (ecl@ss10.0.1-27-14-26-90 [AKN612013]) | | |
| Mounting dimension (standardised) | | 482.6 mm (19 inch) |
| Mounting dimension | mm | 444.5 |
| Mounting direction | | Horizontal |
| Electrical connection | | Connecting cord with plug |
| Type of electric connection | | C20 |
| Cable length | m | 3 |
| Number of socket outlets with protective contact | | 0 |
| Number of socket outlets with earth pin | | 8 |
| Number of C13 socket outlets | | 8 |
| Number of C19 socket outlets | | 0 |
| Number of C20 socket outlets | | 0 |
| Number of UK BS1363 sockets | | |
| number of socket outlets swiss standard type 13 | | |
| number of socket outlets swiss standard type 15 | | |
| number of socket outlets swiss standard type 23 | | |
| number of socket outlets swiss standard type 25 | | |
| Number of other socket outlets | | 0 |
| Number of height units | | 1 |
| Length | mm | 203.2 |
| Width | mm | 42.9 |
| Height | mm | 444.5 |
| Depth | mm | 203.2 |
| Supply voltage | V | |
| Over voltage category | | 2 |
| Mains filter | | No |
| Switchable | | No |
| SNMP | | Yes |
| With display | | Yes |
| Evaluation | | At distance |
| With LED indication | | No |
| With fuse | | No |
| Ampere meter | | Yes |
| With temperature measurement | | No |
| With mounting material | | Yes |