



Fuse-link, low voltage, AC 415 V, BS88/F2, 21 x 68 mm, gM, BS

ESD63M100

Similar to illustration

Product name	Eaton Bussmann series low voltage British standard fuse
Part no.	ESD63M100
EAN	5027590498708
Product Length/Depth	67 millimetre
Product height	22 millimetre
Product width	22 millimetre
Product weight	42.1 gram
Compliances	Contact Manufacturer
Product Tradename	None
Product Type	Low voltage British standard fuse
Product Sub Type	None
Amperage Rating	63 A
Voltage rating	415 V
Voltage type	AC
Breaking capacity	80 kA
Class	Class gM
Application	general industrial applications
Fuse type	ESD
Fuse size	BS88/F2
Fitted with:	Offset bladed tags
Connection	Blade end
Suitable for	63ENS Safelec fuse holder SC63 Safeclip fuse holder

Technical data ETIM 8.0

Circuit breakers and fuses (EG000020) / HRC fuse (EC004556)		
Electric engineering, automation, process control engineering / Electrical installation, device / Safety fuse inserts / Safety fuse inserts (unspecified) (ecl@ss10.0.1-27-14-20-90 [BAB264011])		
Fuse construction type according to IEC 60269		F2
Type of current		AC
Rated voltage AC	V	415
Rated voltage DC	V	
Rated current	A	63
Utilization category		gM (motor protection)
Breaking capacity	kA	80
Colour code		None
Type of fuse status indicator		None
Power loss at rated current	W	2.5
Mounting holes		
Centre-to-centre distance of connections	mm	