

Eaton Switched Rack PDU, 0U, 26U, Inputs C14, 2.3 kW max, 10A, 200-240V, Outlets 16XC13



Catalog No. ESWB03

D	eli	ver	y p	ro	gra	m

De	Rack PDU
nput Connection	C14
Cord Length	3m
	200-240V
nput Voltage	
Phase	Single-phase
requency Rating	50/60 Hz
Ethernet Interface	Yes
Serial Interface	Yes
Form Factor	OU (Vertical)
Outlet Control	Yes
Operating Temperature	0° to 60°C (32° to 140°F)
Outlets	16XC13
Number of Outputs C13	16
Number of Outputs C19	0
Amperage Rating	10A
Mounting Direction	Vertical
TIM Class	EC002762
Fitted With:	Display Ampere Meter Mounting material
Electrical Connection	Connecting cord with plug
Evaluation	At distance
Mounting Dimension (metrical)	52
Mounting Dimension (standardised)	Metric
Switchable	Yes
Over Voltage Category	2
Nattage	2.3 kW max
Communication	HTTP, HTTPS, SSL, Telnet, FTP, SNMP, SMTP, DNS, DHCP, LDAP, RADIU
SNMP	Yes
Mass Configuration	Yes
Package Contents	PDU mounting accessories network cable configuration cable splitter for daisy-chaining Quickstart Safety Instructions
Number of Outpute C20	0
Number of Outputs C20	0
Num of Outputs PC (SCHUKO)	0
Number of Outputs (Other)	0
Number of Outlets with Earth Pin	16

Color Black

Technical data ETIM 7.0

Domestic switching devices (EG000013) / Power distribution unit (PDU) (EC002762)

Electric engineering, automation, process control engineering / Electrical installation, device / Low-voltage distribution system (mobile) / Low-voltage distribution systems (mobile, unspecified) (ecl@ss10.0.1-27-14-26-90 [AKN612013])

(ecl@ss10.0.1-27-14-26-90 [AKN612013])		
Mounting dimension (standardised)		Metric
Mounting dimension	mr	n
Mounting direction		Vertical
Electrical connection		Connecting cord with plug
Type of electric connection		C14
Cable length	m	3
Number of socket outlets with protective contact		0
Number of socket outlets with earth pin		16
Number of C13 socket outlets		16
Number of C19 socket outlets		0
Number of C20 socket outlets		0
Number of UK BS1363 sockets		
number of socket outlets swiss standard type 13		
number of socket outlets swiss standard type 15		
number of socket outlets swiss standard type 23		
number of socket outlets swiss standard type 25		
Number of other socket outlets		
Number of height units		
Length	mn	n 1,150
Width	mn	n 53
Height	mn	n 52
Depth	mn	n 1,150
Supply voltage	V	
Over voltage category		2
Mains filter		No
Switchable		Yes
SNMP		Yes
With display		Yes
Evaluation		At distance
With LED indication		No
With fuse		No
Ampere meter		Yes
With temperature measurement		No
With mounting material		Yes