



**Fuse-link, high speed, 1200 A, AC 1000 V, DC 800 V, 100 kA, 89 x 173 mm, UL**



**Part no. 1200A 1000V AC SEMI-COND FUSE**  
**Catalog No. FWJ-1200A**

Similar to illustration

## Delivery program

Product range			Fuse
Basic function			Fuse-link
Field of application			high speed
Rated current	I	A	1200
Rated voltage			AC 1000 V DC 800 V
Size			89 x 173 mm
Breaking Capacity		kA	100
usable for size/applications			DC common bus, DC drives, power converters/rectifiers and reduced voltage starters
Standard/Approval			UL
Shape			cylindrical with centre-bolted tags
Standards/Regulations			UL 248

## Technical data ETIM 7.0

Circuit breakers and fuses (EG000020) / Low Voltage HRC fuse (EC000055)			
Electric engineering, automation, process control engineering / Electrical installation, device / Safety fuse inserts / Low-Voltage HRC fuse (ecl@ss10.0.1-27-14-20-05 [AFZ800015])			
Construction size			Other
Rated current		A	1200
Rated voltage		V	1000
Voltage type			AC/DC
Rated switching capacity		kA	100
Utilization category			Other
Type of fuse status indicator			None
Insulated metal gripping lugs (IMGL)			No

## Additional product information (links)

Product datasheet (pdf)	<a href="http://www.cooperindustries.com/content/dam/public/bussmann/Electrical/Resources/product-datasheets-b/Bus_Ele_DS_720027_FWJ-(35-2000)A.pdf">http://www.cooperindustries.com/content/dam/public/bussmann/Electrical/Resources/product-datasheets-b/Bus_Ele_DS_720027_FWJ-(35-2000)A.pdf</a>
-------------------------	---