



**Fuse-link, low voltage, 250 A, AC 600 V, 200 kA, 25 x 92 mm, T, UL, very fast acting**



**Part no. TRON FAST ACTING FUSE CLASS T**  
**Catalog No. JJS-250**

## Delivery program

Product range			Fuse
Basic function			Fuse-link
Field of application			low voltage
Rated current	I	A	250
Rated voltage			AC 600 V
Size			25 x 92 mm
Utilization category			T
Breaking Capacity		kA	200
usable for size/applications			commonly applied in electric heat circuits, load center, disconnect switches, and meters
Release characteristic	class		very fast acting
Standard/Approval			UL

## Technical data ETIM 7.0

Circuit breakers and fuses (EG000020) / Low Voltage HRC fuse (EC000055)			
Electric engineering, automation, process control engineering / Electrical installation, device / Safety fuse inserts / Low-Voltage HRC fuse (ecl@ss10.0.1-27-14-20-05 [AFZ800015])			
Construction size			Other
Rated current		A	250
Rated voltage		V	600
Voltage type			AC
Rated switching capacity		kA	200
Utilization category			Other
Type of fuse status indicator			None
Insulated metal gripping lugs (IMGL)			No

## Additional product information (links)

Product datasheet (PDF)	<a href="http://www.cooperindustries.com/content/dam/public/bussmann/Electrical/Resources/product-datasheets-b/Bus_Ele_DS_1029_JJS.pdf">http://www.cooperindustries.com/content/dam/public/bussmann/Electrical/Resources/product-datasheets-b/Bus_Ele_DS_1029_JJS.pdf</a>
Product overview (WEB)	<a href="http://www.cooperindustries.com/content/public/en/bussmann/electrical/products/supplemental/class_t/jjs.html">http://www.cooperindustries.com/content/public/en/bussmann/electrical/products/supplemental/class_t/jjs.html</a>