



Fuse-link, high speed, 20 A, DC 1100 V, 30 kA, IEC 60269-6 type A, 14 x 51 mm, gPV, IEC

Part no. 20AMP 1100V DC SOLAR FERRULE
Catalog No. PV-20A14F

Delivery program

Product range			Fuse
Basic function			Fuse-link
Field of application			high speed
Rated current	I	A	20
Rated voltage			DC 1100 V
Construction size			IEC 60269-6 type A
Size			14 x 51 mm
Utilization category			gPV
Breaking Capacity		kA	30
usable for size/applications			protection of solar PV strings
Standard/Approval			IEC
Shape			cylindrical
Standards/Regulations			IEC 60269-6 UL 2579

Technical data ETIM 7.0

Circuit breakers and fuses (EG000020) / Cylindrical fuse (EC002704)			
Electric engineering, automation, process control engineering / Electrical installation, device / Safety fuse inserts / Cylindrical fuse (safety fuse) (ecl@ss10.0.1-27-14-20-02 [AFZ797013])			
Size			14x51 mm
Rated voltage		V	1100 - 1100
Rated voltage			Other
Voltage type			DC
Utilization category			Other
Rated operating frequency		Hz	0 - 0
Nominal current		A	20
With striker			No
Release characteristic			Other
Breaking capacity		kA	30