



Fuse-link, low voltage, AC 660 V, DC 350 V, BS88/B1, 26 x 137 mm, gM, BS

**TC100M160**

|                      |  |   |
|----------------------|--|---|
| Product name         |  | Eaton Bussmann series low voltage British standard fuse |
| Part no.             |  | TC100M160   |
| EAN                  |  | 5027590513319   |
| Product Length/Depth |  | 111 millimetre  |
| Product height       |  | 34 millimetre   |
| Product width        |  | 34 millimetre   |
| Product weight       |  | 205.6 gram  |
| Compliances          |  | Not Applicable  |
| Certifications       |  | IEC Rated   |
| Product Tradename    |  | None  |
| Product Type         |  | Low voltage British standard fuse                       |
| Product Sub Type     |  | None  |
| Amperage Rating      |  | 160 A   |
| Voltage rating       |  | 660 V   |
| Voltage type         |  | AC/DC   |
| Breaking capacity    |  | 80 kA   |
| Class                |  | Class gM  |
| Application          |  | ! general industrial applications                       |
| Fuse type            |  | TC  |
| Fuse size            |  | BS88/B1   |
| Fitted with:         |  | Centre bolted tags                                      |
| Connection           |  | 111 mm fixing centre                                    |
| Quantity             |  | 10  |

**Technical data ETIM 8.0**

|  |    |                       |
|--|----|-----------------------|
| Circuit breakers and fuses (EG000020) / HRC fuse (EC004556)  |    |                       |
| Electric engineering, automation, process control engineering / Electrical installation, device / Safety fuse inserts / Safety fuse inserts (unspecified) (ecl@ss10.0.1-27-14-20-90 [BAB264011]) |    |                       |
| Fuse construction type according to IEC 60269  |    | B1                    |
| Type of current  |    | AC/DC                 |
| Rated voltage AC   | V  | 660                   |
| Rated voltage DC   | V  | 350                   |
| Rated current  | A  | 160                   |
| Utilization category   |    | gM (motor protection) |
| Breaking capacity  | kA | 80                    |
| Colour code  |    | None                  |
| Type of fuse status indicator  |    | None                  |
| Power loss at rated current  | W  |                       |
| Mounting holes   |    | M8                    |
| Centre-to-centre distance of connections   | mm | 111                   |