Fuse-link, LV, 315 A, AC 660 V, DC 460 V, BS88/B3, 53 x 137 mm, gM, BS, 315M355



TKF315M355

Product name	Eaton Bussmann series low voltage British standard fuse
Part no.	TKF315M355
EAN	5996516026472
Product Length/Depth	137 millimetre
Product height	53 millimetre
Product width	53 millimetre
Product weight	498 gram
Compliances	CE Marked RoHS Compliant
Certifications	EAC BS88 IEC 60269 KEMA
Product Tradename	None
Product Type	Low voltage British standard fuse
Product Sub Type	None
Amperage Rating	355 A
Voltage rating	660 V
Voltage type	AC/DC
Breaking capacity	80 kA
Class	Class gM
Application	general industrial applications
Fuse type	TKF
Fuse size	BS88/B3
Fitted with:	Centre bolted tags
Connection	111 mm fixing centre

Technical data ETIM 8.0

1001111041 4444 = 11111 010		
Circuit breakers and fuses (EG000020) / HRC fuse (EC004556)		
Electric engineering, automation, process control engineering / Electrical installation, d	evice / Safety fuse	inserts / Safety fuse inserts (unspecified) (ecl@ss10.0.1-27-14-20-90 [BAB264011])
Fuse construction type according to IEC 60269		Other
Type of current		AC/DC
Rated voltage AC	V	660
Rated voltage DC	V	460
Rated current	Α	355
Utilization category		gM (motor protection)
Breaking capacity	kA	80
Colour code		None
Type of fuse status indicator		None
Power loss at rated current	W	
Mounting holes		M8
Centre-to-centre distance of connections	mm	111