## **DATASHEET - 5A TIME FUSE LINKS**



Time fuse-link, LV, 5 A, 15  $\times$  58 mm, ESI 12-6

Powering Business Worldwide\*

Part no. 5A TIME FUSE LINKS Catalog No. XF5

Similar to illustration

Delivery program			
Product range			Fuse
Basic function			Time fuse-link
Field of application			low voltage
Functionality			modifies the breaker tripping characteristic
Rated current	1	Α	5
Size			15 x 58 mm
usable for size/applications			for use with current transformer releases on circuit breakers
Standard/Approval			ESI 12-6
Shape			offset bolted tags (slotted)
Standards/Regulations			ESI 12-6

## **Technical data ETIM 7.0**

Circuit breakers and fuses (EG000020) / Low Voltage HRC fuse (EC000055)					
Electric engineering, automation, process control engineering / Electrical installation, device / Safety fuse inserts / Low-Voltage HRC fuse (ecl@ss10.0.1-27-14-20-05 [AFZ800015])					
Construction size		Other			
Rated current	Α	5			
Rated voltage	V	0			
Voltage type		AC			
Rated switching capacity	kA				
Utilization category		Other			
Type of fuse status indicator		None			
Insulated metal gripping lugs (IMGL)		No			