



Eaton Switched Rack PDU, 0U, 36U, Inputs IEC-60309 32A 1Ph, 7.4 kW max, 32A, 200-240V, Outlets 20XC13 : 4XC19



Catalog No. ESWB05

Delivery program

Type			Rack PDU
Electrical Connection			Connecting cord with plug
Evaluation			At distance
Mounting Dimension (metrical)			52
Mounting Dimension (standardised)			Metric
Ampere Meter			Yes
Switchable			Yes
Over Voltage Category			2
Input Connection			IEC-60309 32A 1Ph
Cord Length			3m
Wattage			7.4 kW max
Input Voltage			200-240V
Phase			Single-phase
Frequency Rating			50/60 Hz
With Temperature Measurement			No
Communication			HTTP, HTTPS, SSL, Telnet, FTP, SNMP, SMTP, DNS, DHCP, LDAP, RADIUS
SNMP			Yes
Ethernet Interface			Yes
Display			Yes
LED Indicator			No
Serial Interface			Yes
Mass Configuration			Yes
Form Factor			0U (Vertical)
Outlet Control			Yes
Package Contents			PDU mounting accessories network cable configuration cable splitter for daisy-chaining Quickstart Safety Instructions
With Mounting Material			Yes
Operating Temperature			0° to 60°C (32° to 140°F)
Outlets			20XC13 : 4XC19
Number of Outputs C13			20
Number of Outputs C19			4
Number of Outputs C20			0
Num of Outputs PC (SCHUKO)			0
Number of Outputs (Other)			0
Number of Outlets with Earth Pin			24
Circuit Breaker			(2) single-pole
With Fuse			No
Mains Filter			No

Amperage Rating		32AA
Mounting Direction		Vertical
Color		Black
ETIM Class		EC002762

Technical data ETIM 7.0

Domestic switching devices (EG000013) / Power distribution unit (PDU) (EC002762)		
Electric engineering, automation, process control engineering / Electrical installation, device / Low-voltage distribution system (mobile) / Low-voltage distribution systems (mobile, unspecified) (ecI@ss10.0.1-27-14-26-90 [AKN612013])		
Mounting dimension (standardised)		Metric
Mounting dimension	mm	52
Mounting direction		Vertical
Electrical connection		Connecting cord with plug
Type of electric connection		Other
Cable length	m	
Number of socket outlets with protective contact		0
Number of socket outlets with earth pin		24
Number of C13 socket outlets		20
Number of C19 socket outlets		4
Number of C20 socket outlets		0
Number of UK BS1363 sockets		
number of socket outlets swiss standard type 13		
number of socket outlets swiss standard type 15		
number of socket outlets swiss standard type 23		
number of socket outlets swiss standard type 25		
Number of other socket outlets		0
Number of height units		
Length	mm	1,604
Width	mm	53
Height	mm	52
Depth	mm	1,604
Supply voltage	V	
Over voltage category		2
Mains filter		No
Switchable		Yes
SNMP		Yes
With display		Yes
Evaluation		At distance
With LED indication		No
With fuse		No
Ampere meter		Yes
With temperature measurement		No
With mounting material		Yes