



Eaton Switched Rack PDU, 0U, 36U, Inputs IEC-60309 32A 1Ph, 7.4 kW max, 32A, 200-240V, Outlets 20XC13 : 4XC19



N° de catalogue ESWB05

Gamme de livraison

Type		Rack PDU
Electrical Connection		Cordon et prise de connexion
Evaluation		À distance
Mounting Dimension (metrical)		52
Mounting Dimension (standardised)		Métrique
Ampere Meter		Oui
Switchable		Oui
Over Voltage Category		2
Input Connection		IEC-60309 32 A monophasé
Cord Length		3 m
Wattage		7,4 kW maximum
Input Voltage		200-240V
Phase		Monophasé
Frequency Rating		50/60 Hz
With Temperature Measurement		Non
Communication par bus de terrain		HTTP, HTTPS, SSL, Telnet, FTP, SNMP, SMTP, DNS, DHCP, LDAP, RADIUS
SNMP		Oui
Ethernet Interface		Oui
Display		Oui
LED Indicator		Non
Serial Interface		Yes
Mass Configuration		Yes
Form Factor		0U (Vertical)
Outlet Control		Oui
Package Contents		PDU mounting accessories network cable configuration cable splitter for daisy-chaining Quickstart Safety Instructions
With Mounting Material		Oui
Operating Temperature		0 à 60 °C (32 à 140 °F)
Outlets		20XC13 : 4XC19
Number of Outputs C13		20
Number of Outputs C19		4
Number of Outputs C20		0
Num of Outputs PC (SCHUKO)		0
Number of Outputs (Other)		0
Number of Outlets with Earth Pin		24
Disjoncteur		(2) single-pole
With Fuse		Non
Mains Filter		Non

Amperage Rating		32AA
Mounting Direction		Vertical
Color		Noir

Caractéristiques techniques ETIM 7.0

Appareillage terminal, prises et commandes (résidentiel) (EG000013) / Unité de distribution d'énergie (PDU) (EC002762)		
Electricité, Electronique, Automatisation et Commande / Installation électrique, appareillage / Distributeur à basse tension mobile / Distributeur à basse tension mobile (non classé) (ecI@ss10.0.1-27-14-26-90 [AKN612013])		
Mounting dimension (standardised)		Metric
Mounting dimension	mm	52
Mounting direction		Vertical
Electrical connection		Connecting cord with plug
Type of electric connection		Other
Cable length	m	
Number of socket outlets with protective contact		0
Number of socket outlets with earth pin		24
Number of C13 socket outlets		20
Number of C19 socket outlets		4
Number of C20 socket outlets		0
Number of UK BS1363 sockets		
number of socket outlets swiss standard type 13		
number of socket outlets swiss standard type 15		
number of socket outlets swiss standard type 23		
number of socket outlets swiss standard type 25		
Number of other socket outlets		0
Number of height units		
Length	mm	1,604
Width	mm	53
Height	mm	52
Depth	mm	1,604
Supply voltage	V	
Over voltage category		2
Mains filter		No
Switchable		Yes
SNMP		Yes
With display		Yes
Evaluation		At distance
With LED indication		No
With fuse		No
Ampere meter		Yes
With temperature measurement		No
With mounting material		Yes