

# Especificaciones



## Eaton PDUMV32HV

Eaton Tripp Lite series metered outlet PDU, 1PH, 0U, IEC-60309 input, 10 ft cord, 7.7kW, 32A, 200-240V, 48 Outlets (20) C13 (8) C19

### Especificaciones generales

<b>PRODUCT NAME</b>	Eaton Tripp Lite series metered outlet PDU
<b>CATALOG NUMBER</b>	PDUMV32HV
<b>UPC</b>	037332182814
<b>PRODUCT LENGTH/DEPTH</b>	2.52 in
<b>PRODUCT HEIGHT</b>	70 in
<b>PRODUCT WIDTH</b>	2.17 in
<b>PRODUCT WEIGHT</b>	13 lb
<b>COMPLIANCES</b>	CE Marked RoHS FCC Class B
<b>CERTIFICATIONS</b>	RETIE NOM IEC 62368-1



Powering Business Worldwide

## Especificaciones del producto

## Recursos

<b>FORM FACTOR</b>	0U (Vertical)
<b>PACKAGE CONTENTS</b>	<ul style="list-style-type: none"><li>• PDUMV32HV 32A 200-240V 7.7kW Single-Phase Local metered PDU</li><li>• Plug-lock inserts (8 C20, 40 C13)</li><li>• Spare installation buttons, 2.9 mm/4.6 mm</li><li>• Ground screw</li><li>• Mounting hardware</li><li>• Owner's Manual</li></ul>
<b>MOUNTING DIRECTION</b>	Vertical
<b>MATERIAL</b>	Metal
<b>INPUT CONNECTION</b>	IEC-60309 32A BLUE (2P+E)
<b>CORD LENGTH</b>	10 ft
<b>AMPERAGE RATING</b>	32A
<b>PHASE</b>	Single-phase
<b>FREQUENCY RATING</b>	50/60 Hz
<b>NUMBER OF OUTPUTS C13</b>	40
<b>NUMBER OF OUTPUTS C19</b>	8
<b>FEATURES</b>	Flex Center
<b>FRONT PANEL LCD DISPLAY</b>	Set of two digital current meters report output current in two segments
<b>OUTPUT RECEPTACLES</b>	C19 C13
<b>OVERLOAD PROTECTION</b>	Two 20A circuit breakers protect 24 outlets each
<b>RECOMMENDED ELECTRICAL SERVICE</b>	Single-phase 32A 200-240V service
<b>REPORTED LOAD SEGMENTS</b>	Supports local monitoring of output current for each output load bank; Outlets, circuit breakers and current meters are color-coded and labeled for easy identification (Black: 20A Bank 1 / Gray: 20A Bank 2)
<b>OPERATING ELEVATION</b>	0-3000
<b>OPERATING TEMPERATURE RANGE</b>	32° to 122°F (0° to 50°C)

<b>OUTPUT NOMINAL VOLTAGE</b>	200-240V
<b>RELATIVE HUMIDITY</b>	5% to 95% non-condensing
<b>FORM FACTORS SUPPORTED</b>	0u vertical installation in equipment racks, plus under-counter and wallmount
<b>OUTPUT CAPACITY DETAILS</b>	7.7kW (240V), 7.4kW (230V), 7kW (220V), 6.7kW (208V), 6.4kW (200V) / 32A total capacity; 16A max per breakered outlet bank; 16A max per C19 outlet; 10A max per C13 outlet
<b>STORAGE TEMPERATURE</b>	-22° to 140°F (-30° to 60°C)
<b>PRODUCT HIGHLIGHTS</b>	<p>Ideal for server rooms, network closets and data centers</p> <p>IEC-309 32A blue input plug with 10-ft. (3.05 m) cord</p> <p>Dedicated 20A circuit breakers protect output</p> <p>Dual load banks with 24 outlets each (4 C19 and 20 C13)</p> <p>Ready for immediate toolless 0U installation</p>
<b>PDU TYPE</b>	Local metered
<b>PDU INPUT VOLTAGE</b>	200
<b>PDU FORM FACTOR</b>	Vertical (0U)

**NOMBRE DE PROYECTO:**

**NÚMERO DE PROYECTO:**

**PREPARADO POR:**

**FECHA:**



**Eaton Corporation plc** Eaton House  
 30 Pembroke Road  
 Dublín 4, Irlanda  
 Eaton.com

Síguenos en las redes sociales para obtener la información más reciente sobre productos y asistencia.

