



Fuse-link, low voltage, 1.125 A, AC 250 V, UL supplemental, 10 x 38 mm, UL, CSA, time-delay, with indicator

Catalog No. FNA-1-1/8

Similar to illustration

Delivery program

Product range			Fuse
Basic function			Fuse-link
Field of application			low voltage
Rated current	I	A	1.125
Rated voltage			AC 250 V
Construction size			UL supplemental
Size			10 x 38 mm
Status indicator			with indicator
Description			colour-code green
Release characteristic	class		time-delay
Standard/Approval			UL CSA
Shape			cylindrical
Standards/Regulations			UL 248-14

Technical data ETIM 7.0

Circuit breakers and fuses (EG000020) / Cylindrical fuse (EC002704)			
Electric engineering, automation, process control engineering / Electrical installation, device / Safety fuse inserts / Cylindrical fuse (safety fuse) (ecl@ss10.0.1-27-14-20-02 [AFZ797013])			
Size			10x38 mm
Rated voltage		V	250 - 250
Rated voltage			Other
Voltage type			AC
Utilization category			Other
Rated operating frequency		Hz	45 - 62
Nominal current		A	1.125
With striker			No
Release characteristic			Other
Breaking capacity		kA	0.2

Additional product information (links)

Product datasheet (pdf)	http://www.cooperindustries.com/content/dam/public/bussmann/Electrical/Resources/product-datasheets-a/Bus_Ele_DS_2029_FNA.pdf
Product datasheet (web)	http://www.cooperindustries.com/content/public/en/bussmann/electrical/products/fuses-lv-midget-supplemental/pin-indicating/fna.html