

Shunt release (for power circuit breaker), 380 V 50 Hz, Standard voltage, AC, Screw terminals, For use with: Shunt release PKZ0(4), PKE



**Part no. A-PKZ0(380V50HZ)
073189**

| General specifications | |
|--|---|
| Product name | Eaton Moeller® series PKZ Shunt release |
| Part no. | A-PKZ0(380V50HZ) |
| EAN | 4015080731894 |
| Product Length/Depth | 68 millimetre |
| Product height | 90 millimetre |
| Product width | 24 millimetre |
| Product weight | 0.129 kilogram |
| Certifications | UL 508 CSA Class No.: 3211-05 CSA File No.: 165628 CSA-C22.2 No. 14 CE UL UL Category Control No.: NLRV UL File No.: E36332 CSA IEC/EN 60947-4-1 |
| Product Tradename | A-PKZ0 |
| Product Type | Accessory |
| Product Sub Type | Shunt release |
| Catalog Notes | Cannot be combined with U-PKZ0 undervoltage release Cannot be combined with undervoltage release U-PKZ0 |
| Features & Functions | |
| Electric connection type | Screw connection |
| General information | |
| Product category | Accessories |
| Suitable for | Motor safety switch |
| Used with | Motor protective circuit-breaker |
| Voltage type | AC |
| Ambient conditions, mechanical | |
| Mounting position | Can be fitted to left side of the motor protection switch |
| Climatic environmental conditions | |
| Ambient operating temperature - min | -25 °C |
| Ambient operating temperature - max | 55 °C |
| Terminal capacities | |
| Terminal capacity (solid/flexible with ferrule) | 2 x (0.75 - 2.5) mm ² 1 x (0.75 - 2.5) mm ² |
| Terminal capacity (solid/stranded AWG) | 1 x (18 - 14) 2 x (18 - 14) |
| Electrical rating | |
| Operational voltage | 0.7- 1.1 x Us (DC) 0.7 - 1.1 x Us (AC) 0.7- 1.1 x Us (alternating voltage) |
| Rated operational voltage (Ue) at AC - min | 42 V |
| Rated operational voltage (Ue) at AC - max | 480 V |
| Rated operational voltage (Ue) at DC - min | 24 V |
| Rated operational voltage (Ue) at DC - max | 250 V |
| Magnet system | |
| Rated control supply voltage (Us) at AC, 50 Hz - min | 380 V |
| Rated control supply voltage (Us) at AC, 50 Hz - max | 380 V |
| Rated control supply voltage (Us) at AC, 60 Hz - min | 0 V |

| | | |
|--|--|--|
| Rated control supply voltage (Us) at AC, 60 Hz - max | | 0 V |
| Rated control supply voltage (Us) at DC - min | | 0 V |
| Rated control supply voltage (Us) at DC - max | | 0 V |
| Contacts | | |
| Number of contacts (change-over contacts) | | 0 |
| Number of contacts (normally closed contacts) | | 0 |
| Number of contacts (normally open contacts) | | 0 |
| Power consumption | | |
| Power consumption, pick-up, 50 Hz | | 5 VA, Pull-in power, Coil in a cold state and 1.0 x Us |
| Power consumption, pick-up, 60 Hz | | 5 VA, Pull-in power, Coil in a cold state and 1.0 x Us |
| Power consumption, sealing, 50 Hz | | 3 VA, Coil in a cold state and 1.0 x Us |
| Power consumption, sealing, 60 Hz | | 3 VA, Coil in a cold state and 1.0 x Us |
| Design verification | | |
| Equipment heat dissipation, current-dependent Pvid | | 0 W |
| Heat dissipation capacity Pdis | | 0 W |
| Heat dissipation per pole, current-dependent Pvid | | 0 W |
| Rated operational current for specified heat dissipation (In) | | 0 A |
| Static heat dissipation, non-current-dependent Pvs | | 0.5 W |
| 10.2.2 Corrosion resistance | | Meets the product standard's requirements. |
| 10.2.3.1 Verification of thermal stability of enclosures | | Meets the product standard's requirements. |
| 10.2.3.2 Verification of resistance of insulating materials to normal heat | | Meets the product standard's requirements. |
| 10.2.3.3 Resist. of insul. mat. to abnormal heat/fire by internal elect. effects | | Meets the product standard's requirements. |
| 10.2.4 Resistance to ultra-violet (UV) radiation | | Meets the product standard's requirements. |
| 10.2.5 Lifting | | Does not apply, since the entire switchgear needs to be evaluated. |
| 10.2.6 Mechanical impact | | Does not apply, since the entire switchgear needs to be evaluated. |
| 10.2.7 Inscriptions | | Meets the product standard's requirements. |
| 10.3 Degree of protection of assemblies | | Does not apply, since the entire switchgear needs to be evaluated. |
| 10.4 Clearances and creepage distances | | Meets the product standard's requirements. |
| 10.5 Protection against electric shock | | Does not apply, since the entire switchgear needs to be evaluated. |
| 10.6 Incorporation of switching devices and components | | Does not apply, since the entire switchgear needs to be evaluated. |
| 10.7 Internal electrical circuits and connections | | Is the panel builder's responsibility. |
| 10.8 Connections for external conductors | | Is the panel builder's responsibility. |
| 10.9.2 Power-frequency electric strength | | Is the panel builder's responsibility. |
| 10.9.3 Impulse withstand voltage | | Is the panel builder's responsibility. |
| 10.9.4 Testing of enclosures made of insulating material | | Is the panel builder's responsibility. |
| 10.10 Temperature rise | | The panel builder is responsible for the temperature rise calculation. Eaton will provide heat dissipation data for the devices. |
| 10.11 Short-circuit rating | | Is the panel builder's responsibility. The specifications for the switchgear must be observed. |
| 10.12 Electromagnetic compatibility | | Is the panel builder's responsibility. The specifications for the switchgear must be observed. |
| 10.13 Mechanical function | | The device meets the requirements, provided the information in the instruction leaflet (IL) is observed. |

Technical data ETIM 9.0

| | | |
|---|---|------------------|
| Low-voltage industrial components (EG000017) / Shunt release (for power circuit breaker) (EC001023) | | |
| Electric engineering, automation, process control engineering / Low-voltage switch technology / Circuit breaker (LV < 1 kV) / Full load current trip (ecl@ss13-27-37-04-18 [AKF016018]) | | |
| Rated control supply voltage AC 50 Hz | V | 380 - 380 |
| Rated control supply voltage AC 60 Hz | V | 0 - 0 |
| Rated control supply voltage DC | V | 0 - 0 |
| Voltage type for actuating | | AC |
| Initial value of the undelayed short-circuit release - setting range | A | 0 |
| End value adjustment range undelayed short-circuit release | A | 0 |
| Power consumption | W | 0.5 |
| Type of electric connection | | Screw connection |
| Number of contacts as normally open contact | | 0 |

| | | | |
|---|--|--|-----|
| Number of contacts as normally closed contact | | | 0 |
| Number of contacts as change-over contact | | | 0 |
| Suitable for power circuit breaker | | | No |
| Suitable for off-load switch | | | No |
| Suitable for motor safety switch | | | Yes |
| Suitable for overload relay | | | No |