DATASHEET - +U-PKZ0(230V50HZ)

Undervoltage release PKZ0(4), PKE, AC, 230 V 50 Hz, Screw terminals, When ordered with basic unit



Part no.

+U-PKZ0(230V50HZ) 073250

General specifications	
Product name	Eaton Moeller® series U-PKZ0 Accessory Undervoltage Release
Part no.	+U-PKZ0(230V50HZ)
EAN	4015080732501
Product Length/Depth	68 millimetre
Product height	90 millimetre
Product width	24 millimetre
Product weight	0.129 kilogram
Certifications	UL Listed CSA-C22.2 No. 14 IEC 60947-4-1 CSA certified UL Category Control No.: NLRV UL 508 CSA Class No.: 3211-05 CSA File No.: 185628 CE marking UL File No.: E36332
Product Tradename	U-PKZ0
Product Type	Accessory
Product Sub Type	Undervoltage Release
Features & Functions	
Electric connection type	Screw connection
General information	
Suitable for	Motor safety switch
Voltage type	AC
Magnet system	
Rated control supply voltage (Us) at AC, 50 Hz - min	230 V
Rated control supply voltage (Us) at AC, 50 Hz - max	230 V
Rated control supply voltage (Us) at AC, 60 Hz - min	0 V
Rated control supply voltage (Us) at AC, 60 Hz - max	0 V
Rated control supply voltage (Us) at DC - min	0 V
Rated control supply voltage (Us) at DC - max	0 V
Contacts	
Number of contacts (change-over contacts)	0
Number of contacts (normally closed contacts)	0
Number of contacts (normally open contacts)	0

Technical data ETIM 9.0

Low-voltage industrial components (EG000017) / Under voltage coil (EC001022)

Electric engineering, automation, process control engineering / Low-voltage switch technology / Circuit breaker (LV < 1 kV) / Undervoltage trip (ecl@ss13-27-37-04-17 [AKF015018])				
Rated control supply voltage AC 50 Hz	V	230 - 230		
Rated control supply voltage AC 60 Hz	V	0 - 0		
Rated control supply voltage DC	V	0 - 0		
Voltage type for actuating		AC		
Type of electric connection		Screw connection		
Number of contacts as normally open contact		0		
Number of contacts as normally closed contact		0		
Number of contacts as change-over contact		0		
Delayed		No		
Suitable for power circuit breaker		No		

Suitable for off-load switch	No
Suitable for motor safety switch	Yes
Suitable for overload relay	No