## Indicator light, red, 230V neon lamp



Part no. L-PKZ0-RT(230V) 082157

General specifications	
Product name	Eaton Moeller® series L-PKZ0 Accessory Indicator light
Part no.	L-PKZ0-RT(230V)
EAN	4015080821571
Product Length/Depth	50 millimetre
Product height	17 millimetre
Product width Product width	17 millimetre
Product weight	0.01 kilogram
Compliances	CE
Product Tradename	L-PKZ0
Product Type	Accessory
Product Sub Type	Indicator light
eatures & Functions	
Bezel color	Other
Bezel material	Plastic
Color	Red
Electric connection type	Flat plug-in connection
Fitted with:	Light source
Lens color	Red
General information	
Degree of protection	IP65 NEMA Other
Opening diameter	16 mm
Voltage type	AC/DC
Climatic environmental conditions	
Ambient operating temperature - min	-25 °C
Ambient operating temperature - max	55 °C
lectrical rating	
Rated control supply voltage	110 - 230 V (Us)
Rated operational voltage (Ue) - min	110 V
Rated operational voltage (Ue) - max	230 V
Rated operational voltage (Ue) at AC - min	110 V
Rated operational voltage (Ue) at AC - max	230 V
Design verification	
Equipment heat dissipation, current-dependent Pvid	0 W
Heat dissipation capacity Pdiss	0 W
Heat dissipation per pole, current-dependent Pvid	0 W
Rated operational current for specified heat dissipation (In)	0 A
Static heat dissipation, non-current-dependent Pvs	0.46 W
10.2.2 Corrosion resistance	Meets the product standard's requirements.
10.2.3.1 Verification of thermal stability of enclosures	Meets the product standard's requirements.
10.2.3.2 Verification of tremainstability of enclosures  10.2.3.2 Verification of resistance of insulating materials to normal heat	Meets the product standard's requirements.
10.2.3.3 Resist. of insul. mat. to abnormal heat/fire by internal elect. effects	Meets the product standard's requirements.
10.2.4 Resistance to ultra-violet (UV) radiation	Please enquire
10.2.5 Lifting	Does not apply, since the entire switchgear needs to be evaluated.
10.2.6 Mechanical impact	Does not apply, since the entire switchgear needs to be evaluated.
10.2.7 Inscriptions	Meets the product standard's requirements.
10.2.7 inscriptions  10.3 Degree of protection of assemblies	inicets the product standard s requirements.

10.4 Clearances and creepage distances	Meets the product standard's requirements.
10.5 Protection against electric shock	Does not apply, since the entire switchgear needs to be evaluated.
10.6 Incorporation of switching devices and components	Does not apply, since the entire switchgear needs to be evaluated.
10.7 Internal electrical circuits and connections	Is the panel builder's responsibility.
10.8 Connections for external conductors	Is the panel builder's responsibility.
10.9.2 Power-frequency electric strength	Is the panel builder's responsibility.
10.9.3 Impulse withstand voltage	Is the panel builder's responsibility.
10.9.4 Testing of enclosures made of insulating material	Is the panel builder's responsibility.
10.10 Temperature rise	The panel builder is responsible for the temperature rise calculation. Eaton will provide heat dissipation data for the devices.
10.11 Short-circuit rating	Is the panel builder's responsibility. The specifications for the switchgear must be observed.
10.12 Electromagnetic compatibility	Is the panel builder's responsibility. The specifications for the switchgear must be observed.
10.13 Mechanical function	The device meets the requirements, provided the information in the instruction leaflet (IL) is observed.

## **Technical data ETIM 9.0**

Low-voltage industrial components (EG000017) / Indicator light co	mplete (EC000272)		
Electric engineering, automation, process control engineering / Lo	w-voltage switch technology / C	Command	and alarm device / Indicator light complete (ecl@ss13-27-37-12-23 [AKF041019])
Number of indicator lights			10
Colour lens			Red
Type of lamp socket			Other
With light source			Yes
Rated operating voltage Ue		V	110 - 230
Voltage type			AC/DC
Type of electric connection			Flat plug-in connection
Construction type lens			Rectangular
Type of lens			Flat
Hole diameter		mm	16
Nidth opening		mm	0
Height opening		mm	0
With front ring			No
Material front ring			Plastic
Colour front ring			Other
Degree of protection (IP)			IP65
Degree of protection (NEMA)			Other