DATASHEET - 135TQ25



Button plate for push-button, Inscription: RECHTS, 25 x 25

Part no.135T025Catalog No.093527Alternate Catalog135T025



Similar to illustration

Delivery program

Product range	Accessories
Single unit/Complete unit	Single unit
Inscription	RECHTS
Colour, symbol	
Front dimensions	25 x 25
Connection to SmartWire-DT	no

Design verification as per IEC/EN 61439

No.

besign vermoution as per ind, in orthos			
Technical data for design verification			
Rated operational current for specified heat dissipation	In	А	0
Heat dissipation per pole, current-dependent	P _{vid}	W	0
Equipment heat dissipation, current-dependent	P _{vid}	W	0
Static heat dissipation, non-current-dependent	P _{vs}	W	0
Heat dissipation capacity	P _{diss}	W	0
Operating ambient temperature min.		°C	-25
Operating ambient temperature max.		°C	60
IEC/EN 61439 design verification			
10.2 Strength of materials and parts			
10.2.2 Corrosion resistance			Meets the product standard's requirements.
10.2.3.1 Verification of thermal stability of enclosures			Meets the product standard's requirements.
10.2.3.2 Verification of resistance of insulating materials to normal heat			Meets the product standard's requirements.
10.2.3.3 Verification of resistance of insulating materials to abnormal heat and fire due to internal electric effects			Meets the product standard's requirements.
10.2.4 Resistance to ultra-violet (UV) radiation			Please enquire
10.2.5 Lifting			Does not apply, since the entire switchgear needs to be evaluated.
10.2.6 Mechanical impact			Does not apply, since the entire switchgear needs to be evaluated.
10.2.7 Inscriptions			Meets the product standard's requirements.
10.3 Degree of protection of ASSEMBLIES			Does not apply, since the entire switchgear needs to be evaluated.
10.4 Clearances and creepage distances			Meets the product standard's requirements.
10.5 Protection against electric shock			Does not apply, since the entire switchgear needs to be evaluated.
10.6 Incorporation of switching devices and components			Does not apply, since the entire switchgear needs to be evaluated.
10.7 Internal electrical circuits and connections			Is the panel builder's responsibility.
10.8 Connections for external conductors			Is the panel builder's responsibility.
10.9 Insulation properties			
10.9.2 Power-frequency electric strength			Is the panel builder's responsibility.
10.9.3 Impulse withstand voltage			Is the panel builder's responsibility.
10.9.4 Testing of enclosures made of insulating material			Is the panel builder's responsibility.
10.10 Temperature rise			Not applicable.
10.11 Short-circuit rating			Is the panel builder's responsibility. The specifications for the switchgear must be observed.

10.13 Mechanical function

Is the panel builder's responsibility. The specifications for the switchgear must be observed.

The device meets the requirements, provided the information in the instruction leaflet (IL) is observed.

Technical data ETIM 7.0

Low-voltage industrial components (EG000017) / Legend plate for control circuit devices (EC000621)

Electric engineering, automation, process control engineering / Low-voltage switch technology / Command and alarm device / Button plate for command and alarm devices (ecl@ss10.0.1-27-37-12-24 [AKF042014])						
Shape			Square			
Construction type			Flat			
Colour			Black			
Imprint			Other			
Imprint ISO symbols			Other			
Engravable			No			
Programme diameter		mm	16			
Width		mm	25			
Height		mm	0			
Outer diameter		mm	0			
Suitable for push button			Yes			
Suitable for illuminated push buttons			No			
Suitable for indicator light			No			
Mushroom head push button			No			
Suitable for signalling lamp			No			
Suitable for selector switch			No			

Approvals

North America Certification

UL/CSA certification not required

Assets (links)

Declaration of CE Conformity 00002898 **Instruction Leaflets** IL04716016Z2018_05

Additional product information (links)

IL04716016Z (AWA1160-1429) Mounting of components

ftp://ftp.moeller.net/DOCUMENTATION/AWA_INSTRUCTIONS/IL04716016Z2018_05.pdf IL04716016Z (AWA1160-1429) Mounting of components