



Programming cable for EC4P, XC100, XC200, 2m

Part no. EU4A-RJ45-CAB1
Catalog No. 106726
EL-Nummer (Norway) 4519606

Delivery program

Description			SUB-D, 9 pole, serial
Description			Programming cable for XC, EC4P, EU5C-SWD-CAN, EU5C-SWD-DP, EU5C-SWD-EIP-MODTCP
Function			For transferring the user program to the PLC or for diagnosing SmartWire-DT networks
Length		m	2
For use with			EC4P XC100 XC200 XC121 easy800-SWD EU5C

Design verification as per IEC/EN 61439

Technical data for design verification			
Rated operational current for specified heat dissipation	I_n	A	0
Heat dissipation per pole, current-dependent	P_{vid}	W	0
Equipment heat dissipation, current-dependent	P_{vid}	W	0
Static heat dissipation, non-current-dependent	P_{vs}	W	0
Heat dissipation capacity	P_{diss}	W	0
Operating ambient temperature min.		°C	0
Operating ambient temperature max.		°C	55
IEC/EN 61439 design verification			
10.2 Strength of materials and parts			
10.2.2 Corrosion resistance			
Meets the product standard's requirements.			
10.2.3.1 Verification of thermal stability of enclosures			
Meets the product standard's requirements.			
10.2.3.2 Verification of resistance of insulating materials to normal heat			
Meets the product standard's requirements.			
10.2.3.3 Verification of resistance of insulating materials to abnormal heat and fire due to internal electric effects			
Meets the product standard's requirements.			
10.2.4 Resistance to ultra-violet (UV) radiation			
Meets the product standard's requirements.			
10.2.5 Lifting			
Does not apply, since the entire switchgear needs to be evaluated.			
10.2.6 Mechanical impact			
Does not apply, since the entire switchgear needs to be evaluated.			
10.2.7 Inscriptions			
Meets the product standard's requirements.			
10.3 Degree of protection of ASSEMBLIES			
Meets the product standard's requirements.			
10.4 Clearances and creepage distances			
Meets the product standard's requirements.			
10.5 Protection against electric shock			
Does not apply, since the entire switchgear needs to be evaluated.			
10.6 Incorporation of switching devices and components			
Does not apply, since the entire switchgear needs to be evaluated.			
10.7 Internal electrical circuits and connections			
Is the panel builder's responsibility.			
10.8 Connections for external conductors			
Is the panel builder's responsibility.			
10.9 Insulation properties			
10.9.2 Power-frequency electric strength			
Is the panel builder's responsibility.			
10.9.3 Impulse withstand voltage			
Is the panel builder's responsibility.			
10.9.4 Testing of enclosures made of insulating material			
Is the panel builder's responsibility.			
10.10 Temperature rise			
The panel builder is responsible for the temperature rise calculation. Eaton will provide heat dissipation data for the devices.			
10.11 Short-circuit rating			
Is the panel builder's responsibility.			
10.12 Electromagnetic compatibility			
Is the panel builder's responsibility.			
10.13 Mechanical function			
The device meets the requirements, provided the information in the instruction leaflet (IL) is observed.			

Technical data ETIM 7.0

PLC's (EG000024) / PLC connection cable (EC000237)		
Electric engineering, automation, process control engineering / Control / Programmable logic control (SPS) / SPS cable connection (ecI@ss10.0.1-27-24-22-20 [AFR598003])		
Function		PLC - PC
Length	m	2
Suitable for input board PLC		Yes
Suitable for output card PLC		Yes
Suitable for digital signals		Yes
Suitable for analogue signals		Yes
Type of electrical connection, field-sided		Connection plug board
Type of electrical connection, box-sided		Connection plug board
Number of poles		8

Approvals

North America Certification		Request filed for UL and CSA
Specially designed for North America		No
Current Limiting Circuit-Breaker		No

Additional product information (links)

Product overview (WEB)	http://www.eaton.eu/ec4p
------------------------	---