

Terminal plate, 3p, 95-300mm², 560A

Part no. BBA-TP3/300
107185
EL Number 2465023
(Norway)

General specifications		
Product name		Eaton xEffect SASY 60i terminal plate
Part no.		BBA-TP3/300
EAN		4015081069484
Product Length/Depth		260 millimetre
Product height		210 millimetre
Product width		125 millimetre
Product weight		1.991 kilogram
Compliances		RoHS conform
Product Tradename		xEffect SASY 60i
Product Type		Busbar system component
Product Sub Type		Terminal plate
Delivery program		
Type		60 mm system Connection
Technical Data - Electrical		
Rated operation current (Ie)		560 A
Rated operational current		560 A
Rated operational current (Ie) - max		560 A
Creepage resistance		CTI 200
Technical Data - Mechanical		
Material		Silicon free, chlorine free
Busbar thickness - min		5 mm
Busbar thickness - max		10 mm
Busbar width - min		12 mm
Busbar width - max		30 mm
Terminal capacity (conductor)		95 mm ² - 300 mm ² MCM 300 - MCM 600
Conductor cross section - max		300 mm ²
Width clamp		240 mm
Design verification as per IEC/EN 61439 - technical data		
Temperature resistance		Temperature resistant to 120 °C
Additional information		
Features		Self-extinguishing acc. UL 94
Functions		Connections Connection kit
Special features		Pole pitch adjustable Fixing direct over busbar terminals Including shroud with adjustable width Looping is possible
Suitable for		Flat rail Three-pole Round conductor connection Sector conductor connection Strip conductor connection
Used with		25 mm x 5/10 mm rail Double T profile 30 mm x 5/10 mm rail 20 mm x 5/10 mm rail 60 mm system Connection

Technical data ETIM 9.0

Busbar thickness		mm	5 - 10
Busbar width		mm	12 - 30
Suitable for			Flat rail
Width clamp		mm	240
Max. conductor cross section		mm ²	300
Max. rated operation current I _e		A	560
Suitable for round conductor connection			Yes
Suitable for sector conductor connection			Yes
Suitable for strip conductor connection			Yes