



Distribution cabinet, HxWxD=1600x425x300mm, IP40

Part no. XVTL-BF-4/3/16
Catalog No. 114386

EL-Nummer (Norway) 0002459856

Design verification as per IEC/EN 61439

Technical data for design verification			
Heat dissipation, at an ambient temperature of 35°C, delta T: 20 degrees in top of the enclosure, calculated as per IEC 60890			
Individual enclosure, free-standing	P _V	W	102
Starting enclosure, free-standing	P _V	W	86
Middle enclosure, free-standing	P _V	W	75
Individual enclosure for wall mounting	P _V	W	82
Starting enclosure for wall mounting	P _V	W	73
Middle enclosure for wall mounting	P _V	W	66
Heat dissipation, at an ambient temperature of 35°C, delta T: 35 degrees in top of the enclosure, calculated as per IEC 60890			
Individual enclosure, free-standing	P _V	W	205
Starting enclosure, free-standing	P _V	W	173
Middle enclosure, free-standing	P _V	W	151
Individual enclosure for wall mounting	P _V	W	165
Starting enclosure for wall mounting	P _V	W	146
Middle enclosure for wall mounting	P _V	W	132
IEC/EN 61439 design verification			
10.2 Strength of materials and parts			
10.2.2 Corrosion resistance			Meets the product standard's requirements.
10.2.3.1 Verification of thermal stability of enclosures			Meets the product standard's requirements.
10.2.3.2 Verification of resistance of insulating materials to normal heat			Not applicable.
10.2.3.3 Verification of resistance of insulating materials to abnormal heat and fire due to internal electric effects			Not applicable.
10.2.4 Resistance to ultra-violet (UV) radiation			Not relevant to indoor installations.
10.2.5 Lifting			Met; assembled and secured as per the latest applicable instruction leaflet.
10.2.6 Mechanical impact			IK10
10.2.7 Inscriptions			Meets the product standard's requirements.
10.3 Degree of protection of ASSEMBLIES			IP40
10.4 Clearances and creepage distances			Is the panel builder's responsibility.
10.5 Protection against electric shock			< 0.1 Ω; meets the product standard's requirements.
10.6 Incorporation of switching devices and components			Is the panel builder's responsibility.
10.7 Internal electrical circuits and connections			Is the panel builder's responsibility.
10.8 Connections for external conductors			Is the panel builder's responsibility.
10.9 Insulation properties			
10.9.2 Power-frequency electric strength			U _i = 690 V AC
10.9.3 Impulse withstand voltage			6 kV
10.9.4 Testing of enclosures made of insulating material			Does not apply to metal enclosures.
10.10 Temperature rise			The panel builder is responsible for the temperature rise calculation. Eaton will provide heat dissipation data for the devices.
10.11 Short-circuit rating			Is the panel builder's responsibility.
10.12 Electromagnetic compatibility			Is the panel builder's responsibility.

10.13 Mechanical function		Meets the product standard's requirements.
---------------------------	--	--

Technical data ETIM 7.0

Cabinet enclosures (EG000011) / Enclosure/switchgear cabinet (empty) (EC000261)			
Electric engineering, automation, process control engineering / Electrical cabinet, housing, rack / Electrical cabinet (empty) / Electrical cabinet (ecl@ss10.0.1-27-18-01-01 [AGZ056016])			
Width		mm	425
Height		mm	1600
Depth		mm	308.5
Material			Steel
Material quality			Other
Surface finishing			Powder coating
Colour			Grey
RAL-number			7035
With mounting plate			No
Mounting plate depth-adjustable			Yes
Number of locks			1
Floor installation possible			Yes
Wall fastening possible			Yes
Wall build in			No
Pole fastening			No
Tackable			Yes
Number of doors			1
Suitable for metrical mounting			Yes
Suitable for outdoor set-up			No
Pitched roof			No
EMC-version			Yes
With glazed door			No
With ventilation door			No
With backside door			No
Impact strength			IK10
Degree of protection (IP)			IP40
Degree of protection (NEMA)			