

**LED element, for combination with RMQ-Titan operating elements
M22-..., Front fixing, red**

Part no. M22-SWD-LED-R
115969
EL Number 4355005
(Norway)

General specifications	
Product name	Eaton Moeller® series M22 LED element
Part no.	M22-SWD-LED-R
EAN	4015081157099
Product Length/Depth	45 millimetre
Product height	42 millimetre
Product width	10 millimetre
Product weight	0.009 kilogram
Certifications	CSA EN 50178 UL File No.: E29184 UL Category Control No.: NKCR CSA Class No.: 3211-07 UL CSA File No.: 2324643 IEC/EN 61131-2
Product Tradename	M22
Product Type	LED element
Product Sub Type	None
Features & Functions	
Fitted with:	Light source
Functions	For combination with RMQ-Titan operating elements M22-...
Light color	Red
General information	
Degree of protection	IP20
Overvoltage category	Not applicable
Pollution degree	2
Voltage type	DC
Ambient conditions, mechanical	
Constant acceleration	1 g, 8.4 - 150 Hz, according to IEC/EN 61131-2, Vibrations
Constant amplitude	3,5 mm, 5 - 8.4 Hz, according to IEC/EN 61131-2, Vibrations
Drop and topple	50 mm Drop height, Drop to IEC/EN 60068-2-31
Height of fall (IEC/EN 60068-2-32) - max	0.3 m
Mounting position	As required
Shock resistance	15 g, Mechanical, according to IEC/EN 60068-2-27, Half-sinusoidal shock 11 ms, 9 Impacts
Climatic environmental conditions	
Ambient operating temperature - min	-30 °C
Ambient operating temperature - max	70 °C
Environmental conditions	Condensation: prevent with appropriate measures
Relative humidity	9 - 95 % (non-condensing, IEC/EN 60068-2-30)
Electro magnetic compatibility	
Air discharge	8 kV, according to IEC 61131-2, level 3, ESD
Burst impulse	2 kV, Supply cable, according to IEC/EN 61131-2, Level 3 1 kV, SmartWire-DT cable, according to IEC/EN 61131-2, Level 3
Contact discharge	4 kV, according to IEC/EN 61131-2, Level 2, ESD
Electromagnetic fields	1 V/m at 2.0 - 2.7 GHz (according to IEC/EN 61131-2:2008) 10 V/m at 80 - 1000 MHz (according to IEC/EN 61131-2:2008) 3 V/m at 1.4 - 2 GHz (according to IEC/EN 61131-2:2008)
Radiated RFI	10 V (IEC/EN 61131-2:2008, Level 3)
Radio interference class	Class A (EN 55011)

Electrical rating		
Rated operational voltage (Ue) at AC - max		0 V
Rated operational voltage (Ue) at AC - min		0 V
Rated operational voltage (Ue) at DC - max		30 V
Rated operational voltage (Ue) at DC - min		30 V
Communication		
Connection		SmartWire-DT plug connector SWD4-8SF2-5
Connection to SmartWire-DT		Yes
Connection type		Front fixing SWD: Plug, 8-pole
LED indicator		Status indication of SmartWire-DT network: Green LED
Station		SmartWire-DT slave, SmartWire-DT network
Design verification		
Equipment heat dissipation, current-dependent Pvid		0 W
Heat dissipation capacity Pdis		0 W
Heat dissipation per pole, current-dependent Pvid		0 W
Rated operational current for specified heat dissipation (In)		0 A
Static heat dissipation, non-current-dependent Pvs		0.3 W
10.2.2 Corrosion resistance		Meets the product standard's requirements.
10.2.3.1 Verification of thermal stability of enclosures		Meets the product standard's requirements.
10.2.3.2 Verification of resistance of insulating materials to normal heat		Meets the product standard's requirements.
10.2.3.3 Resist. of insul. mat. to abnormal heat/fire by internal elect. effects		Meets the product standard's requirements.
10.2.4 Resistance to ultra-violet (UV) radiation		Meets the product standard's requirements.
10.2.5 Lifting		Does not apply, since the entire switchgear needs to be evaluated.
10.2.6 Mechanical impact		Does not apply, since the entire switchgear needs to be evaluated.
10.2.7 Inscriptions		Meets the product standard's requirements.
10.3 Degree of protection of assemblies		Does not apply, since the entire switchgear needs to be evaluated.
10.4 Clearances and creepage distances		Meets the product standard's requirements.
10.5 Protection against electric shock		Does not apply, since the entire switchgear needs to be evaluated.
10.6 Incorporation of switching devices and components		Does not apply, since the entire switchgear needs to be evaluated.
10.7 Internal electrical circuits and connections		Is the panel builder's responsibility.
10.8 Connections for external conductors		Is the panel builder's responsibility.
10.9.2 Power-frequency electric strength		Is the panel builder's responsibility.
10.9.3 Impulse withstand voltage		Is the panel builder's responsibility.
10.9.4 Testing of enclosures made of insulating material		Is the panel builder's responsibility.
10.10 Temperature rise		The panel builder is responsible for the temperature rise calculation. Eaton will provide heat dissipation data for the devices.
10.11 Short-circuit rating		Is the panel builder's responsibility. The specifications for the switchgear must be observed.
10.12 Electromagnetic compatibility		Is the panel builder's responsibility. The specifications for the switchgear must be observed.
10.13 Mechanical function		The device meets the requirements, provided the information in the instruction leaflet (IL) is observed.

Technical data ETIM 9.0

Low-voltage industrial components (EG000017) / Lamp holder block for control circuit devices (EC000204)

Electric engineering, automation, process control engineering / Low-voltage switch technology / Command and alarm device / Bulb socket block for command and alarm devices (ecl@ss13-27-37-12-09 [AKF027019])

Transformer integrated		No
With integrated voltage decreasing resistor		No
With light source		Yes
With integrated diode		No
Lamp holder		None
Rated voltage Ue at AC 50 Hz	V	0 - 0
Rated voltage Ue at AC 60 Hz	V	0 - 0
Rated voltage Ue at DC	V	30 - 30
Voltage type for actuating		DC

Lamp type			LED
Connection type auxiliary circuit			Flat plug-in connection
Colour light source			Red
Type of fastening			Front fastening