

Cable interconnect frame IP54, HxWxD=200x600x320mm



**Part no.** BPZ-KR62/320  
**116288**  
**EL Number** 2460386  
**(Norway)**

General specifications		
Product name		Eaton xEnergy Basic base element
Part no.		BPZ-KR62/320
EAN		4015081160273
Product Length/Depth		325 millimetre
Product height		205 millimetre
Product width		605 millimetre
Product weight		7.84 kilogram
Compliances		RoHS conform
Product Tradename		xEnergy Basic
Product Type		Accessories
Product Sub Type		Base element
Delivery program		
Type		Additional equipment for floor-standing service distribution board IVS
Model		Base complete
Accessory/spare part type		Cable marshalling box
Color		Gray
Technical Data - Mechanical		
Unit type		Modular system
Surface finishing		With powder coating
Mounting method		Floor standing distribution board
Material		Steel Sheet steel
Degree of protection		IP54
Load capacity - max		350 kg
Housing material		Sheet steel
Suitable for enclosure building length/depth		320 mm
Suitable for enclosure building width		600 mm
Suitable for length/depth		320 mm
Suitable for width		600 mm
Additional information		
Functions		Additional equipment
RAL-number		7035
Special features		For total weight > 300 kg Cladding removable on all sides Can be fitted to top or bottom of the enclosure Supplied assembled Including fixing sundries Cable clamp rail not included as standard
Suitable for		Cable patch
Used with		Accessory Accessory consideration Service distribution board IVS Floor-standing enclosure

**Technical data ETIM 9.0**

Cabinet enclosures (EG000011) / Base/base element (enclosure/cabinet) (EC000721)		
Electric engineering, automation, process control engineering / Electrical cabinet, housing, rack / Base/plinth (electrical cabinet) / Base/base element (enclosure) (ecl@ss13-27-18-20-03 [ACN612016])		
Model		Base complete
Material		Steel

Colour		Grey
RAL-number (similar)		7035
Impact strength		Other
Max. load capacity	kg	350
Suitable for enclosure building width	mm	600
Suitable for enclosure building depth	mm	320
Suitable for aeration/de-aeration		No
Suitable for cable patch		Yes
Suitable for outdoor set-up		No
Width	mm	605
Height	mm	205
Depth	mm	325