

Indicator light, Flat, Screw connection, Lens Without lens, LED green, 230 V AC

Part no. **C22-L-XG-230**
121651

| General specifications | | |
|---|--|---|
| Product name | | Eaton Moeller® series C22 Indicator light |
| Part no. | | C22-L-XG-230 |
| EAN | | 4015081194650 |
| Product Length/Depth | | 56 millimetre |
| Product height | | 30 millimetre |
| Product width | | 30 millimetre |
| Product weight | | 0.015 kilogram |
| Certifications | | UL File No.: E29184 CSA-C22.2 No. 14-05 and 94-M91 UL 508 CSA certified VDE 0660 CE marking CSA File No.: 165628 CSA Class No.: 321103 UL Listed IEC/EN 60947-5-1 UL Category Control No.: NKCR |
| Product Tradename | | C22 |
| Product Type | | Indicator light |
| Product Sub Type | | None |
| Catalog Notes | | Lenses for indicator lights → accessories |
| Features & Functions | | |
| Bezel color | | Other |
| Bezel material | | Plastic |
| Design | | Flat |
| Electric connection type | | Screw connection |
| Fitted with: | | Front ring Light source |
| Lens color | | Without hood |
| Light color | | Green |
| General information | | |
| Connection to SmartWire-DT | | No |
| Degree of protection | | NEMA 4X, 13 IP67/IP69K |
| Mounting position | | As required |
| Opening diameter | | 22.5 mm |
| Overvoltage category | | III |
| Pollution degree | | 3 |
| Rated impulse withstand voltage (Uimp) | | 4000 V AC |
| Terminal capacity | | 2 x (0.5 - 1.5) mm ² , flexible with ferrules to DIN 46228 2 x (0.5 - 1.5) mm ² , solid |
| Tightening torque | | 0.8 Nm, Screw terminals |
| Type | | Indicator lights |
| Voltage type | | AC |
| Climatic environmental conditions | | |
| Ambient operating temperature - min | | -25 °C |
| Ambient operating temperature - max | | 70 °C |
| Climatic proofing | | Damp heat, constant, to IEC 60068-2-78 Damp heat, cyclic, to IEC 60068-2-30 |
| Electrical rating | | |
| Rated conditional short-circuit current (I _q) | | 1 kA |

| | | |
|--------------------------------------|--|-------|
| Rated insulation voltage (Ui) | | 250 V |
| Rated operational voltage (Ue) - min | | 230 V |
| Rated operational voltage (Ue) - max | | 230 V |

Technical data ETIM 9.0

| | | |
|--|----|------------------|
| Low-voltage industrial components (EG000017) / Indicator light complete (EC000272) | | |
| Electric engineering, automation, process control engineering / Low-voltage switch technology / Command and alarm device / Indicator light complete (ecl@ss13-27-37-12-23 [AKF041019]) | | |
| Number of indicator lights | | 1 |
| Colour lens | | Without hood |
| Type of lamp socket | | LED |
| With light source | | Yes |
| Rated operating voltage Ue | V | 230 - 230 |
| Voltage type | | AC |
| Type of electric connection | | Screw connection |
| Construction type lens | | Round |
| Type of lens | | Flat |
| Hole diameter | mm | 22.5 |
| Width opening | mm | 0 |
| Height opening | mm | 0 |
| With front ring | | Yes |
| Material front ring | | Plastic |
| Colour front ring | | Other |
| Degree of protection (IP) | | IP67/IP69K |
| Degree of protection (NEMA) | | 4X, 13 |