## **DATASHEET - CSAR3F3CY2202**



Connection cable, 3p, AC, coupling m12 angled, open end, L=2m



Part no. CSAR3F3CY2202 Catalog No. 136262 Alternate Catalog CSAR3F3CY2202

**Delivery program** 

Donvory program		
Basic function		Accessories
Accessories		Connecting cables
Length	mm	2000
Pin assignment		2 3 1 = Green 2 = Red/Black 3 = Red/White
Voltage type		AC
Number of poles		3 pole
Style output side		Cable end, open
Style input side		Coupling, angled
For use with		
For use with		AC sensors, 3 pole, M12

## Design verification as per IEC/EN 61439

Technical data for design verification		
Operating ambient temperature min.	°C	-25
Operating ambient temperature max.	°C	70

## **Technical data ETIM 7.0**

Technical uata Ethiyi 7.0			
Sensors (EG000026) / Sensor-actuator patch cord (EC001855)			
Electric engineering, automation, process control engineering / Cable, wire / Real control engineering / Cable, wire	ady-made data ca	ble / Asse	embled sensor actuator-line (ecl@ss10.0.1-27-06-03-11 [AFR601003])
Number of poles			3
Type of electrical connection, field-sided			M12
Type of plug-in contact, field sided			Female (bus)
Positioning cable feed, field-sided			Angled
Type of electrical connection, box-sided			Other
Type of plug-in contact, box-sided			
Positioning cable feed, box-sided			Other
Cable length		m	2
Material of cable sheath			Other
Halogen free			No
Colour cable sheath			Other
With LED indication			No
Screened			No
Type of cable			Multi-core
Vulcanize			No
Material contact body			Other
Material of contact surface			Other
Permitted cable outer temperature after assembling without vibration		°C	40 - 70
Permitted cable outer temperature during assembling/handling		°C	40 - 70
Rated current In		Α	0
Rated voltage		V	0
Continuity resistor		m0hm	0
Degree of protection (IP)			Other

Approvals

Product Standards CE marking