

## Connection cable, 3p, AC, coupling M12 flat, open end, L=10m

Part no. **CSAS3F3CY2210**  
**136267**

General specifications		
Product name		Eaton Moeller® series CSAS Accessory Connection cable
Part no.		CSAS3F3CY2210
EAN		4015081330607
Product Length/Depth		152.4 millimetre
Product height		44.45 millimetre
Product width		152.4 millimetre
Product weight		0.23 kilogram
Certifications		CE
Product Tradename		CSAS
Product Type		Accessory
Product Sub Type		Connection cable
Product Specification Details		
Ambient operating temperature - max		70 °C
Ambient operating temperature - min		-25 °C
Cable length		10 m
Cable sheath material		Other
Cable type		Multi-core Cable end, open, Output side Coupling, straight, Input side
Color cable sheath		Yellow
Contact body material		Other
Contact surface material		Other
Continuity resistor		0 mΩ
Degree of protection		Other
Electrical connection type (box-sided)		Other
Electrical connection type (field-sided)		M12
Nominal current		0 A
Number Of Poles		Three-pole
Permitted temperature of outer cable (assembled) without vibration - max		70 °C
Permitted temperature of outer cable (assembled) without vibration - min		40 °C
Permitted temperature of outer cable (assembling/handling) - max		70 °C
Permitted temperature of outer cable (assembling/handling) - min		40 °C
Plug-in contact type (box-sided)		Male (plug)
Plug-in contact type (field-sided)		Female (bus)
Positioning cable feed (box-sided)		Other
Positioning cable feed (field-sided)		Straight
Product category		Accessories
Rated operational voltage (Ue) - max		0 V
Type		Connecting cables
Voltage type		AC

## Technical data ETIM 9.0

Sensors (EG000026) / Sensor-actuator patch cord (EC001855)		
Electric engineering, automation, process control engineering / Cable, wire / Ready-made data cable / Assembled sensor/actuator adapter, with cable (ecl@ss13-27-06-03-13 [AFR625008])		
Number of poles		3
Type of electrical connection, field-sided		M12
Type of plug-in contact, field sided		Female (bus)
Positioning cable feed, field-sided		Straight

Type of electrical connection, box-sided		Other
Type of plug-in contact, box-sided		Male (plug)
Positioning cable feed, box-sided		Other
Cable length	m	10
Material of cable sheath		Other
Halogen free		No
Colour cable sheath		Yellow
With LED indication		No
Screened		No
Cable type		Multi-core
Vulcanize		No
Material contact body		Other
Material of contact surface		Other
Permitted cable outer temperature after assembling without vibration	°C	40 - 70
Permitted cable outer temperature during assembling/handling	°C	40 - 70
Rated current I <sub>n</sub>	A	0
Rated voltage	V	0
Continuity resistance	mOhm	0
Degree of protection (IP)		Other