

Busbar adapter, 4p, for NZM3, 630A, UL508



**Part no.** NZM3-4-XAD630  
**138389**  
**EL Number** 1718010  
**(Norway)**

General specifications		
Product name		Eaton xEffect SASY 60i MCCB adapter
Part no.		NZM3-4-XAD630
EAN		4015081351695
Product Length/Depth		35 millimetre
Product height		300 millimetre
Product width		185 millimetre
Product weight		3.5 kilogram
Compliances		RoHS conform
Product Tradename		xEffect SASY 60i
Product Type		Busbar system component
Product Sub Type		MCCB adapter
Delivery program		
Type		60 mm system Busbar adapters for NZM
Nominal current		630 A
Number of poles		Four-pole
Technical Data - Electrical		
Voltage rating at AC		690 V AC
Rated operation current (Ie)		630 A
Electric connection type		Other
Creepage resistance		CTI 200
Technical Data - Mechanical		
Rail width		30 mm
Busbar distance		60 mm
Busbar thickness - min		5 mm
Busbar thickness - max		10 mm
Busbar adapter width		185 mm
Adapter width		185 mm
Design verification as per IEC/EN 61439 - technical data		
Temperature resistance		Up to 120 °C
Additional information		
Features		Self-extinguishing acc. UL 94
Functions		Busbar adapters for NZM Component adapter for circuit breakers and switch-disconnector
Suitable for		Surface mounting on flat copper busbars 12 – 30 x 5 – 10, double T and triple T profile
Used with		NZM3(-4), PN3(-4), N3(-4)

Technical data ETIM 9.0

Low-voltage industrial components (EG000017) / Busbar adapter (EC001531)		
Electric engineering, automation, process control engineering / Low-voltage switch technology / Busbar trunking system (LV circuitry) / Busbar adapter (low-voltage switching technology) (ecl@ss13-27-37-03-04 [ACN951016])		
Mounting rail armament		None
Type of electric connection		Other
Rated current In	A	630
Min. busbar thickness	mm	5
Max. busbar thickness	mm	10
Width of the adapter	mm	185

Rail width	mm	30
Busbar distance	mm	60