



Analog output module XI/ON, 24 V DC, 2AO (0-10V, +-10V)

Part no. **XN-2AO-U(-10/0...+10VDC)**

Catalog No. **140066**

EL-Nummer (Norway) **0004520623**

## Delivery program

Function			XI/ON I/O modules
Function			XN Slice module
Short Description			2 Analog outputs -10/0 to +10 V DC
For use with			XN-S3T-SBB XN-S3S-SBB

## Technical data

### General

Standards				EN 61000-6-2 EN 61000-6-4 EN 61131-2
Potential isolation				Yes, through optocoupler
Ambient temperature				
Ambient temperature, operation			°C	0 - +55
Storage, transport	9		°C	-25 - +85
Relative humidity				
Relative humidity				5 - 95 % (indoor), Level RH-2, no condensation (for storage at 45°C)
Ambient conditions, mechanical				
Degree of Protection				IP20
Harmful gases			ppm	SO <sub>2</sub> : 10 (rel. humidity < 75%, no condensation) H <sub>2</sub> S: 1.0 (rel. humidity < 75 %,no condensation)
Vibration resistance, operating conditions				according to IEC/EN 60068-2-6
Mechanical shock resistance			g	according to IEC 60068-2-27
Continuous shock resistance (IEC/EN 60068-2-29)				According to IEC 60068-2-29
Drop and topple				According to IEC 60068-2-31, free fall according to IEC 60068-2-32
Electromagnetic compatibility (EMC)				
ESD		Air/contact discharge	kV	EN 61000-4-2
Electromagnetic fields		(0.08...1) / (1,4...2) / (2...2,7) GHz	V/m	EN 61100-4-2
Burst				EN 61100-4-4
Surge				EN 61100-4-5
Radiated RFI			V	EN 61100-4-6
Emitted interference (radiated, high frequency)		(30...230 MHz) / (230...1000 MHz)	dB	EN 55016-2-3
Voltage fluctuations/voltage dips				EN 61131-2
Type test				to EN 61131-2
Approvals				CE, cULus
Other technical data (sheet catalogue)				Technical Data

### Analog input modules

Measured variables				Voltage
Channels			Number	2

Rated voltage through supply terminal	$U_L$		24 V DC
Rated current consumption from supply terminal	$I_L$	mA	50
Rated current consumption from module bus	$I_{MB}$	mA	$\leq 43$
Heat dissipation		W	normally 1
Offset error		%	0.1
Linearity		%	0.1
Basic error limit at 23 °C		%	0.2
Repetition accuracy (deviation)		%	0.05
Temperature coefficient			300 ppm/°C of full scale
Measured value representation			16-bit signed integer 12-bit signed integer left-justified 12-bit full range left-justified

### Analog output modules

Measured variables			Voltage
Channels		Number	2
Rated voltage through supply terminal	$U_L$		24 V DC
Rated current consumption from supply terminal	$I_L$	mA	50
Rated current consumption from module bus	$I_{MB}$	mA	$\leq 43$
Heat dissipation		W	normally 1
Output voltage		V DC	-10/0...+10
Load resistance			
Resistive load		$\Omega$	> 1000
Capacitive load		$\mu F$	>1
Short-circuit current		mA	40
Transfer frequency		Hz	100
Offset error		%	0.1
Linearity		%	0.1
Basic error limit at 23 °C		%	0.2
Repetition accuracy (deviation)		%	0.05
Output ripple		%	0.02
Temperature coefficient			300 ppm/°C of full scale
Settling time			
Resistive load		ms	0.1
Inductive load		ms	0.5
Capacitive load		ms	0.5
Interference voltage suppression			Common-mode > 90 dB Differential-mode > 70 dB Crosstalk between the channels > -50 dB
Measured value representation			16-bit signed integer 12-bit signed integer left-justified 12-bit full range left-justified

### Digital outputs

Channels		Number	2
Rated voltage through supply terminal	$U_L$		24 V DC
Rated current consumption from the supply terminal (at load current = 0 mA)	$I_L$	mA	50
Rated current consumption from module bus	$I_{MB}$	mA	$\leq 43$
Power loss	P	W	Normally 1
Resistive load		$\Omega$	> 1000

### Digital inputs

Channels		Number	2
Rated voltage through supply terminal	$U_L$		24 V DC
Rated current consumption from supply terminal	$I_L$	mA	50
Rated current consumption from module bus	$I_{MB}$	mA	$\leq 43$
Heat dissipation		W	normally 1

### Relay modules

Rated voltage through supply terminal	$U_L$		24 V DC
Rated current consumption from supply terminal	$I_L$	mA	50

Rated current consumption from module bus	I <sub>MB</sub>	mA	≤ 43
Power loss	P	W	Normally 1

### Power supply module

Rated voltage through supply terminal	U <sub>L</sub>		24 V DC
Rated current consumption from supply terminal	I <sub>L</sub>	mA	50
Rated current consumption from module bus	I <sub>MB</sub>	mA	≤ 43
Power loss	P	W	1

### Counter module

Channels		Number	2
Rated voltage through supply terminal	U <sub>L</sub>		24 V DC
Rated current consumption from supply terminal	I <sub>L</sub>	mA	50
Rated current consumption from module bus	I <sub>MB</sub>	mA	≤ 43
Heat dissipation		W	normally 1

### Measuring modes

Temperature coefficient			300 ppm/°C of full scale
Number of parameter bits			6 (3 per channel)

### Interfaces

Rated voltage through supply terminal	U <sub>L</sub>		24 V DC
Rated current consumption from supply terminal	I <sub>L</sub>	mA	50
Rated current consumption from module bus	I <sub>MB</sub>	mA	≤ 43
Power loss	P	W	Normally 1
Number of parameter bytes			6 (3 per channel)

## Design verification as per IEC/EN 61439

Technical data for design verification			
Rated operational current for specified heat dissipation	I <sub>n</sub>	A	0
Heat dissipation per pole, current-dependent	P <sub>vid</sub>	W	0
Equipment heat dissipation, current-dependent	P <sub>vid</sub>	W	0
Static heat dissipation, non-current-dependent	P <sub>vs</sub>	W	1
Heat dissipation capacity	P <sub>diss</sub>	W	0
Operating ambient temperature min.		°C	0
Operating ambient temperature max.		°C	55
Degree of Protection			IP20
IEC/EN 61439 design verification			
10.2 Strength of materials and parts			
10.2.2 Corrosion resistance			
			Meets the product standard's requirements.
10.2.3.1 Verification of thermal stability of enclosures			
			Meets the product standard's requirements.
10.2.3.2 Verification of resistance of insulating materials to normal heat			
			Meets the product standard's requirements.
10.2.3.3 Verification of resistance of insulating materials to abnormal heat and fire due to internal electric effects			
			Meets the product standard's requirements.
10.2.4 Resistance to ultra-violet (UV) radiation			
			Meets the product standard's requirements.
10.2.5 Lifting			
			Does not apply, since the entire switchgear needs to be evaluated.
10.2.6 Mechanical impact			
			Does not apply, since the entire switchgear needs to be evaluated.
10.2.7 Inscriptions			
			Meets the product standard's requirements.
10.3 Degree of protection of ASSEMBLIES			
			Meets the product standard's requirements.
10.4 Clearances and creepage distances			
			Meets the product standard's requirements.
10.5 Protection against electric shock			
			Does not apply, since the entire switchgear needs to be evaluated.
10.6 Incorporation of switching devices and components			
			Does not apply, since the entire switchgear needs to be evaluated.
10.7 Internal electrical circuits and connections			
			Is the panel builder's responsibility.
10.8 Connections for external conductors			
			Is the panel builder's responsibility.
10.9 Insulation properties			
10.9.2 Power-frequency electric strength			
			Is the panel builder's responsibility.
10.9.3 Impulse withstand voltage			
			Is the panel builder's responsibility.
10.9.4 Testing of enclosures made of insulating material			
			Is the panel builder's responsibility.
10.10 Temperature rise			
			The panel builder is responsible for the temperature rise calculation. Eaton will provide heat dissipation data for the devices.

10.11 Short-circuit rating		Is the panel builder's responsibility.
10.12 Electromagnetic compatibility		Is the panel builder's responsibility.
10.13 Mechanical function		The device meets the requirements, provided the information in the instruction leaflet (IL) is observed.

## Technical data ETIM 7.0

PLC's (EG000024) / Fieldbus, decentr. periphery - analogue I/O module (EC001596)

Electric engineering, automation, process control engineering / Control / Field bus, decentralized peripheral / Field bus, decentralized peripheral - analogue I/O module (ec1@ss10.0.1-27-24-26-01 [BAA061014])


Supply voltage AC 50 Hz	V	0 - 0
Supply voltage AC 60 Hz	V	0 - 0
Supply voltage DC	V	20.4 - 28.8
Voltage type of supply voltage		DC
Input, current		No
Input, voltage		No
Input, resistor		No
Input, resistance thermometer		No
Input, thermocouple		No
Input signal, configurable		No
Resolution of the analogue inputs	Bit	0
Output, current		No
Output, voltage		Yes
Output signal configurable		Yes
Resolution of the analogue outputs	Bit	16
Number of analogue inputs		0
Number of analogue outputs		2
Analogue inputs configurable		Yes
Analogue outputs configurable		Yes
Number of HW-interfaces industrial Ethernet		0
Number of interfaces PROFINET		0
Number of HW-interfaces RS-232		0
Number of HW-interfaces RS-422		0
Number of HW-interfaces RS-485		0
Number of HW-interfaces serial TTY		0
Number of HW-interfaces parallel		0
Number of HW-interfaces Wireless		0
Number of HW-interfaces USB		0
Number of HW-interfaces other		1
Supporting protocol for TCP/IP		No
Supporting protocol for PROFIBUS		No
Supporting protocol for CAN		No
Supporting protocol for INTERBUS		No
Supporting protocol for ASI		No
Supporting protocol for KNX		No
Supporting protocol for MODBUS		No
Supporting protocol for Data-Highway		No
Supporting protocol for DeviceNet		No
Supporting protocol for SUCONET		No
Supporting protocol for LON		No
Supporting protocol for PROFINET IO		No
Supporting protocol for PROFINET CBA		No
Supporting protocol for SERCOS		No
Supporting protocol for Foundation Fieldbus		No
Supporting protocol for EtherNet/IP		No
Supporting protocol for AS-Interface Safety at Work		No
Supporting protocol for DeviceNet Safety		No

Supporting protocol for INTERBUS-Safety		No
Supporting protocol for PROFIsafe		No
Supporting protocol for SafetyBUS p		No
Supporting protocol for other bus systems		No
Radio standard Bluetooth		No
Radio standard WLAN 802.11		No
Radio standard GPRS		No
Radio standard GSM		No
Radio standard UMTS		No
IO link master		No
System accessory		Yes
Degree of protection (IP)		IP20
Degree of protection (NEMA)		
Type of electric connection		Screw-/spring clamp connection
Fieldbus connection over separate bus coupler possible		Yes
Rail mounting possible		Yes
Wall mounting/direct mounting		No
Front build in possible		No
Rack-assembly possible		No
Suitable for safety functions		No
Category according to EN 954-1		
SIL according to IEC 61508		None
Performance level acc. EN ISO 13849-1		None
Appendant operation agent (Ex ia)		No
Appendant operation agent (Ex ib)		No
Explosion safety category for gas		None
Explosion safety category for dust		None
Width	mm	12.6
Height	mm	74
Depth	mm	55.4

## Approvals

Product Standards		UL 508; CSA-C22.2 No. 142; IEC/EN 6113-2; CE marking
UL File No.		E205091
UL Category Control No.		NRAQ, NRAQ7
CSA File No.		UL report applies to both US and Canada
CSA Class No.		2252-01, 2252-81
North America Certification		UL recognized, certified by UL for use in Canada
Specially designed for North America		No
Current Limiting Circuit-Breaker		No
Degree of Protection		IEC: IP20, UL/CSA Type: -

## Dimensions



Dimensions

## Additional product information (links)

### Manual XI/ON analog I/O modules MN05002011Z

Handbuch XI/ON analoge E/A-Module  
MN05002011Z - Deutsch

[https://es-assets.eaton.com/DOCUMENTATION/AWB\\_MANUALS/MN05002011Z\\_DE.pdf](https://es-assets.eaton.com/DOCUMENTATION/AWB_MANUALS/MN05002011Z_DE.pdf)

Manual XI/ON analog I/O modules  
MN05002011Z - English

[https://es-assets.eaton.com/DOCUMENTATION/AWB\\_MANUALS/MN05002011Z\\_EN.pdf](https://es-assets.eaton.com/DOCUMENTATION/AWB_MANUALS/MN05002011Z_EN.pdf)

Technical Data

<http://ecat.moeller.net/flip-cat/?edition=HPLEN&startpage=14.111>