

Lightning current and surge arresters kit, TN-C kit, 3p



**Part no.** SPBT12-280/3  
**158330**  
**EL Number** 1609777  
**(Norway)**

| <b>General specifications</b>                         |  |   |
|---|--|---|
| Product name  |  | Eaton Moeller series xPole - SPBT12 Surge Protection Device |
| Part no.  |  | SPBT12-280/3  |
| EAN   |  | 4015081548880   |
| Product Length/Depth                                  |  | 86 millimetre   |
| Product height  |  | 69 millimetre   |
| Product width   |  | 52.5 millimetre   |
| Product weight  |  | 0.429 kilogram  |
| Compliances   |  | RoHS conform  |
| Product Tradename                                     |  | xPole - SPBT12  |
| Product Type  |  | Surge Protection Device                                     |
| Product Sub Type                                      |  | None  |
| <b>Delivery program</b>                               |  |   |
| Application   |  | Open areas<br>Residential buildings<br>Utility buildings    |
| Number of poles                                       |  | Three-pole  |
| Type  |  | Surge arrester  |
| <b>Technical Data - Electrical</b>                    |  |   |
| Voltage protection level                              |  | 1.5 kV  |
| Voltage protection level (DC+ - DC-)                  |  | 0 kV  |
| Voltage protection level (DC+/DC- - PE)               |  | 0 kV  |
| Voltage protection level (L-N)                        |  | 0 kV  |
| Voltage protection level (L-PE)                       |  | 1.5 kV  |
| Voltage protection level (N-PE)                       |  | 0 kV  |
| Nominal voltage at AC                                 |  | 280 V   |
| Nominal voltage at DC                                 |  | 0 V   |
| Continuous voltage at AC - max                        |  | 280 V   |
| Continuous voltage at DC - max                        |  | 0 V   |
| PV-voltage - max                                      |  | 0 V   |
| Lightning impulse current (10/350 µs)                 |  | 12.5 kA   |
| Follow current extinguishing capability               |  | 0 kA  |
| Signalling at the device                              |  | Optic   |
| Specific energy (W/R)                                 |  | 39.1 kJ/Ohm   |
| <b>Technical Data - Mechanical</b>                    |  |   |
| Frame   |  | 3 modular spacing   |
| Mounting method                                       |  | DIN rail (top hat rail) 35 mm                               |
| Conductor cross section (flexible, fine-strand) - max |  | 35 mm <sup>2</sup>  |
| Conductor cross section (solid, solid-strand) - max   |  | 25 mm <sup>2</sup>  |
| Degree of protection                                  |  | IP20  |
| <b>Additional information</b>                         |  |   |
| System configuration type                             |  | Other<br>TN-C-S<br>TN-C<br>TN<br>TN-S<br>TT                 |
| Test class  |  | Type 1 + 2  |

**Technical data ETIM 9.0**

## Earthing, lightning and surge protection (EG000021) / Combined arrester for power supply systems (EC001457)

Electric engineering, automation, process control engineering / Internal and external lightning protection / Combined SPD for energy and information technology / Energy and MSR technology (ecl@ss13-27-17-16-01 [AHE455002])

|  |  |                 |                               |
|--|--|-----------------|-------------------------------|
| System configuration DC  |  |                 | No                            |
| System configuration IT  |  |                 | No                            |
| System configuration TN  |  |                 | Yes                           |
| System configuration TN-C  |  |                 | Yes                           |
| System configuration TN-C-S  |  |                 | Yes                           |
| System configuration TN-S  |  |                 | Yes                           |
| System configuration TT  |  |                 | Yes                           |
| System configuration other   |  |                 | Yes                           |
| Number of poles  |  |                 | 3                             |
| Lightning impulse current (10/350 µs)                                      |  | kA              | 12.5                          |
| Max. continuous voltage AC   |  | V               | 280                           |
| Max. continuous voltage DC   |  | V               | 0                             |
| Nominal voltage AC   |  | V               | 280                           |
| Nominal voltage DC   |  | V               | 0                             |
| Max. PV-voltage  |  | V               | 0                             |
| Voltage protection level   |  | kV              | 1.5                           |
| Voltage protection level L-N   |  | kV              | 0                             |
| Voltage protection level L-PE  |  | kV              | 1.5                           |
| Voltage protection level N-PE  |  | kV              | 0                             |
| Voltage protection level (DC+ - DC-)                                       |  | kV              | 0                             |
| Voltage protection level (DC+/DC- - PE)                                    |  | kV              | 0                             |
| Follow current extinguishing capability                                    |  | kA              | 0                             |
| Specific energy (W/R)  |  | kJ/Ohm          | 39.1                          |
| Max. overcurrent protection device, parallel connection (fuse)             |  | A               | 0                             |
| Max. overcurrent protection device, series connection (fuse)               |  | A               | 160                           |
| Mounting method  |  |                 | DIN rail (top hat rail) 35 mm |
| Construction size  |  |                 | 3 modular spacing             |
| Max. conductor cross section solid (solid, stranded)                       |  | mm <sup>2</sup> | 25                            |
| Max. conductor cross section flexible (fine-strand)                        |  | mm <sup>2</sup> | 35                            |
| Remote signalling  |  |                 | No                            |
| Signalling at the device   |  |                 | Optical                       |
| Test class   |  |                 | Type 1 + 2                    |
| Integrated backup fuse   |  |                 | No                            |
| Energy-coordinated protection effect with regard to the terminal equipment |  |                 | No                            |
| Voltage switching spark gap technology                                     |  |                 | No                            |
| Overcurrent protected voltage tapping                                      |  |                 | No                            |
| Degree of protection (IP)  |  |                 | IP20                          |