



Plug-in surge arresters, 3-phase+N/BB, 460VAC, 20 kA

Part no. SPCT2-460-3+NPE/BB
Catalog No. 167632
Alternate Catalog No. SPCT2-460-3NPE/BB

Similar to illustration

Delivery program

Products	Surge arresters
Application field	Residential buildings Utility buildings Open areas

Technical data ETIM 7.0

Earthing, lightning and surge protection (EG000021) / Surge protection device for power supply systems (EC000941)			
Electric engineering, automation, process control engineering / Protection installation, device (electric) / Surge protection device (inner lightning protection) / Surge protection device for power supply systems (ecl@ss10.0.1-27-13-08-05 [ACN278011])			
System configuration DC			No
System configuration IT			Yes
System configuration TN			Yes
System configuration TN-C			No
System configuration TN-C-S			Yes
System configuration TN-S			Yes
System configuration TT			Yes
System configuration other			Yes
Number of conductors (without earthing)			3
Nominal discharge surge current (8/20)	kA		20
Nominal voltage AC	V		460
Nominal voltage DC	V		0
Short-circuit breaking capacity (Iscbr)	kA		0
Max. continuous voltage AC	V		460
Max. discharge surge current (8/20)	kA		40
Max. continuous voltage DC	V		0
Mounting method			DIN rail (top hat rail) 35 mm
Construction size			4 modular spacing
Max. PV-voltage	V		0
Voltage protection level	kV		2.2
Max. conductor cross section solid (solid, stranded)	mm ²		25
Max. conductor cross section flexible (fine-strand)	mm ²		35
Voltage protection level L-N	kV		0
Voltage protection level N-PE	kV		0
With remote signalling contact			No
Integrated backup fuse			No
Signalling at the device			Optic
Category type 2			Yes
Degree of protection (IP)			IP20