

Soft starter, 180 A, 200 - 690 V AC, Us= 24 V DC, with control unit and pump algorithm, for 690-V grids, Frame size T



Powering Business Worldwide™

**Part no.** S811+T18V3S

168986

**EL Number  
(Norway)**

4137470

General specifications		
Product name		Eaton S811 Soft starter
Part no.		S811+T18V3S
EAN		4015081654819
Product Length/Depth		164.4 millimetre
Product height		322.9 millimetre
Product width		194.4 millimetre
Product weight		18.6 kilogram
Certifications		CSA CE UL 508 GB14048 IEC/EN 60947-4-2 UL UL File No.: E202571 UL Category Control No.: NMFT CSA22.2-14-1995 CCC C-Tick CSA UL
Product Tradename		S811
Product Type		Soft starter
Product Sub Type		None
Catalog Notes		External solution required (reversing contactor) Regulator supply: External supply voltage Terminal blocks for the terminals are required for frame sizes T, U, and V -> Accessories
Features & Functions		
Fault memory		10 Faults
Fitted with:		Motor overload protection Internal bypass Display Internal bypass contacts
Functions		Overload monitoring Soft start function Suppression of closing transients Suppression of DC components for motors Min. ramp time 1 s - fast switching (semiconductor contactor) Potential isolation between power and control sections Current limitation Underload monitoring Single direction
Interfaces		Modbus RTU (built-in)
General information		
Class		Adjustable
Connection to SmartWire-DT		No
Degree of protection		IP20 NEMA Other
Frame size		T
Mains voltage - min		200 V
Mains voltage - max		690 V
Mounting position		As required
Overvoltage category		II
Pollution degree		3
Radio interference class		Class A (EN 55011)
Rated impulse withstand voltage (Uimp)		4000 V
Shock resistance		15 g, Mechanical

Startup class	CLASS 30 (6 x I# for 30 s) CLASS 10 (star-delta replacement) CLASS 20 (heavy starting duty 3 x I# for 45 s)
Suitable for	Branch circuits, not as BCPD, (UL/CSA)
Type	Soft starter for three-phase loads, with control unit and pump algorithm, for 690-V grids
Voltage type	DC
<b>Climatic environmental conditions</b>	
Altitude	Above 2000 m with 0.5 % derating per 100 m Max. 2000 m
Ambient operating temperature - min	-30 °C
Ambient operating temperature - max	50 °C
Ambient storage temperature - min	-50 °C
Ambient storage temperature - max	70 °C
Climatic proofing	Damp heat, cyclic, to IEC 60068-2-30 Damp heat, constant, to IEC 60068-2-3
<b>Main conducting paths</b>	
Overload cycle	AC-53a: 4.0 - 32: 99 - 3
Rated operational current (Ie) at AC-53	180 A
Rated operational voltage (Ue) - min	200 V
Rated operational voltage (Ue) - max	690 V
Short-circuit protection rating	NZMN2-S200, Type "1" coordination, Main conducting paths
Supply frequency	50/60 Hz, fLN, Main circuit
Voltage rating - max	690 V
<b>Motor rating</b>	
Assigned motor power at 200/208 V, 60 Hz, 3-phase	60 HP
Assigned motor power at 220/230 V, 60 Hz, 3-phase	60 HP
Assigned motor power at 460/480 V, 60 Hz, 3-phase	150 HP
Assigned motor power at 600 V, 60 Hz, 3-phase	150 HP
Assigned motor power at 690 V, 60 Hz, 3-phase	200 HP
Assigned motor power in-delta at 690 V, 60 Hz	350 HP
Rated operational power at 220/230 V, 50 Hz	55 kW
Rated operational power at 400 V, 50 Hz	90 kW
Rated operational power at 500 V, 50 Hz	110 kW
Rated operational power at 690 V, 50 Hz	160 kW
<b>Terminal capacities</b>	
Terminal capacity (flexible with ferrule)	2 x (1 - 2.5) mm <sup>2</sup> , Control circuit cables 2 x (25 - 240) mm <sup>2</sup> , Main cables 1 x (2.5 - 4) mm <sup>2</sup> , Control circuit cables 1 x (70 - 240) mm <sup>2</sup> , Main cables
Terminal capacity (solid)	1 x (2.5 - 4) mm <sup>2</sup> , Control circuit cables 2 x (25 - 240) mm <sup>2</sup> , Main cables 2 x (1 - 2.5) mm <sup>2</sup> , Control circuit cables 1 x (70 - 240) mm <sup>2</sup> , Main cables
Terminal capacity (solid/stranded AWG)	2 x (14 - 12), Control circuit cables 2 x (4 - 500 kcmil), Main cables 1 x (14 - 12), Control circuit cables 1 x (4 - 500 kcmil), Main cables
Terminal capacity (stranded)	2 x (25 - 240) mm <sup>2</sup> , Main cables 1 x (2.5 - 4) mm <sup>2</sup> , Control circuit cables 1 x (70 - 240) mm <sup>2</sup> , Main cables 2 x (1 - 2.5) mm <sup>2</sup> , Control circuit cables
Screwdriver size	0.6 x 3.5 mm, Terminal screws, Control circuit cables 4 mm Hexagon socket-head screw, Terminal screw, Main cables
Tightening torque	25.5 Nm (≤ 150 mm <sup>2</sup> ) 0.4 Nm, Screw terminals, Control circuit cables 28.3 Nm (> 150 mm <sup>2</sup> )
<b>Control circuit</b>	
Current consumption	10 A/150 ms, Control circuit, Regulator supply at peak performance (close bypass) at 24 V DC 150 mA, Control circuit, Digital inputs, External 24 V 1000 mA, Control circuit, Regulator supply 100 mA, Control circuit, Digital inputs, External 24 V (no-load)
Drop-out time	100 ms, DC operated

Drop-out voltage		0 - 3 V, DC operated
Pick-up time		100 ms at DC
Pick-up voltage		21.6 - 26.4 V DC
Rated control supply voltage (Us) at AC, 50 Hz - min		0 V
Rated control supply voltage (Us) at AC, 50 Hz - max		0 V
Rated control supply voltage (Us) at AC, 60 Hz - min		0 V
Rated control supply voltage (Us) at AC, 60 Hz - max		0 V
Rated control supply voltage (Us) at DC - min		24 V
Rated control supply voltage (Us) at DC - max		24 V
<b>Input/Output</b>		
Input current		4 - 20 mA (Analog inputs)
Number of inputs		1 (current input)
Number of outputs		2 Relay Outputs (programmable)
Output voltage		120 V AC/DC (relay outputs)
Protection		Finger and back-of-hand proof, Protection against direct contact
Rated control voltage (Uc)		24 V DC (-10 %/+10 %) 24 V DC
Rated operational current (Ie) at AC-11		3 A
<b>Soft start function</b>		
Application		3-phase motors: Yes Soft starting of three-phase asynchronous motors
Delay time		0 - 120 s, Soft start function, Ramp times
Kickstart		100% (Kickstart voltage) Max. 2000 ms (Kickstart Duration)
Ramp/run-up time		360 s
Start voltage		Max. 85 %, Soft start function, Start voltage = turn-off voltage
<b>Design verification</b>		
Equipment heat dissipation, current-dependent Pvid		25 W
Heat dissipation capacity Pdis		0 W
Heat dissipation per pole, current-dependent Pvid		0 W
Rated operational current for specified heat dissipation (In)		180 A
Static heat dissipation, non-current-dependent Pvs		25 W
10.2.2 Corrosion resistance		Meets the product standard's requirements.
10.2.3.1 Verification of thermal stability of enclosures		Meets the product standard's requirements.
10.2.3.2 Verification of resistance of insulating materials to normal heat		Meets the product standard's requirements.
10.2.3.3 Resist. of insul. mat. to abnormal heat/fire by internal elect. effects		Meets the product standard's requirements.
10.2.4 Resistance to ultra-violet (UV) radiation		Meets the product standard's requirements.
10.2.5 Lifting		Does not apply, since the entire switchgear needs to be evaluated.
10.2.6 Mechanical impact		Does not apply, since the entire switchgear needs to be evaluated.
10.2.7 Inscriptions		Meets the product standard's requirements.
10.3 Degree of protection of assemblies		Does not apply, since the entire switchgear needs to be evaluated.
10.4 Clearances and creepage distances		Meets the product standard's requirements.
10.5 Protection against electric shock		Does not apply, since the entire switchgear needs to be evaluated.
10.6 Incorporation of switching devices and components		Does not apply, since the entire switchgear needs to be evaluated.
10.7 Internal electrical circuits and connections		Is the panel builder's responsibility.
10.8 Connections for external conductors		Is the panel builder's responsibility.
10.9.2 Power-frequency electric strength		Is the panel builder's responsibility.
10.9.3 Impulse withstand voltage		Is the panel builder's responsibility.
10.9.4 Testing of enclosures made of insulating material		Is the panel builder's responsibility.
10.10 Temperature rise		The panel builder is responsible for the temperature rise calculation. Eaton will provide heat dissipation data for the devices.
10.11 Short-circuit rating		Is the panel builder's responsibility. The specifications for the switchgear must be observed.
10.12 Electromagnetic compatibility		Is the panel builder's responsibility. The specifications for the switchgear must be observed.
10.13 Mechanical function		The device meets the requirements, provided the information in the instruction leaflet (IL) is observed.

## Technical data ETIM 9.0

Low-voltage industrial components (EG000017) / Soft starter (EC000640)

Electric engineering, automation, process control engineering / Low-voltage switch technology / Load breakout, motor breakout / Semiconductor motor controller or soft starter  
(ec1@ss13-27-37-09-07 [ACO300016])

Rated operation current $I_e$ at 40 °C $T_u$	A	180
Rated operating voltage $U_e$	V	200 - 690
Rated power three-phase motor, inline, at 230 V	kW	55
Rated power three-phase motor, inline, at 400 V	kW	90
Rated power three-phase motor, inside delta, at 230 V	kW	90
Rated power three-phase motor, inside delta, at 400 V	kW	160
Function		Single direction
Internal bypass		Yes
With display		Yes
Torque control		No
Rated surrounding temperature without derating	°C	50
Rated control supply voltage AC 50 Hz	V	0 - 0
Rated control supply voltage AC 60 Hz	V	0 - 0
Rated control supply voltage DC	V	24 - 24
Voltage type for actuating		DC
Integrated motor overload protection		Yes
Release class		Adjustable
Degree of protection (IP)		IP20
Degree of protection (NEMA)		Other