Variable frequency drive splitter (RJ45, 3 sockets)



Part no. DX-SPL-RJ45-3SL

169141 4137458

EL Number

(Norway)

<u> </u>	
General specifications	
Product name	Eaton DX Splitter
Part no.	DX-SPL-RJ45-3SL
EAN	4015081658855
Product Length/Depth	38 millimetre
Product height	170 millimetre
Product width	120 millimetre
Product weight Product weight	0.04 kilogram
Certifications	UL 508C UL report applies to both US and Canada UL Category Control No.: NMMS, NMMS7 Certified by UL for use in Canada CSA-C22.2 No. 14 IEC/EN61800-5 IEC/EN61800-3 UL CE UL File No.: E172143
Product Tradename	DX
Product Type	Accessory
Product Sub Type	Splitter
General information	
Accessory/spare part type	Splitter
Degree of protection	IP00
Product Category	Accessories
Suitable for	Branch circuits, (UL/CSA)
Used with	DA1, DB1, DC1, DE1
Climatic environmental conditions	
Ambient operating temperature - max	50 °C
Ambient operating temperature - min	-10 °C
Connection	
Connection	RJ45, 8-pin, 3 sockets
Design verification	
10.2.2 Corrosion resistance	Meets the product standard's requirements.
10.2.3.1 Verification of thermal stability of enclosures	Meets the product standard's requirements.
10.2.3.2 Verification of resistance of insulating materials to normal heat	Meets the product standard's requirements.
10.2.3.3 Resist. of insul. mat. to abnormal heat/fire by internal elect. effects	Meets the product standard's requirements.
10.2.4 Resistance to ultra-violet (UV) radiation	Meets the product standard's requirements.
10.2.5 Lifting	Does not apply, since the entire switchgear needs to be evaluated.
10.2.6 Mechanical impact	Does not apply, since the entire switchgear needs to be evaluated.
10.2.7 Inscriptions	Meets the product standard's requirements.
10.3 Degree of protection of assemblies	Does not apply, since the entire switchgear needs to be evaluated.
10.4 Clearances and creepage distances	Meets the product standard's requirements.
10.5 Protection against electric shock	Does not apply, since the entire switchgear needs to be evaluated.
10.6 Incorporation of switching devices and components	Does not apply, since the entire switchgear needs to be evaluated.
10.7 Internal electrical circuits and connections	Is the panel builder's responsibility.
10.8 Connections for external conductors	Is the panel builder's responsibility.
10.9.2 Power-frequency electric strength	Is the panel builder's responsibility.
10.9.3 Impulse withstand voltage	Is the panel builder's responsibility.
10.9.4 Testing of enclosures made of insulating material	Is the panel builder's responsibility.

10.10 Temperature rise	The panel builder is responsible for the temperature rise calculation. Eaton will provide heat dissipation data for the devices.
10.11 Short-circuit rating	Is the panel builder's responsibility. The specifications for the switchgear must be observed.
10.12 Electromagnetic compatibility	Is the panel builder's responsibility. The specifications for the switchgear must be observed.
10.13 Mechanical function	The device meets the requirements, provided the information in the instruction leaflet (IL) is observed.

Technical data ETIM 9.0

Tooliniour data Erini olo		
Low-voltage industrial components (EG000017) / Accessories/spare parts for frequency controller (EC002025)		
Electric engineering, automation, process control engineering / Electrical drive / Static frequency converter / Static frequency converter (accessories) (ecl@ss13-27-02-31-92 [AFR303008])		
Type of accessory/spare part	Splitter	
Accessory	Yes	
Spare part	No	