

Variable frequency drive, 230 V AC, 3-phase, 18 A, 4 kW, IP66/NEMA 4X,  
Radio interference suppression filter, OLED display, Local controls



Powering Business Worldwide™

**Part no.** DA1-32018FB-B6SC

**169360**

**EL Number**

**4137828**

**(Norway)**

General specifications	
Product name	Eaton DA1 Variable frequency drive
Part no.	DA1-32018FB-B6SC
EAN	4015081660377
Product Length/Depth	266.3 millimetre
Product height	310 millimetre
Product width	211 millimetre
Product weight	7.3 kilogram
Certifications	EAC IEC/EN 61800-3 Safety: EN 61800-5-1: 2003 CSA-C22.2 No. 14 CE UL report applies to both US and Canada Specification for general requirements: IEC/EN 61800-2 UL 508C UL Certified by UL for use in Canada IEC/EN61800-3 RoHS, ISO 9001 UL File No.: E172143 CUL RCM UkrSEPRO IEC/EN61800-5 UL Category Control No.: NMMS, NMMS7
Product Tradename	DA1
Product Type	Variable frequency drive
Product Sub Type	None
Catalog Notes	The brake resistors are assigned based on the maximum rated power of the variable frequency drive. Additional brake resistors and designs (e.g. different duty cycles) are available upon request.
General information	
Cable length	300 m, unscreened, with motor choke, maximum permissible, Motor feeder C2 ≤ 5 m, Radio interference level, maximum motor cable length C3 ≤ 25 m, Radio interference level, maximum motor cable length 150 m, unscreened, maximum permissible, Motor feeder 200 m, screened, with motor choke, maximum permissible, Motor feeder 100 m, screened, maximum permissible, Motor feeder
Communication interface	EtherCAT, optional Modbus RTU, built in Modbus-TCP, optional PROFIBUS, optional DeviceNet, optional OP-Bus (RS485), built in PROFINET, optional CANopen®, built in Ethernet IP, optional
Connection to SmartWire-DT	No
Degree of protection	NEMA 4X IP66
Electromagnetic compatibility	1st and 2nd environments (according to EN 61800-3)
Fitted with:	Control unit Brake chopper Local controls IGBT inverter Additional PCB protection Breaking resistance Radio interference suppression filter PC connection OLED display Internal DC link
Frame size	FS3
Functions	4-quadrant operation possible

Mounting position		Vertical
Product Category		Variable frequency drives
Protection		Finger and back-of-hand proof, Protection against direct contact (BGV A3, VBG4)
Protocol		CAN Other bus systems DeviceNet MODBUS PROFINET IO PROFIBUS EtherNet/IP TCP/IP
Safety function/level		STO (Safe Torque Off, SIL2, PLc Cat 2)
Suitable for		Branch circuits, (UL/CSA)
Radio interference class		C2, C3: depending on the motor cable length, the connected load, and ambient conditions. External radio interference suppression filters (optional) may be necessary.
<b>Climatic environmental conditions</b>		
Ambient operating temperature - min		-10 °C
Altitude		Max. 4000 m Above 1000 m with 1 % derating per 100 m Max. 1000 m
Ambient operating temperature - max		40 °C
Ambient operating temperature at 150% overload - min		-10 °C
Ambient operating temperature at 150% overload - max		40 °C
Ambient storage temperature - min		-40 °C
Ambient storage temperature - max		60 °C
Climatic proofing		< 95 average relative humidity (RH), no condensation, no corrosion
<b>Main circuit</b>		
Efficiency		96 % ( $\eta$ )
Heat dissipation at current/speed		109 W at 50% current and 50% speed 122 W at 50% current and 90% speed 172 W at 100% current and 0% speed 175 W at 100% current and 50% speed 178 W at 100% current and 90% speed 75 W at 25% current and 0% speed 86 W at 25% current and 50% speed 91 W at 50% current and 0% speed
Input current ILN at 150% overload		20.9 A
Leakage current at ground IPE - max		0.93 mA
Mains switch-on frequency		Maximum of one time every 30 seconds
Mains voltage - min		200 V
Mains voltage - max		240 V
Operating mode		U/f control Sensorless vector control (SLV) Optional: Vector control with feedback (CLV) Speed control with slip compensation
Output frequency - min		0 Hz
Output frequency - max		500 Hz
Output voltage (U2)		240 V AC, 3-phase 230 V AC, 3-phase
Overload current IL at 150% overload		27 A
Rated control supply voltage		10 V DC (Us, max. 10 mA)
Rated frequency - min		48 Hz
Rated frequency - max		62 Hz
Rated operational current (Ie) at 150% overload		18 A
Rated operational power at 220/230 V, 50 Hz, 1-phase		4 kW
Rated operational voltage		230 V AC, 3-phase 240 V AC, 3-phase
Resolution		0.1 Hz (Frequency resolution, setpoint value)
Short-circuit protection rating		30 A, UL (Class CC or J), Safety device (fuse or miniature circuit-breaker), Power Wiring
Starting current - max		200 %, IH, max. starting current (High Overload), for 4 seconds every 40 seconds, Power section
Supply frequency		50/60 Hz
Switching frequency		16 kHz, 4 - 24 kHz adjustable (audible), rPWM, Power section, Main circuit

System configuration type		AC supply systems with earthed center point
Voltage rating - max		240 V AC
<b>Motor rating</b>		
Assigned motor current IM at 220 - 240 V, 60 Hz, 150% overload		15.2 A
Assigned motor current IM at 230 V, 50 Hz, 150% overload		14.8 A
Assigned motor power at 230/240 V, 60 Hz, 1-phase		5 HP
<b>Apparent power</b>		
Apparent power at 230 V		7.17 kV-A
Apparent power at 240 V		7.48 kV-A
<b>Braking function</b>		
Braking resistance		20 Ω
Braking torque		Max. 100 % of rated operational current I <sub>e</sub> with external braking resistor - Main circuit Max. 30 % MN, Standard - Main circuit Max. 100 % of rated operational current I <sub>e</sub> , variable, DC - Main circuit
Switch-on threshold for the braking transistor		390 V DC
<b>Control circuit</b>		
Number of inputs (analog)		2
Number of inputs (digital)		5
Number of outputs (analog)		2
Number of outputs (digital)		2
Number of relay outputs		2 (parameterizable, 1 N/O and 1 changeover contact, 6 A (250 V, AC-1) / 5 A (30 V, DC-1))
Rated control voltage (U <sub>c</sub> )		24 V DC (external, max. 100 mA)
<b>Design verification</b>		
Equipment heat dissipation, current-dependent P <sub>vid</sub>		160 W
Heat dissipation capacity P <sub>diss</sub>		0 W
Heat dissipation per pole, current-dependent P <sub>vid</sub>		0 W
Rated operational current for specified heat dissipation (I <sub>n</sub> )		18 A
Static heat dissipation, non-current-dependent P <sub>vs</sub>		0 W
10.2.2 Corrosion resistance		Meets the product standard's requirements.
10.2.3.1 Verification of thermal stability of enclosures		Meets the product standard's requirements.
10.2.3.2 Verification of resistance of insulating materials to normal heat		Meets the product standard's requirements.
10.2.3.3 Resist. of insul. mat. to abnormal heat/fire by internal elect. effects		Meets the product standard's requirements.
10.2.4 Resistance to ultra-violet (UV) radiation		Meets the product standard's requirements.
10.2.5 Lifting		Does not apply, since the entire switchgear needs to be evaluated.
10.2.6 Mechanical impact		Does not apply, since the entire switchgear needs to be evaluated.
10.2.7 Inscriptions		Meets the product standard's requirements.
10.3 Degree of protection of assemblies		Does not apply, since the entire switchgear needs to be evaluated.
10.4 Clearances and creepage distances		Meets the product standard's requirements.
10.5 Protection against electric shock		Does not apply, since the entire switchgear needs to be evaluated.
10.6 Incorporation of switching devices and components		Does not apply, since the entire switchgear needs to be evaluated.
10.7 Internal electrical circuits and connections		Is the panel builder's responsibility.
10.8 Connections for external conductors		Is the panel builder's responsibility.
10.9.2 Power-frequency electric strength		Is the panel builder's responsibility.
10.9.3 Impulse withstand voltage		Is the panel builder's responsibility.
10.9.4 Testing of enclosures made of insulating material		Is the panel builder's responsibility.
10.10 Temperature rise		The panel builder is responsible for the temperature rise calculation. Eaton will provide heat dissipation data for the devices.
10.11 Short-circuit rating		Is the panel builder's responsibility. The specifications for the switchgear must be observed.
10.12 Electromagnetic compatibility		Is the panel builder's responsibility. The specifications for the switchgear must be observed.
10.13 Mechanical function		The device meets the requirements, provided the information in the instruction leaflet (IL) is observed.

## Technical data ETIM 9.0

Low-voltage industrial components (EG000017) / Frequency converter ≤ 1 kV (EC001857)

Mains voltage	V	200 - 240
Mains frequency		50/60 Hz
Number of phases input		3
Number of phases output		3
Max. output frequency	Hz	500
Max. output voltage	V	250
Nominal output current I <sub>2N</sub>	A	18
Max. output at quadratic load at rated output voltage	kW	4
Max. output at linear load at rated output voltage	kW	4
Power consumption	W	160
Relative symmetric net frequency tolerance	%	10
Relative symmetric net voltage tolerance	%	10
Number of analogue outputs		2
Number of analogue inputs		2
Number of digital outputs		2
Number of digital inputs		5
With control element		Yes
Application in industrial area permitted		Yes
Application in domestic- and commercial area permitted		Yes
Supporting protocol for TCP/IP		Yes
Supporting protocol for PROFIBUS		Yes
Supporting protocol for CAN		Yes
Supporting protocol for INTERBUS		No
Supporting protocol for ASI		No
Supporting protocol for KNX		No
Supporting protocol for Modbus		Yes
Supporting protocol for Data-Highway		No
Supporting protocol for DeviceNet		Yes
Supporting protocol for SUCONET		No
Supporting protocol for LON		No
Supporting protocol for PROFINET IO		Yes
Supporting protocol for PROFINET CBA		No
Supporting protocol for SERCOS		No
Supporting protocol for Foundation Fieldbus		No
Supporting protocol for EtherNet/IP		Yes
Supporting protocol for AS-Interface Safety at Work		No
Supporting protocol for DeviceNet Safety		No
Supporting protocol for INTERBUS-Safety		No
Supporting protocol for PROFIsafe		No
Supporting protocol for SafetyBUS p		No
Supporting protocol for BACnet		No
Supporting protocol for other bus systems		Yes
Number of HW-interfaces industrial Ethernet		0
Number of interfaces PROFINET		0
Number of HW-interfaces RS-232		0
Number of HW-interfaces RS-422		0
Number of HW-interfaces RS-485		1
Number of HW-interfaces serial TTY		0
Number of HW-interfaces USB		0
Number of HW-interfaces parallel		0
Number of HW-interfaces other		0
With optical interface		No
With PC connection		Yes
Integrated breaking resistance		Yes

4-quadrant operation possible			Yes
Type of converter			U converter
Degree of protection (IP)			IP66
Degree of protection (NEMA)			4X
Height		mm	310
Width		mm	211
Depth		mm	266.3