



Fuse-link, high speed, 32 A, DC 1200 V, 50 kA, compact size 1, 39 x 66 x 164 mm, aR, IEC, type K indicator



Powering Business Worldwide™

Part no. **FUSE 32A 1200VDC 1C/A116 SST AR**
 Catalog No. **170M2102**

Similar to illustration

Delivery program

| | | | |
|------------------------------|---|----|-------------------------------------|
| Product range | | | Fuse |
| Basic function | | | Fuse-link |
| Field of application | | | high speed |
| Rated current | I | A | 32 |
| Rated voltage | | | DC 1200 V |
| Construction size | | | compact size 1 |
| Size | | | 39 x 66 x 164 mm |
| Utilization category | | | aR |
| Status indicator | | | type K indicator |
| Breaking Capacity | | kA | 50 |
| usable for size/applications | | | traction third rail |
| Standard/Approval | | | IEC |
| Shape | | | square body with offset bolted tags |
| Standards/Regulations | | | IEC 60269-4 |

Technical data ETIM 7.0

| | | | |
|---|--|----|---|
| Circuit breakers and fuses (EG000020) / Low Voltage HRC fuse (EC000055) | | | |
| Electric engineering, automation, process control engineering / Electrical installation, device / Safety fuse inserts / Low-Voltage HRC fuse (ecl@ss10.0.1-27-14-20-05 [AFZ800015]) | | | |
| Construction size | | | Other |
| Rated current | | A | 32 |
| Rated voltage | | V | 1200 |
| Voltage type | | | DC |
| Rated switching capacity | | kA | 150 |
| Utilization category | | | aR (accompanied semiconductor protection) |
| Type of fuse status indicator | | | Other |
| Insulated metal gripping lugs (IMGL) | | | No |