



Fuse-link, 2400 A, AC 1250 V, 200 kA, size 4, 100 x 120 x 106 mm, aR, IEC, type K indicator

Part no. **FUSE 2400A 1250V 4SBKN/105 AR**
 Catalog No. **170M7516**

Delivery program

| | | | |
|------------------------------|---|----|-------------------------------------|
| Product range | | | Fuse |
| Basic function | | | Fuse-link |
| Rated current | I | A | 2400 |
| Rated voltage | | | AC 1250 V |
| Construction size | | | size 4 |
| Size | | | 100 x 120 x 106 mm |
| Utilization category | | | aR |
| Status indicator | | | type K indicator |
| Breaking Capacity | | kA | 200 |
| usable for size/applications | | | Protection of power rectifiers |
| Standard/Approval | | | IEC |
| Shape | | | square body with flush end contacts |
| Standards/Regulations | | | IEC 60269-4 |

Technical data ETIM 7.0

| | | | |
|---|--|----|---|
| Circuit breakers and fuses (EG000020) / Low Voltage HRC fuse (EC000055) | | | |
| Electric engineering, automation, process control engineering / Electrical installation, device / Safety fuse inserts / Low-Voltage HRC fuse (ecl@ss10.0.1-27-14-20-05 [AFZ800015]) | | | |
| Construction size | | | Other |
| Rated current | | A | 2400 |
| Rated voltage | | V | 1250 |
| Voltage type | | | AC |
| Rated switching capacity | | kA | 200 |
| Utilization category | | | aR (accompanied semiconductor protection) |
| Type of fuse status indicator | | | Other |
| Insulated metal gripping lugs (IMGL) | | | No |