

Fuse switch-disconnector, LPC, 25 A, service distribution board  
mounting, 3 pole, DII

Part no.                   LPC25/3  
                                  1713617

<b>General specifications</b>		
Product name		Eaton LPC Fuse Switch-disconnector
Part no.		LPC25/3
EAN		8711426959156
Product Length/Depth		152 millimetre
Product height		108 millimetre
Product width		132 millimetre
Product weight		544.723 gram
Certifications		IEC/EN 60204 KEMA VDE 0660 IEC/EN 60947 CE RoHS IEC/EN 60947-3
Product Tradename		LPC
Product Type		Fuse Switch-disconnector
Product Sub Type		None
<b>Features &amp; Functions</b>		
Fitted with:		Error protection Connectors
Number of poles		Three-pole
<b>General information</b>		
Actuator type		Rocker lever
Degree of protection		IP20
Degree of protection (front side)		IP20
Mounting method		Service distribution board mounting
Mounting position		As required
Overvoltage category		III
Pollution degree		3
Product category		Fuse switch-disconnector
<b>Climatic environmental conditions</b>		
Ambient operating temperature - min		-25 °C
Ambient operating temperature - max		50 °C
Ambient storage temperature - min		-30 °C
Ambient storage temperature - max		80 °C
Operating temperature - min		-25 °C
Operating temperature - max		55 °C
<b>Terminal capacities</b>		
Terminal capacity (flexible)		1.5 - 10 mm <sup>2</sup>
Terminal capacity (solid)		1.5 - 16 mm <sup>2</sup>
Stripping length (main cable)		8 mm
Tightening torque		3 Nm, Screw terminals
<b>Electrical rating</b>		
Rated operating voltage (Ue) at AC - max		400 V
Rated operational power at AC-23A, 400 V, 50 Hz		0 kW
Rated short-time withstand current (Icw)		0 kA
Rated uninterrupted current (Iu)		25 A
Uninterrupted current		Rated uninterrupted current Iu is specified for max. cross-section.
<b>Design verification</b>		

Equipment heat dissipation, current-dependent P <sub>vid</sub>		0 W
Heat dissipation capacity P <sub>diss</sub>		0 W
Heat dissipation per pole, current-dependent P <sub>vid</sub>		3 W
Rated operational current for specified heat dissipation (I <sub>n</sub> )		0 A
Static heat dissipation, non-current-dependent P <sub>vs</sub>		0 W
10.2.2 Corrosion resistance		Meets the product standard's requirements.
10.2.3.1 Verification of thermal stability of enclosures		Meets the product standard's requirements.
10.2.3.2 Verification of resistance of insulating materials to normal heat		Meets the product standard's requirements.
10.2.3.3 Resist. of insul. mat. to abnormal heat/fire by internal elect. effects		Meets the product standard's requirements.
10.2.4 Resistance to ultra-violet (UV) radiation		Meets the product standard's requirements.
10.2.5 Lifting		Does not apply, since the entire switchgear needs to be evaluated.
10.2.6 Mechanical impact		Does not apply, since the entire switchgear needs to be evaluated.
10.2.7 Inscriptions		Meets the product standard's requirements.
10.3 Degree of protection of assemblies		Does not apply, since the entire switchgear needs to be evaluated.
10.4 Clearances and creepage distances		Meets the product standard's requirements.
10.5 Protection against electric shock		Does not apply, since the entire switchgear needs to be evaluated.
10.6 Incorporation of switching devices and components		Does not apply, since the entire switchgear needs to be evaluated.
10.7 Internal electrical circuits and connections		Is the panel builder's responsibility.
10.8 Connections for external conductors		Is the panel builder's responsibility.
10.9.2 Power-frequency electric strength		Is the panel builder's responsibility.
10.9.3 Impulse withstand voltage		Is the panel builder's responsibility.
10.9.4 Testing of enclosures made of insulating material		Is the panel builder's responsibility.
10.10 Temperature rise		The panel builder is responsible for the temperature rise calculation. Eaton will provide heat dissipation data for the devices.
10.11 Short-circuit rating		Is the panel builder's responsibility. The specifications for the switchgear must be observed.
10.12 Electromagnetic compatibility		Is the panel builder's responsibility. The specifications for the switchgear must be observed.
10.13 Mechanical function		The device meets the requirements, provided the information in the instruction leaflet (IL) is observed.

## Technical data ETIM 9.0

Low-voltage industrial components (EG000017) / Fuse switch disconnecter (EC001040)

Electric engineering, automation, process control engineering / Low-voltage switch technology / Off-load switch, circuit breaker, control switch / Fuse switch disconnecter (ec1@ss13-27-37-14-01 [AKF058018])

Version as main switch		No
Version as safety switch		No
Max. rated operation voltage U <sub>e</sub> AC	V	400
Rated permanent current I <sub>u</sub>	A	25
Rated operation power at AC-23, 400 V	kW	0
Conditioned rated short-circuit current I <sub>q</sub>	kA	0
Rated short-time withstand current I <sub>cw</sub>	kA	0
Suitable for fuses		Other
Number of poles		3
With error protection		Yes
Type of electrical connection of main circuit		Screw connection
Cable entry		Top/bottom
Equipped with connectors		Yes
Suitable for floor mounting		No
Suitable for front mounting		No
Suitable for busbar mounting		No
Type of control element		Rocker lever
Position control element		Front side
Motor drive optional		No
Motor drive integrated		No
Version as emergency stop installation		No
Degree of protection (IP), front side		IP20

