## Base module;internal fixing screw

Part no. SL7-CB-IMS 171448

**EL Number** 4137703

(Norway)



(INUI Way)	
General specifications	
Product name	Eaton Moeller® series SL7 Base module
Part no.	SL7-CB-IMS
EAN	4015081677788
Product Length/Depth	73 millimetre
Product height	90 millimetre
Product width	73 millimetre
Product weight	0.194 kilogram
Certifications	CE CSA-C22.2 No. 14-10 UL 508 IEC/EN 60947-5-1 IEC/EN 60529 UL UL Category Control No.: NKCR CSA-C22.2 No. 94-91 UL File No.: E29184 Certified by UL for use in Canada UL report applies to both US and Canada CSA Class No.: NKCR7
Product Tradename	SL7
Product Type	Base module
Product Sub Type	None
Features & Functions	
Color	Other
Fitted with:	Cover Built-in (pre-assembled) fixing screws
Number of modules	Max. 10 (with base for mounting on both sides) Max. 5 Max. 5 (with standard base)
General information	
Connection to SmartWire-DT	No
Degree of protection	IP66 NEMA 13 NEMA 4 NEMA 4X
Mounting Method	Floor Bracket Horizontal
Mounting position	As required
Overvoltage category	III
Pollution degree	3
Product Category	SL signal towers
Rated impulse withstand voltage (Uimp)	4000 V AC
Shock resistance	Mechanical, According to IEC/EN 60068-2-27 15 g, Mechanical, According to IEC/EN 60068-2-27, Sinusoidal shock 11 ms
Туре	Base module
Climatic environmental conditions	
Ambient operating temperature - min	-30 °C
Ambient operating temperature - max	0° ℃
Climatic proofing	Damp heat, constant, to IEC 60068-2-78 Damp heat, cyclic, to IEC 60068-2-30
Terminal capacities	
Terminal capacity (AWG)	24 - 14
Terminal capacity (flexible with ferrule and plastic collar)	0.25 - 1.5 mm <sup>2</sup>

Electrical rating	
Rated insulation voltage (Ui)	250 V
Rated operational voltage	110/120 V AC ± 10 % 24 V AC/DC ± 10 % 230/240 V AC ± 10 %

## **Technical data ETIM 9.0**

Low-voltage industrial components (EG000017) / Connection module for signal tower (EC001152)

Electric engineering, automation, process control engineering / Low-voltage switch technology / Command and alarm device / Signal column element, connection module (ecl@ss13-27-37-12-32 [AKF050019])

(50,650,67,70,712,62) (11,11,100,610)		
Connection type auxiliary circuit	Spring clamp connection	
Suitable for tube mounting	No	
Suitable for angle mounting	Yes	
Suitable for floor mounting	Yes	
Colour	Other	
Suitable for AS interface	No	
Suitable for M12 connector	No	
Suitable for IO link	No	