

Visualization Software, GALILEO for all XV/XP switchgear, single-user license, update from GALILEO V 8.1.2



Part no. SW-GALILEO-S
171500
EL Number 4560874
(Norway)

General specifications		
Product name		Eaton GALILEO Software
Part no.		SW-GALILEO-S
EAN		7640130098022
Product Length/Depth		230 millimetre
Product height		2 millimetre
Product width		162 millimetre
Product weight		0.016 kilogram
Certifications		UL/CSA certification not required
Product Tradename		GALILEO
Product Type		Software
Product Sub Type		None
General information		
Features		Loadable for operating system for configuration software, Windows XP Loadable for operating system for configuration software, Windows 2000 Loadable for operating system for configuration software, Windows Vista Loadable for operating system for configuration software, Windows 7 Loadable for operating system for configuration software, Windows 9x Loadable for operating system for configuration software, Windows NT Loadable for operating system for configuration software, Windows 8 Alarm-management Online projecting possible Language switch possible User groups (password protection) possible
Fitted with:		OPC-interface, server Other script language OPC-interface, client Programming interfaces
Operating system		Runtime operation system, Windows Vista Runtime operating system, Windows 2000 Runtime operating system, Windows XP
Software		Supports update for GALILEO version 8.1.2 or higher For creating projects to operate and visualize machines, plants and buildings Microsoft Windows™-based, intelligent and interactive visualization tool Comprehensive help and documentation GALILEO Single-user license
Suitable for		Operating system Windows 7 Web-clients Operating system Windows 8 Operating system Windows 10

Technical data ETIM 9.0

Programmable logic controllers PLC (EG000024) / Visualization software (EC001416)		
Electric engineering, automation, process control engineering / Control, Process Control System (PCS) / Control software / Visualization software (ecl@ss13-27-24-25-02 [AKE561020])		
With OPC-interface, server		Yes
With OPC-interface, client		Yes
With programming interfaces		Yes
Runtime operating system, Windows XP		No
Runtime operating system, Windows 2000		No
Runtime operating system, Linux		No
Runtime operation system, Windows Vista		No
Suitable for operating system Windows 7		Yes
Suitable for operating system Windows 8		Yes
Suitable for operating system Windows 10		Yes
Runtime operating system, other		No

Loadable for operating system for configuration software, Windows 9x			Yes
Loadable for operating system for configuration software, Windows NT			Yes
Loadable for operating system for configuration software, Windows 2000			Yes
Loadable for operating system for configuration software, Windows XP			Yes
Loadable for operating system for configuration software, Linux			No
Loadable for operating system for configuration software, Windows ME			No
Loadable for operating system for configuration software, Windows Vista			Yes
Loadable for operating system for configuration software, Windows 2003 Server			No
Loadable for operating system for configuration software, Windows 7			Yes
Loadable for operating system for configuration software, Windows 8			Yes
Min. required main memory for runtime system		MB	256
Min. required main memory for configuration software		MB	128
Industry- and technological expansions			Integrated
Multi-user capable, runtime			No
Max. number of servers			1
Max. number of clients			10
Suitable for web-clients			Yes
SCADA functionality			No
Alarm-management			Yes
Trend representation			Yes
Max. number of multi-users configuration			1
Online projecting possible			Yes
Integrable in the engineering software o.t autom.system			No
Number of online/runtime languages			100
Language switch possible			Yes
Number of configuration-/runtime languages			100
Number of configuration-/desktop languages			2
With script language Visual Basic			No
With other script language			Yes
Library with object elements			Integrated
User groups (password protection) possible			Yes
Message system			Integrated
User archive/recipes management			Integrated
Reporting system/protocol system			Integrated
Function process diagnostics			Integrated
SQL-database			Optional
Min. required processor speed for runtime system		GHz	0.2
Min. required processor speed for configuration software		GHz	1