

Function element for connecting interface to SmartWire-DT



Part no. PKE-SWD-CP
172735
EL Number 4560851
(Norway)

| General specifications | | |
|--|--|---|
| Product name | | Eaton Moeller® series PKE Function element |
| Part no. | | PKE-SWD-CP |
| EAN | | 4015081692811 |
| Product Length/Depth | | 75 millimetre |
| Product height | | 65 millimetre |
| Product width | | 67.5 millimetre |
| Product weight | | 0.028 kilogram |
| Certifications | | IEC/EN 61131-2 |
| Product Tradename | | PKE |
| Product Type | | Accessory |
| Product Sub Type | | Function element |
| Features & Functions | | |
| Functions | | Remote circuit-breaker de-energization For attachment to PKE circuit-breakers Display of Set short-circuit release value Display of Contactor state PKE Display of Trip indications (Overload, Short-circuit,...) Display of Part no. of trip block Display of All phase currents in % For connecting the PKE circuit-breaker with PKE-XTU(W)ACP-... trip blocks to SmartWire-DT Display of Thermal load as a % System protection Display of Set value of overload releases |
| General information | | |
| Accessory/spare part type | | Communication and measuring function |
| Current consumption | | 35 mA, SmartWire-DT network, 15-V-SWD supply |
| Degree of protection | | IP20 |
| Overvoltage category | | II |
| Pollution degree | | 2 |
| Product category | | Accessories SmartWire-DT slave |
| Type | | Function element |
| Ambient conditions, mechanical | | |
| Constant acceleration | | 1 g, 8.4 - 150 Hz, according to IEC/EN 61131-2, Vibrations |
| Constant amplitude | | 3,5 mm, 5 - 8.4 Hz, according to IEC/EN 61131-2, Vibrations |
| Drop and topple | | 50 mm Drop height, Drop to IEC/EN 60068-2-31 |
| Height of fall (IEC/EN 60068-2-32) - max | | 0.3 m |
| Mounting position | | As PKE32/65 |
| Shock resistance | | 15 g, Mechanical, according to IEC/EN 60068-2-27, Half-sinusoidal shock 11 ms, 9 Impacts |
| Climatic environmental conditions | | |
| Ambient operating temperature - min | | -25 °C |
| Ambient operating temperature - max | | 60 °C |
| Ambient storage temperature - min | | -30 °C |
| Ambient storage temperature - max | | 70 °C |
| Environmental conditions | | Condensation: prevent with appropriate measures |
| Relative humidity | | 5 - 95 % (non-condensing, IEC/EN 60068-2-30) |
| Electro magnetic compatibility | | |
| Air discharge | | 8 kV, according to IEC 61131-2, level 3, ESD |
| Burst impulse | | 1 kV, SmartWire-DT cable, Signal cable, according to IEC/EN 61131-2, Level 3 |

| | | |
|--|--|--|
| | | 1 kV, CAN/DP-bus cable, SmartWire-DT cables, according to IEC/EN 61131-2, Level 3 |
| Contact discharge | | 4 kV, according to IEC/EN 61131-2, Level 2, ESD |
| Electromagnetic fields | | 10 V/m at 80 - 1000 MHz (according to IEC/EN 61131-2:2008) 1 V/m at 2.0 - 2.7 GHz (according to IEC/EN 61131-2:2008) 3 V/m at 1.4 - 2 GHz (according to IEC/EN 61131-2:2008) |
| Radiated RFI | | 10 V (IEC/EN 61131-2:2008, Level 3) |
| Radio interference class | | Class A (EN 55011) |
| Communication | | |
| Addressing | | Address set automatically |
| Connection to SmartWire-DT | | Yes |
| Connection type | | SWD: Plug, 8-pole External device plug SWD4-8SF2-5, SmartWire-DT |
| LED indicator | | Status indication of SmartWire-DT network: Green LED |
| Station | | SmartWire-DT slave, SmartWire-DT network |
| Design verification | | |
| Static heat dissipation, non-current-dependent Pvs | | 0 W |
| 10.2.2 Corrosion resistance | | Meets the product standard's requirements. |
| 10.2.3.1 Verification of thermal stability of enclosures | | Meets the product standard's requirements. |
| 10.2.3.2 Verification of resistance of insulating materials to normal heat | | Meets the product standard's requirements. |
| 10.2.3.3 Resist. of insul. mat. to abnormal heat/fire by internal elect. effects | | Meets the product standard's requirements. |
| 10.2.4 Resistance to ultra-violet (UV) radiation | | Meets the product standard's requirements. |
| 10.2.5 Lifting | | Does not apply, since the entire switchgear needs to be evaluated. |
| 10.2.6 Mechanical impact | | Does not apply, since the entire switchgear needs to be evaluated. |
| 10.2.7 Inscriptions | | Meets the product standard's requirements. |
| 10.3 Degree of protection of assemblies | | Does not apply, since the entire switchgear needs to be evaluated. |
| 10.4 Clearances and creepage distances | | Meets the product standard's requirements. |
| 10.5 Protection against electric shock | | Does not apply, since the entire switchgear needs to be evaluated. |
| 10.6 Incorporation of switching devices and components | | Does not apply, since the entire switchgear needs to be evaluated. |
| 10.7 Internal electrical circuits and connections | | Is the panel builder's responsibility. |
| 10.8 Connections for external conductors | | Is the panel builder's responsibility. |
| 10.9.2 Power-frequency electric strength | | Is the panel builder's responsibility. |
| 10.9.3 Impulse withstand voltage | | Is the panel builder's responsibility. |
| 10.9.4 Testing of enclosures made of insulating material | | Is the panel builder's responsibility. |
| 10.10 Temperature rise | | The panel builder is responsible for the temperature rise calculation. Eaton will provide heat dissipation data for the devices. |
| 10.11 Short-circuit rating | | Is the panel builder's responsibility. The specifications for the switchgear must be observed. |
| 10.12 Electromagnetic compatibility | | Is the panel builder's responsibility. The specifications for the switchgear must be observed. |
| 10.13 Mechanical function | | The device meets the requirements, provided the information in the instruction leaflet (IL) is observed. |

Technical data ETIM 9.0

| | | |
|--|--|--------------------------------------|
| Low-voltage industrial components (EG000017) / Accessories/spare parts for low-voltage switch technology (EC002498) | | |
| Electric engineering, automation, process control engineering / Low-voltage switch technology / Component for low-voltage switching technology / Component for low-voltage switching technology (accessories) (ecl@ss13-27-37-13-92 [AKN570018]) | | |
| Type of accessory/spare part | | Communication and measuring function |
| Accessory | | Yes |
| Spare part | | No |