

Variable frequency drive, 500 V AC, 3-phase, 4.1 A, 2.2 kW, IP66/NEMA 4X, OLED display



Part no. **DA1-354D1NB-B66C**
176986

General specifications		
Product name		Eaton DA1 Variable frequency drive
Part no.		DA1-354D1NB-B66C
EAN		4015081714292
Product Length/Depth		239.3 millimetre
Product height		257 millimetre
Product width		188 millimetre
Product weight		1.8 kilogram
Certifications		IEC/EN 61800-3 IEC/EN61800-5 Certified by UL for use in Canada Safety: EN 61800-5-1: 2003 EAC Specification for general requirements: IEC/EN 61800-2 UL UkrSEPRO UL 508C UL report applies to both US and Canada CE UL Category Control No.: NMMS, NMMS7 RCM RoHS, ISO 9001 CSA-C22.2 No. 14 IEC/EN61800-3 CUL UL File No.: E172143
Product Tradename		DA1
Product Type		Variable frequency drive
Product Sub Type		None
Catalog Notes		The brake resistors are assigned based on the maximum rated power of the variable frequency drive. Additional brake resistors and designs (e.g. different duty cycles) are available upon request.
General information		
Cable length		100 m, screened, maximum permissible, Motor feeder 200 m, screened, with motor choke, maximum permissible, Motor feeder 300 m, unscreened, with motor choke, maximum permissible, Motor feeder 150 m, unscreened, maximum permissible, Motor feeder
Communication interface		EtherCAT, optional Modbus RTU, built in CANopen®, built in Modbus-TCP, optional DeviceNet, optional OP-Bus (RS485), built in Ethernet IP, optional PROFIBUS, optional PROFINET, optional
Connection to SmartWire-DT		No
Degree of protection		IP66 NEMA 4X
Fitted with:		PC connection Brake chopper Control unit OLED display Breaking resistance Internal DC link Additional PCB protection IGBT inverter
Frame size		FS2
Functions		4-quadrant operation possible
Mounting position		Vertical
Product Category		Variable frequency drives
Protection		Finger and back-of-hand proof, Protection against direct contact (BGV A3, VBG4)
Protocol		EtherNet/IP DeviceNet

			CAN MODBUS PROFINET IO PROFIBUS Other bus systems TCP/IP
Safety function/level			STO (Safe Torque Off, SIL2, PLc Cat 2)
Suitable for			Branch circuits, (UL/CSA)
Climatic environmental conditions			
Ambient operating temperature - min			-10 °C
Altitude			Max. 1000 m Above 1000 m with 1 % derating per 100 m Max. 4000 m
Ambient operating temperature - max			40 °C
Ambient operating temperature at 150% overload - min			-10 °C
Ambient operating temperature at 150% overload - max			40 °C
Ambient storage temperature - min			-40 °C
Ambient storage temperature - max			60 °C
Climatic proofing			< 95 average relative humidity (RH), no condensation, no corrosion
Main circuit			
Efficiency			97 % (η)
Heat dissipation at current/speed			45 W at 25% current and 0% speed 51 W at 25% current and 50% speed 52 W at 50% current and 0% speed 57 W at 50% current and 50% speed 59 W at 50% current and 90% speed 61 W at 100% current and 0% speed 66 W at 100% current and 50% speed 76 W at 100% current and 90% speed
Input current ILN at 150% overload			4.9 A
Leakage current at ground IPE - max			4.1 mA
Mains switch-on frequency			Maximum of one time every 30 seconds
Mains voltage - min			500 V
Mains voltage - max			600 V
Operating mode			Speed control with slip compensation Optional: Vector control with feedback (CLV) Sensorless vector control (SLV) U/f control
Output frequency - min			0 Hz
Output frequency - max			500 Hz
Output voltage (U2)			500 V AC, 3-phase 600 V AC, 3-phase
Overload current IL at 150% overload			7.35 A
Rated control supply voltage			10 V DC (Us, max. 10 mA)
Rated frequency - min			48 Hz
Rated frequency - max			62 Hz
Rated operational current (Ie) at 150% overload			4.1 A
Rated operational power at 500 V, 50 Hz, 3-phase			2.2 kW
Rated operational power at 525 V, 50 Hz, 3-phase			2.2 kW
Rated operational voltage			500 V AC, 3-phase 600 V AC, 3-phase
Resolution			0.1 Hz (Frequency resolution, setpoint value)
Short-circuit protection			NH fuse used together with TB00-D fuse base, Power wiring, Assigned switching and protective elements LPJ fuse used together with J60060-3 fuse base, Power wiring, Assigned switching and protective elements
Short-circuit protection rating			10 A, UL (Class CC or J), Safety device (fuse or miniature circuit-breaker), Power Wiring
Starting current - max			200 %, IH, max. starting current (High Overload), for 4 seconds every 40 seconds, Power section
Supply frequency			50/60 Hz
Switching frequency			8 kHz, 4 - 24 kHz adjustable (audible), fPWM, Power section, Main circuit
System configuration type			AC supply systems with earthed center point
Voltage rating - max			600 V AC
Motor rating			

Assigned motor current IM at 500 V, 50 Hz, 150% overload		4 A
Assigned motor current IM at 525 V, 50 Hz, 150% overload		3.8 A
Assigned motor current IM at 550 - 600 V, 60 Hz, 150% overload		3.9 A
Assigned motor power at 575/600 V, 60 Hz, 3-phase		3 HP
Apparent power		
Apparent power at 600 V		4.26 kV-A
Braking function		
Braking resistance		200 Ω
Braking torque		Max. 100 % of rated operational current I _e , variable, DC - Main circuit Max. 100 % of rated operational current I _e with external braking resistor - Main circuit Max. 30 % MN, Standard - Main circuit
Switch-on threshold for the braking transistor		975 V DC
Control circuit		
Number of inputs (analog)		2
Number of inputs (digital)		5
Number of outputs (analog)		2
Number of outputs (digital)		2
Number of relay outputs		2 (parameterizable, 1 N/O and 1 changeover contact, 6 A (250 V, AC-1) / 5 A (30 V, DC-1))
Rated control voltage (U _c)		24 V DC (external, max. 100 mA)
Design verification		
Equipment heat dissipation, current-dependent P _{vid}		66 W
Heat dissipation capacity P _{diss}		0 W
Heat dissipation per pole, current-dependent P _{vid}		0 W
Rated operational current for specified heat dissipation (I _n)		4.1 A
Static heat dissipation, non-current-dependent P _{vs}		0 W
Heat dissipation details		Operation (with 150 % overload)
10.2.2 Corrosion resistance		Meets the product standard's requirements.
10.2.3.1 Verification of thermal stability of enclosures		Meets the product standard's requirements.
10.2.3.2 Verification of resistance of insulating materials to normal heat		Meets the product standard's requirements.
10.2.3.3 Resist. of insul. mat. to abnormal heat/fire by internal elect. effects		Meets the product standard's requirements.
10.2.4 Resistance to ultra-violet (UV) radiation		Meets the product standard's requirements.
10.2.5 Lifting		Does not apply, since the entire switchgear needs to be evaluated.
10.2.6 Mechanical impact		Does not apply, since the entire switchgear needs to be evaluated.
10.2.7 Inscriptions		Meets the product standard's requirements.
10.3 Degree of protection of assemblies		Does not apply, since the entire switchgear needs to be evaluated.
10.4 Clearances and creepage distances		Meets the product standard's requirements.
10.5 Protection against electric shock		Does not apply, since the entire switchgear needs to be evaluated.
10.6 Incorporation of switching devices and components		Does not apply, since the entire switchgear needs to be evaluated.
10.7 Internal electrical circuits and connections		Is the panel builder's responsibility.
10.8 Connections for external conductors		Is the panel builder's responsibility.
10.9.2 Power-frequency electric strength		Is the panel builder's responsibility.
10.9.3 Impulse withstand voltage		Is the panel builder's responsibility.
10.9.4 Testing of enclosures made of insulating material		Is the panel builder's responsibility.
10.10 Temperature rise		The panel builder is responsible for the temperature rise calculation. Eaton will provide heat dissipation data for the devices.
10.11 Short-circuit rating		Is the panel builder's responsibility. The specifications for the switchgear must be observed.
10.12 Electromagnetic compatibility		Is the panel builder's responsibility. The specifications for the switchgear must be observed.
10.13 Mechanical function		The device meets the requirements, provided the information in the instruction leaflet (IL) is observed.

Technical data ETIM 9.0

Low-voltage industrial components (EG000017) / Frequency converter =< 1 kV (EC001857)		
Electric engineering, automation, process control engineering / Electrical drive / Static frequency converter / Static frequency / Servo converter = < 1 kV (ecI@ss13-27-02-31-01 [AKE177019])		
Mains voltage	V	500 - 600

Mains frequency		50/60 Hz
Number of phases input		3
Number of phases output		3
Max. output frequency	Hz	500
Max. output voltage	V	600
Nominal output current I2N	A	4.1
Max. output at quadratic load at rated output voltage	kW	2.2
Max. output at linear load at rated output voltage	kW	2.2
Power consumption	W	66
Relative symmetric net frequency tolerance	%	10
Relative symmetric net voltage tolerance	%	10
Number of analogue outputs		2
Number of analogue inputs		2
Number of digital outputs		2
Number of digital inputs		5
With control element		Yes
Application in industrial area permitted		Yes
Application in domestic- and commercial area permitted		Yes
Supporting protocol for TCP/IP		Yes
Supporting protocol for PROFIBUS		Yes
Supporting protocol for CAN		Yes
Supporting protocol for INTERBUS		No
Supporting protocol for ASI		No
Supporting protocol for KNX		No
Supporting protocol for Modbus		Yes
Supporting protocol for Data-Highway		No
Supporting protocol for DeviceNet		Yes
Supporting protocol for SUCONET		No
Supporting protocol for LON		No
Supporting protocol for PROFINET IO		Yes
Supporting protocol for PROFINET CBA		No
Supporting protocol for SERCOS		No
Supporting protocol for Foundation Fieldbus		No
Supporting protocol for EtherNet/IP		Yes
Supporting protocol for AS-Interface Safety at Work		No
Supporting protocol for DeviceNet Safety		No
Supporting protocol for INTERBUS-Safety		No
Supporting protocol for PROFIsafe		No
Supporting protocol for SafetyBUS p		No
Supporting protocol for BACnet		No
Supporting protocol for other bus systems		Yes
Number of HW-interfaces industrial Ethernet		0
Number of interfaces PROFINET		0
Number of HW-interfaces RS-232		0
Number of HW-interfaces RS-422		0
Number of HW-interfaces RS-485		1
Number of HW-interfaces serial TTY		0
Number of HW-interfaces USB		0
Number of HW-interfaces parallel		0
Number of HW-interfaces other		0
With optical interface		No
With PC connection		Yes
Integrated breaking resistance		Yes
4-quadrant operation possible		Yes
Type of converter		U converter

Degree of protection (IP)			IP66
Degree of protection (NEMA)			4X
Height		mm	257
Width		mm	188
Depth		mm	239.3