

Mini compact distribution board, 1-row 2 SU, IP30



Part no. MINI-2-T
177071
EL Number 1702976
(Norway)

| General specifications | | |
|--|--|--|
| Product name | | Eaton xComfort Micro/Mini mini series |
| Part no. | | MINI-2-T |
| EAN | | 4015081715145 |
| Product Length/Depth | | 83 millimetre |
| Product height | | 140 millimetre |
| Product width | | 53 millimetre |
| Product weight | | 0.09 kilogram |
| Compliances | | RoHS conform |
| Certifications | | IEC/EN 62208 |
| Product Tradename | | xComfort Micro/Mini |
| Product Type | | Mini series |
| Product Sub Type | | None |
| Delivery program | | |
| Type | | Basic device Installation distribution board MINI distribution board |
| Application | | Indoor (installation site) |
| Color | | Signal white (RAL 9003) White |
| Technical Data - Electrical | | |
| Voltage rating at AC | | 400 V AC |
| Frequency rating of contacts | | 50 Hz |
| Technical Data - Mechanical | | |
| Closure type | | Other |
| Enclosure material | | Plastic |
| Width in number of modular spacings | | 2 |
| Mounting method | | DIN-rail Surface mounted (plaster) Surface mounting |
| Material | | ABS (plastic) |
| Degree of protection | | IP30 IK05 (impact resistance) |
| Number of module space units per row | | 2 |
| Number of rows | | 1 |
| Terminal type | | Without terminals |
| Built-in depth | | 70 mm |
| Built-in height | | 0 mm |
| Built-in width | | 0 mm |
| Internal depth | | 60 mm |
| Cover/door color | | Transparent |
| Cover/door model | | Closed |
| Cover/door type | | Door Single |
| Module rack type | | Single-rail |
| Protective shrouding material | | Plastic |
| Temperature-rise verification as per IEC 60890 | | |
| Heat diss. ambient 35°C delta T:20°C wall mount individ. encl. top (IEC 60890) | | 10 W |
| Heat diss. ambient 35°C delta T:35°C wall mount individ. encl. top (IEC 60890) | | 12 W |
| Design verification as per IEC/EN 61439 - technical data | | |
| Ambient operating temperature details | | -5 °C - 40 °C |

Design verification as per IEC/EN 61439

| | | | |
|--|--|--|--|
| 10.2.2 Corrosion resistance | | | Meets the product standard's requirements. |
| 10.2.3.1 Verification of thermal stability of enclosures | | | Meets the product standard's requirements. |
| 10.2.3.2 Verification of resistance of insulating materials to normal heat | | | Meets the product standard's requirements. |
| 10.2.3.3 Resist. of insul. mat. to abnormal heat/fire by internal elect. effects | | | 650 °C; meets the product standard's requirements. |
| 10.2.4 Resistance to ultra-violet (UV) radiation | | | Not relevant to indoor installations. |
| 10.2.5 Lifting | | | Does not apply to enclosures without lifting aids. |
| 10.2.6 Mechanical impact | | | IK05 |
| 10.2.7 Inscriptions | | | Meets the product standard's requirements. |
| 10.3 Degree of protection of assemblies | | | IP30 |
| 10.4 Clearances and creepage distances | | | Is the panel builder's responsibility. |
| 10.5 Protection against electric shock | | | Protection class 2, therefore not applicable. |
| 10.6 Incorporation of switching devices and components | | | Is the panel builder's responsibility. |
| 10.7 Internal electrical circuits and connections | | | Is the panel builder's responsibility. |
| 10.8 Connections for external conductors | | | Is the panel builder's responsibility. |
| 10.9.2 Power-frequency electric strength | | | U _i = 400 V AC |
| 10.9.3 Impulse withstand voltage | | | 2.8 kV |
| 10.9.4 Testing of enclosures made of insulating material | | | Meets the product standard's requirements. |
| 10.10 Temperature rise | | | The panel builder is responsible for the temperature rise calculation. Eaton will provide heat dissipation data for the devices. |
| 10.11 Short-circuit rating | | | Is the panel builder's responsibility. |
| 10.12 Electromagnetic compatibility | | | Is the panel builder's responsibility. |
| 10.13 Mechanical function | | | Meets the product standard's requirements. |
| Additional information | | | |
| Features | | | EMC-version |
| Fitted with: | | | Basic device |
| Functions | | | Basic device |
| Protection class | | | II (totally insulated) |
| RAL-number | | | 9003 |
| Special features | | | IP30 Protection Class II Plastic housing white (RAL 9003) |
| Used with | | | Basic device MINI distribution board Installation distribution board |

Technical data ETIM 9.0

| | | | |
|--|--|----|-----------------|
| Distribution boards (EG000023) / Small distribution board (EC000214) | | | |
| Electric engineering, automation, process control engineering / Electrical installation, device / Electrical distribution system (including small distribution board) / Small distribution board (ec@ss13-27-14-24-09 [ACN387016]) | | | |
| Mounting method | | | Surface mounted |
| Number of rows | | | 1 |
| Width in number of modular spacings | | | 2 |
| Type of covering | | | Door |
| Cover model | | | Closed |
| Type of door | | | Single |
| Transparent cover/door | | | Yes |
| Signal passing door | | | No |
| With lock | | | No |
| Type of closure | | | Other |
| Housing material | | | Plastic |
| Built-in depth | | mm | 70 |
| Built-in height | | mm | 0 |
| Built-in width | | mm | 0 |
| Inner depth | | mm | 60 |
| Earthing terminal block | | | No |
| Neutral terminal block | | | No |
| DIN-rail | | | Yes |

| | | | |
|---------------------------|--|----|-------|
| With mounting plate | | | No |
| Extension possible | | | No |
| EMC-version | | | Yes |
| UV resistant | | | No |
| Colour | | | White |
| RAL-number | | | 9003 |
| Degree of protection (IP) | | | IP30 |
| Height | | mm | 140 |
| Width | | mm | 53 |
| Depth | | mm | 83 |