

Analog input module; 8 thermocouple inputs and two KTY inputs



Part no. **XN-322-10AI-TEKT**  
**178792**

General specifications		
Product name		Eaton XN-322 Accessory Input module
Part no.		XN-322-10AI-TEKT
EAN		7640130098268
Product Length/Depth		104.2 millimetre
Product height		16.8 millimetre
Product width		80.3 millimetre
Product weight		0.061 kilogram
Certifications		IEC/EN 61000-6-2 CE UL File No.: E135462 CULus IEC/EN 61000-6-4 IEC/EN 61131-2
Product Tradename		XN-322
Product Type		Accessory
Product Sub Type		Input module
Catalog Notes		265 V AC (thermocouples), 40V DC (KTY) A KTY sensor is included with the product. The max. heat dissipation is specified as the maximum power produced inside the device's housing.
Features & Functions		
Electric connection type		Plug-in connection
Features		Fieldbus connection over separate bus coupler possible Input, thermocouple Analog outputs configurable Input, resistance thermometer Analog inputs configurable Input signal, configurable
Fitted with:		Parameterizable Software input filter 2 kHz, third-order low-pass input filter
Measurement ranges		0 - 1760 °C (Temperature measurement, Type S) -20 - 80 °C (Temperature measurement, KTY10) 0 - 1080 °C (Temperature measurement, Type N) 0 - 690 °C (Temperature measurement, Type J) 0 - 520 °C (Temperature measurement, Type E) 0 - 680 °C (Temperature measurement, Type L) 0 - 590 °C (Temperature measurement, Type U) 0 - 400 °C (Temperature measurement, Type T) 0 - 1760 °C (Temperature measurement, Type R) 0 - 940 °C (Temperature measurement, Type K) 0 - 1820 °C (Temperature measurement, Type B)
Value representation		SIGNED16 (0.1 °C), Temperature and resistance measurement
General information		
Current consumption		62 mA (typ.), for +5 V power supply (internal), Power supply - Input 75 mA (typ.), for +24 V, Power supply - Input
Degree of protection		IP20 NEMA 1
Mounting method		Rail mounting possible
Number of channels		10, Analog Inputs
Overvoltage category		III
Pollution degree		3
Product category		XN-322 analog input module
Resolution		16 Bit (Analog inputs)
Type		Analog input module for eight thermocouples and two KTY temperature sensors for cold-junction compensation purposes. XN300 I/O slice module
Used with		XN-312-... XN300
Voltage type		DC

<b>Ambient conditions, mechanical</b>		
Height of fall (IEC/EN 60068-2-32) - max		1 m
Mounting position		Horizontal
Shock resistance		15 g, Mechanical, Half-sinusoidal shock 11 ms, 18 Impacts
Vibration resistance		5 - 8.4 / 8.4 -150 Hz, 3,5 mm / 1 g
<b>Climatic environmental conditions</b>		
Air pressure		795 - 1080 hPa (operation)
Ambient operating temperature - min		0 °C
Ambient operating temperature - max		60 °C
Ambient storage temperature - min		-20 °C
Ambient storage temperature - max		85 °C
Climatic proofing		Damp heat, constant, to IEC 60068-2-3 Dry heat to IEC 60068-2-2
Environmental conditions		Condensation: prevent with appropriate measures
Relative humidity		0 - 95 % (non-condensing)
<b>Electro magnetic compatibility</b>		
Air discharge		8 kV
Burst impulse		2 kV, Supply cable 1 kV, Signal cable
Contact discharge		4 kV
Electromagnetic fields		1 V/m at 2 - 2.7 GHz (according to IEC EN 61000-4-3) 10 V/m at 0.08 - 1.0 GHz (according to IEC EN 61000-4-3) 3 V/m at 1.4 - 2 GHz (according to IEC EN 61000-4-3)
Emitted interference		47 dB (at 230 - 1000 MHz, Class A, radiated, high frequency) 40 dB (at 30 - 230 MHz, Class A, radiated, high frequency)
Radiated RFI		10 V
Surge rating		1 kV, Signal cable, unbalanced, EMC 0.5/0.5 kV, Supply cable, balanced/unbalanced), EMC
Voltage dips		Voltage dips: 10 ms/Voltage fluctuations: Yes
<b>Terminal capacities</b>		
Terminal capacity		0.2 - 1.5 mm <sup>2</sup> , flexible without ferrule, H07V-K 0.25 - 1.5 mm <sup>2</sup> , with ferrules with plastic collar according to DIN 46228-1 (ferrules crimped gas-tight) 24 - 16 AWG 0.25 - 1.5 mm <sup>2</sup> , with ferrules without plastic collar according to DIN 46228-1 (ferrules crimped gas-tight) 0.2 - 1.5 mm <sup>2</sup> , solid, H07V-U
Gauge pin		A1 (according to IEC/EN 60947-1)
Stripping length (main cable)		10 mm
Insulating material group		I
<b>Electrical rating</b>		
Rated operational voltage		160 V (terminations)
Supply voltage at AC, 50 Hz - min		0 V AC
Supply voltage at AC, 50 Hz - max		0 V AC
Supply voltage at DC - min		18 V DC
Supply voltage at DC - max		30 V DC
<b>Communication</b>		
Connection type		2 conductors, Temperature and resistance measurement Push-in spring-cage terminal (plug-in connection), Connection design in TOP direction
Protocol		Other bus systems
<b>Input/Output</b>		
Accuracy		± 0.7 % of full scale, Temperature and resistance measurement
Input		8 Analog thermocouple inputs 2 KTY inputs
Load current		Not specified by plug manufacturer
Measured variables		Temperature
Number of inputs (analog)		10
Number of outputs (analog)		0
Value refresh time/cycle time		Min. 1 / 1 ms (per channel / all channels), Analog Inputs

Safety		
Explosion safety category for dust		None
Explosion safety category for gas		None
Potential isolation		Analog inputs: no
Design verification		
Equipment heat dissipation, current-dependent Pvid		0 W
Heat dissipation capacity Pdis		0 W
Heat dissipation per pole, current-dependent Pvid		2.11 W
Rated operational current for specified heat dissipation (In)		0 A
Static heat dissipation, non-current-dependent Pvs		3.04 W
10.2.2 Corrosion resistance		Meets the product standard's requirements.
10.2.3.1 Verification of thermal stability of enclosures		Meets the product standard's requirements.
10.2.3.2 Verification of resistance of insulating materials to normal heat		Meets the product standard's requirements.
10.2.3.3 Resist. of insul. mat. to abnormal heat/fire by internal elect. effects		Meets the product standard's requirements.
10.2.4 Resistance to ultra-violet (UV) radiation		Meets the product standard's requirements.
10.2.5 Lifting		Does not apply, since the entire switchgear needs to be evaluated.
10.2.6 Mechanical impact		Does not apply, since the entire switchgear needs to be evaluated.
10.2.7 Inscriptions		Meets the product standard's requirements.
10.3 Degree of protection of assemblies		Meets the product standard's requirements.
10.4 Clearances and creepage distances		Meets the product standard's requirements.
10.5 Protection against electric shock		Does not apply, since the entire switchgear needs to be evaluated.
10.6 Incorporation of switching devices and components		Does not apply, since the entire switchgear needs to be evaluated.
10.7 Internal electrical circuits and connections		Is the panel builder's responsibility.
10.8 Connections for external conductors		Is the panel builder's responsibility.
10.9.2 Power-frequency electric strength		Is the panel builder's responsibility.
10.9.3 Impulse withstand voltage		Is the panel builder's responsibility.
10.9.4 Testing of enclosures made of insulating material		Is the panel builder's responsibility.
10.10 Temperature rise		The panel builder is responsible for the temperature rise calculation. Eaton will provide heat dissipation data for the devices.
10.11 Short-circuit rating		Is the panel builder's responsibility.
10.12 Electromagnetic compatibility		Is the panel builder's responsibility.
10.13 Mechanical function		The device meets the requirements, provided the information in the instruction leaflet (IL) is observed.

## Technical data ETIM 9.0

Programmable logic controllers PLC (EG000024) / Fieldbus, decentr. periphery - analogue I/O module (EC001596)		
Electric engineering, automation, process control engineering / Control, Process Control System (PCS) / Field bus, decentralized peripheral / Field bus, decentralized peripheral - analogue I/O module (ecl@ss13-27-24-26-01 [BAA061019])		
Supply voltage AC 50 Hz	V	0 - 0
Supply voltage AC 60 Hz	V	0 - 0
Supply voltage DC	V	18 - 30
Voltage type (supply voltage)		DC
Power consumption	W	2.6
Input, current		No
Input, voltage		No
Input, resistor		No
Input, resistance thermometer		Yes
Input, thermocouple		Yes
Input signal, configurable		Yes
Resolution of the analogue inputs	Bit	16
Output, current		No
Output, voltage		No
Output signal configurable		No
Resolution of the analogue outputs	Bit	0
Number of analogue inputs		10
Number of analogue outputs		0

Analogue inputs configurable		Yes
Analogue outputs configurable		Yes
Number of HW-interfaces industrial Ethernet		0
Number of interfaces PROFINET		0
Number of HW-interfaces RS-232		0
Number of HW-interfaces RS-422		0
Number of HW-interfaces RS-485		0
Number of HW-interfaces serial TTY		0
Number of HW-interfaces parallel		0
Number of HW-interfaces wireless		0
Number of HW-interfaces USB		0
Number of HW-interfaces other		1
Supporting protocol for EtherCAT		No
Supporting protocol for TCP/IP		No
Supporting protocol for PROFIBUS		No
Supporting protocol for CAN		No
Supporting protocol for INTERBUS		No
Supporting protocol for ASI		No
Supporting protocol for KNX		No
Supporting protocol for Modbus		No
Supporting protocol for Data-Highway		No
Supporting protocol for DeviceNet		No
Supporting protocol for SUCONET		No
Supporting protocol for LON		No
Supporting protocol for PROFINET IO		No
Supporting protocol for PROFINET CBA		No
Supporting protocol for SERCOS		No
Supporting protocol for Foundation Fieldbus		No
Supporting protocol for EtherNet/IP		No
Supporting protocol for AS-Interface Safety at Work		No
Supporting protocol for DeviceNet Safety		No
Supporting protocol for INTERBUS-Safety		No
Supporting protocol for PROFIsafe		No
Supporting protocol for SafetyBUS p		No
Supporting protocol for other bus systems		Yes
Radio standard Bluetooth		No
Radio standard WLAN 802.11		No
Radio standard GPRS		No
Radio standard GSM		No
Radio standard UMTS		No
IO link master		No
System accessory		Yes
Degree of protection (IP)		IP20
Degree of protection (NEMA)		1
Type of electric connection		Plug-in connection
Fieldbus connection over separate bus coupler possible		Yes
Rail mounting possible		Yes
Wall mounting/direct mounting		No
Front built-in possible		No
Rack-assembly possible		No
Suitable for safety functions		No
SIL according to IEC 61508		None
Performance level according to EN ISO 13849-1		None
Appendant operation agent (Ex ia)		No
Appendant operation agent (Ex ib)		No

Explosion safety category for gas			None
Explosion safety category for dust			None
Certified for UL hazardous location class I			No
Certified for UL hazardous location class II			No
Certified for UL hazardous location class III			No
Certified for UL hazardous location division 1			No
Certified for UL hazardous location division 2			No
Certified for UL hazardous location group A (acetylene)			No
Certified for UL hazardous location group B (hydrogen)			No
Certified for UL hazardous location group C (ethylene)			No
Certified for UL hazardous location group D (propane)			No
Certified for UL hazardous location group E (metal dusts)			No
Certified for UL hazardous location group F (carbonaceous dusts)			No
Certified for UL hazardous location group G (non-conductive dusts)			No
Width		mm	80.3
Height		mm	16.8
Depth		mm	104.2