



Fuse-link, high speed, 180 A, AC 690 V, DC 500 V, 200 kA, BS88, 37 x 94 mm, aR, BS

**Part no.** 180A 690V AC TYPE T FUSE  
**Catalog No.** 180FEE

### Delivery program

|                              |   |    |  |
|------------------------------|---|----|--|
| Product range                |   |    | Fuse   |
| Basic function               |   |    | Fuse-link  |
| Field of application         |   |    | high speed   |
| Rated current                | I | A  | 180  |
| Rated voltage                |   |    | AC 690 V<br>DC 500 V   |
| Construction size            |   |    | BS88   |
| Size                         |   |    | 37 x 94 mm   |
| Utilization category         |   |    | aR   |
| Breaking Capacity            |   | kA | 200  |
| usable for size/applications |   |    | protection of DC common bus, DC drives, power converters/rectifiers and reduced voltage starters |
| Standard/Approval            |   |    | BS   |
| Shape                        |   |    | offset bolted tags (dual barrel)   |
| Standards/Regulations        |   |    | BS88-4<br>IEC 60269-4  |
| Optional accessories         |   |    | fuse-holder BH-1132  |

### Technical data ETIM 7.0

|   |  |    |       |
|---|--|----|-------|
| Circuit breakers and fuses (EG000020) / Low Voltage HRC fuse (EC000055)   |  |    |       |
| Electric engineering, automation, process control engineering / Electrical installation, device / Safety fuse inserts / Low-Voltage HRC fuse (ecl@ss10.0.1-27-14-20-05 [AFZ800015]) |  |    |       |
| Construction size   |  |    | Other |
| Rated current   |  | A  | 180   |
| Rated voltage   |  | V  | 690   |
| Voltage type  |  |    | AC/DC |
| Rated switching capacity  |  | kA | 200   |
| Utilization category  |  |    | Other |
| Type of fuse status indicator   |  |    | None  |
| Insulated metal gripping lugs (IMGL)  |  |    | No    |