

Indicator light, RMQ-Titan, Flat, Blue, Metal bezel



Part no. M30C-FL-B
183284
EL Number 4315653
(Norway)

| General specifications | | |
|--|--|--|
| Product name | | Eaton Moeller® series M30 Indicator light |
| Part no. | | M30C-FL-B |
| EAN | | 4015081782253 |
| Product Length/Depth | | 36 millimetre |
| Product height | | 32 millimetre |
| Product width | | 46 millimetre |
| Product weight | | 0.035 kilogram |
| Certifications | | IEC/EN 60947 VDE 0660 |
| Product Tradename | | M30 |
| Product Type | | Indicator light |
| Product Sub Type | | None |
| Features & Functions | | |
| Bezel color | | Chrome |
| Bezel material | | Metal |
| Design | | Flat |
| Fitted with: | | Front ring |
| Lens color | | Blue |
| General information | | |
| Degree of protection | | NEMA 4X, 13 |
| Degree of protection (front side) | | IP67/IP69K |
| Opening diameter | | 30 mm |
| Overvoltage category | | III |
| Pollution degree | | 3 |
| Product category | | RMQ-Titan |
| Rated impulse withstand voltage (Uimp) | | 4000 V AC |
| Size | | Front dimensions: Ø 36 mm |
| Type | | Indicator lights |
| Ambient conditions, mechanical | | |
| Mounting position | | As required |
| Shock resistance | | Not planned |
| Climatic environmental conditions | | |
| Ambient operating temperature - min | | -25 °C |
| Ambient operating temperature - max | | 70 °C |
| Climatic proofing | | Damp heat, constant, to IEC 60068-2-78 Damp heat, cyclic, to IEC 60068-2-30 |
| Terminal capacities | | |
| Terminal capacity | | 0.5 - 1.5 mm ² , solid 0.5 - 1.5 mm ² , stranded |
| Electrical rating | | |
| Rated insulation voltage (Ui) | | 250 V |
| Communication | | |
| Connection to SmartWire-DT | | With SWD-RMQ connections Yes |
| Contacts | | |
| Force for positive opening - min | | 0 N |

Technical data ETIM 9.0

| | | |
|--|----|------------|
| Low-voltage industrial components (EG000017) / Front element for indicator light (EC000223) | | |
| Electric engineering, automation, process control engineering / Low-voltage switch technology / Command and alarm device / Front element for warning lights (ecl@ss13-27-37-12-11 [AKF029019]) | | |
| Suitable for number of built-in signal lights | | 1 |
| Colour lens | | Blue |
| Construction type lens | | Round |
| Hole diameter | mm | 30 |
| Width opening | mm | 0 |
| Height opening | mm | 30 |
| With front ring | | Yes |
| Material front ring | | Metal |
| Colour front ring | | Chrome |
| Type of lens | | Flat |
| Degree of protection (IP), front side | | IP67/IP69K |
| Degree of protection (NEMA) | | 4X, 13 |