

**Switch-disconnector, 3 pole, 800A, without protection, IEC,
Withdrawable****Part no.** INX40N3-08W-1

184064

**EL Number
(Norway)**

4398426

General specifications	
Product name	Eaton Moeller series IZMX/INX switch-disconnector
Part no.	INX40N3-08W-1
EAN	4015081796038
Product Length/Depth	584 millimetre
Product height	597 millimetre
Product width	521 millimetre
Product weight	69 kilogram
Compliances	IEC IEC/EN 60947 RoHS conform
Product Tradename	IZMX/INX
Product Type	Switch-disconnector
Product Sub Type	None
Delivery program	
Type	Air circuit breakers/switch-disconnector Open switch-disconnector
Number of poles	Three-pole
Amperage Rating	800 A
Release system	Without releases
Features	Version as main switch Motor drive optional Version as maintenance-/service switch
Special features	Cassette must be separately ordered. Optionally fittable by user with comprehensive accessories Terminal capacity hint: These are values used in separate switchgear. The actual values will depend on the temperature around the circuit breaker, which is influenced by the ambient temperature, the degree of protection (IP), the mounting height, the partitions, and any external ventilation. Depending on the specific switchgear design, this may result in derating, which can then be compensated for by increasing the cross-sectional area. Temperature rise tests in the specific switchgear can provide specific and detailed information.
Frame	INX40
Suitable for	Ground mounting Distribution board installation Intermediate mounting
Technical Data - Electrical	
Voltage rating at AC	690 V AC
Rated operating voltage (Ue) - min	690 V
Rated operating voltage (Ue) - max	690 V
Rated operating voltage (Ue) at AC - max	690 V
Rated insulation voltage (Ui)	1000 V
Rated impulse withstand voltage (Uimp)	12 kV AC
Rated uninterrupted current (Iu)	800 A
Rated uninterrupted current (Iu) at 50°C	800 A
Rated uninterrupted current (Iu) at 60°C	800 A
Rated uninterrupted current (Iu) at 70°C	800 A
Rated conditional short-circuit current (Iq)	187 kA
Rated permanent current at AC-21, 400 V	0 A
Rated permanent current at AC-23, 400 V	800 A
Rated short-time withstand current (Icw)	85 kA
Rated short-time withstand current (t = 1 s)	85 kA
Rated short-time withstand current at 50/60 Hz (t = 3 s)	66 kA

Rated short-circuit making capacity up to 440 V, 50/60 Hz		187 kA
Rated short-circuit making capacity up to 690 V, 50/60 Hz		166 kA
Power of withdrawable switch with cassette		35 W
Rated operating power at AC-3, 400 V		0 kW
Rated operating power at AC-23, 400 V		0 kW
Switching power at 400 V		0 kW
Closing delay via spring release		35 ms
Electrical connection type of main circuit		Rail connection
Number of standard mechanical operations per hour - max		60
Actuator type		Push button
Utilization category		B
Overvoltage category		III
Pollution degree		3
Lifespan, electrical		10000 operations (switching capacity) 20000 operations (switching cycles ON/OFF, with maintenance)
Direction of incoming supply		As required
Technical Data - Mechanical		
Device construction		Built-in device slide-in technique (withdrawable)
Mounting Method		Withdrawable
Degree of protection		IP55 with protective cover IP31 with door seals
Degree of protection (front side)		IP31
Protection		None
Number of auxiliary contacts (change-over contacts)		2
Number of auxiliary contacts (normally closed contacts)		0
Number of auxiliary contacts (normally open contacts)		0
Number of switches		1
Position of connection for main current circuit		Back side
Weight of cassette version (3-pole)		29 kg
Weight of fixed withdrawable version (3-pole)		66 kg
Actuator color		Green
Lifespan, mechanical		12500 switching cycles (ON/OFF) 25000 operations (switching capacity, with maintenance)
Technical Data - Mechanical - Terminals		
Terminal capacity (copper bar)		60 mm x 10 mm (1x) for withdrawable units (black)
Design verification as per IEC/EN 61439 - technical data		
Rated operational current for specified heat dissipation (In)		800 A
Equipment heat dissipation, current-dependent		35 W
Ambient operating temperature details		-20 °C - 70 °C
Ambient operating temperature - min		-25 °C
Ambient operating temperature - max		70 °C
Ambient storage temperature - min		-40 °C
Ambient storage temperature - max		70 °C
Design verification as per IEC/EN 61439		
10.2.2 Corrosion resistance		Meets the product standard's requirements.
10.2.3.1 Verification of thermal stability of enclosures		Meets the product standard's requirements.
10.2.3.2 Verification of resistance of insulating materials to normal heat		Meets the product standard's requirements.
10.2.3.3 Resist. of insul. mat. to abnormal heat/fire by internal elect. effects		Meets the product standard's requirements.
10.2.4 Resistance to ultra-violet (UV) radiation		Meets the product standard's requirements.
10.2.5 Lifting		Does not apply, since the entire switchgear needs to be evaluated.
10.2.6 Mechanical impact		Does not apply, since the entire switchgear needs to be evaluated.
10.2.7 Inscriptions		Meets the product standard's requirements.
10.3 Degree of protection of assemblies		Does not apply, since the entire switchgear needs to be evaluated.
10.4 Clearances and creepage distances		Meets the product standard's requirements.
10.5 Protection against electric shock		Does not apply, since the entire switchgear needs to be evaluated.
10.6 Incorporation of switching devices and components		Does not apply, since the entire switchgear needs to be evaluated.

10.7 Internal electrical circuits and connections		Is the panel builder's responsibility.
10.8 Connections for external conductors		Is the panel builder's responsibility.
10.9.2 Power-frequency electric strength		Is the panel builder's responsibility.
10.9.3 Impulse withstand voltage		Is the panel builder's responsibility.
10.9.4 Testing of enclosures made of insulating material		Is the panel builder's responsibility.
10.10 Temperature rise		The panel builder is responsible for the temperature rise calculation. Eaton will provide heat dissipation data for the devices.
10.11 Short-circuit rating		Is the panel builder's responsibility. The specifications for the switchgear must be observed.
10.12 Electromagnetic compatibility		Is the panel builder's responsibility. The specifications for the switchgear must be observed.
10.13 Mechanical function		The device meets the requirements, provided the information in the instruction leaflet (IL) is observed.
Additional information		
Functions		Interlockable Voltage release optional

Technical data ETIM 9.0

Low-voltage industrial components (EG000017) / Switch disconnecter (low voltage) (EC000216)		
Electric engineering, automation, process control engineering / Low-voltage switch technology / Off-load switch, circuit breaker, control switch / Switch disconnecter (ecf@ss13-27-37-14-03 [AKF060018])		
Version as main switch		Yes
Version as maintenance-/service switch		Yes
Version as safety switch		No
Version as emergency stop installation		No
Version as reversing switch		No
Number of switches		1
Max. rated operation voltage U _e AC	V	690
Rated operating voltage	V	690 - 690
Rated permanent current I _u	A	800
Rated permanent current at AC-23, 400 V	A	800
Rated permanent current at AC-21, 400 V	A	0
Rated operation power at AC-3, 400 V	kW	0
Rated short-time withstand current I _{cw}	kA	85
Rated operation power at AC-23, 400 V	kW	0
Switching power at 400 V	kW	0
Conditioned rated short-circuit current I _q	kA	187
Number of poles		3
Number of auxiliary contacts as normally closed contact		0
Number of auxiliary contacts as normally open contact		0
Number of auxiliary contacts as change-over contact		2
Motor drive optional		Yes
Motor drive integrated		No
Voltage release optional		Yes
Device construction		Built-in device slide-in technique (withdrawable)
Suitable for floor mounting		Yes
Suitable for front mounting 4-hole		No
Suitable for front mounting centre		No
Suitable for distribution board installation		Yes
Suitable for intermediate mounting		Yes
Colour control element		Green
Type of control element		Push button
Interlockable		Yes
Type of electrical connection of main circuit		Rail connection
With pre-assembled cabling		No
Degree of protection (IP), front side		IP31
Degree of protection (NEMA)		

Width	mm	521
Height	mm	597
Depth	mm	584
Width in number of modular spacings		24