

Undervoltage release 60 VDC



**Part no.** IZMX-UVR60DC-1  
**184112**  
**EL Number** 4398475  
**(Norway)**

General specifications	
Product name	Eaton Moeller series IZMX/INX undervoltage release
Part no.	IZMX-UVR60DC-1
EAN	4015081783168
Product Length/Depth	150 millimetre
Product height	100 millimetre
Product width	100 millimetre
Product weight	0.091 kilogram
Compliances	RoHS conform
Product Tradename	IZMX/INX
Product Type	Accessories
Product Sub Type	Undervoltage release
Delivery program	
Type	Accessory
Special features	Cannot be combined with a second shunt release. Retrofitting kit Slot on the right on the adapter plate. Limited to 3/min due to the high pick-up current for 35 ms. Please note - the circuit-breaker's switching frequency = 60/h The retrofit kit includes the required SEC control cable terminals.
Suitable for	Power circuit breaker Motor safety switch Off-load switch Overload relay
Used with	INX16..., INX40... IZMX16..., IZMX40...
Technical Data - Electrical	
Voltage type	DC
Control voltage operating range	60 V DC 0.85 - 1.1 x Us
Rated control supply voltage (Us) at AC, 50 Hz - min	0 V
Rated control supply voltage (Us) at AC, 50 Hz - max	0 V
Rated control supply voltage (Us) at AC, 60 Hz - min	0 V
Rated control supply voltage (Us) at AC, 60 Hz - max	0 V
Rated control supply voltage (Us) at DC - min	60 V
Rated control supply voltage (Us) at DC - max	60 V
Current rating - max	0.07 A (maximum holding current)
Rated operational current	0.07 A (maximum holding current)
Power consumption	5 VA/W AC/DC
Pick-up power consumption at 35 ms - max	890 VA/W
Circuit breaker total switching time	40 ms (Us = 100%) (IZMX40..., INX40...) 50 ms (Us = 100%) (IZMX16..., INX16...)
Electric connection type	Flat plug-in connection
Technical Data - Mechanical	
Number of actuation per minute - max	3
Number of contacts (change-over contacts)	0
Number of contacts (normally closed contacts)	0
Number of contacts (normally open contacts)	0
Design verification as per IEC/EN 61439 - technical data	
Ambient operating temperature - min	-25 °C
Ambient operating temperature - max	70 °C
Additional information	

## Technical data ETIM 9.0

Low-voltage industrial components (EG000017) / Under voltage coil (EC001022)

Electric engineering, automation, process control engineering / Low-voltage switch technology / Circuit breaker (LV < 1 kV) / Undervoltage trip (ecl@ss13-27-37-04-17 [AKF015018])

Rated control supply voltage AC 50 Hz	V	0 - 0
---------------------------------------	---	-------

Rated control supply voltage AC 60 Hz	V	0 - 0
---------------------------------------	---	-------

Rated control supply voltage DC	V	60 - 60
---------------------------------	---	---------

Voltage type for actuating		DC
----------------------------	--	----

Type of electric connection		Flat plug-in connection
-----------------------------	--	-------------------------

Number of contacts as normally open contact		0
---	--	---

Number of contacts as normally closed contact		0
---	--	---

Number of contacts as change-over contact		0
---	--	---

Delayed		No
---------	--	----

Suitable for power circuit breaker		Yes
------------------------------------	--	-----

Suitable for off-load switch		Yes
------------------------------	--	-----

Suitable for motor safety switch		Yes
----------------------------------	--	-----

Suitable for overload relay		Yes
-----------------------------	--	-----