



Mechanical interlock, TYPE 32, bowden cables, F

Part no. IZMX-MIL32C-F16-1
Catalog No. 184208
Alternate Catalog No. 65A2840G35

Delivery program

Product range			Accessories
Accessories			Interlocks
Accessories			Mechanical interlock, fixed mounting
			Type 32
			For 3 circuit-breakers with the same or different frame size: interlock: 2 against 1 / max. 2 ON. Any one or two circuit-breakers can be closed at the same time. In addition, three IZMX-MIL-CAB... cable kits are required. Select the appropriate part no. for each circuit-breaker.
For use with			IZMX16... INX16...
Installation type			Fixed

Design verification as per IEC/EN 61439

Technical data for design verification			
Operating ambient temperature min.		°C	-25
Operating ambient temperature max.		°C	70

Technical data ETIM 7.0

Low-voltage industrial components (EG000017) / Mechanic interlock for switch (EC001044)			
Electric engineering, automation, process control engineering / Low-voltage switch technology / Component for low-voltage switching technology / Mechanic interlock for switch (ecl@ss10.0.1-27-37-13-03 [AKN341013])			
Auxiliary contacts, extendable			No
Number of contacts as normally closed contact			0
Number of contacts as normally open contact			0

Dimensions

