





Overload relay, ZBT32, I<sub>r</sub>= 24 - 32 A, 1 N/O, 1 N/C, Direct mounting, IP20

Part no. **ZBT32-32**  
 Catalog No. **190942**

**Delivery program**

Product range			Overload relay ZBT up to 97 A
Product range			Accessories
Accessories			Overload relays
Frame size			ZBT32
Phase-failure sensitivity			IEC/EN 60947, VDE 0660 Part 102
Description			Test/off button Reset pushbutton manual/auto Trip-free release Overload trigger: tripping class 10 A
Mounting type			Direct mounting
	I <sub>r</sub>	A	24 - 32
Contact sequence			
<b>Auxiliary contacts</b>			
N/O = Normally open			1 N/O
N/C = Normally closed			1 N/C
For use with			DILMT17 DILMT25 DILMT32

**Technical data**

<b>General</b>			
Standards			IEC/EN 60947, GB14048
Climatic proofing			Damp heat, constant, to IEC 60068-2-78 Damp heat, cyclic, to IEC 60068-2-30
Ambient temperature			Operating range to IEC/EN 60947: -5 - +40 °C
Open		°C	-25 - +55
Enclosed		°C	- 25 - 40
Temperature compensation			Continuous
Weight		kg	0.114
Mechanical shock resistance		g	10 Sinusoidal Shock duration 10 ms
Degree of Protection			IP20
Protection against direct contact when actuated from front (EN 50274)			Finger and back-of-hand proof

**Main conducting paths**

Rated impulse withstand voltage	U <sub>imp</sub>	V AC	6000
Overvoltage category/pollution degree			III/3
Rated insulation voltage	U <sub>i</sub>	V	690
Rated operational voltage	U <sub>e</sub>	V AC	690
Safe isolation to EN 61140			
Between auxiliary contacts and main contacts		V AC	440

Between main circuits	V AC	440
Terminal capacities	mm <sup>2</sup>	
Solid	mm <sup>2</sup>	1 x (1 - 6)
Flexible with ferrule	mm <sup>2</sup>	1 x (1 - 6)
Stranded	mm <sup>2</sup>	1 x (1 - 6)
Terminal screw		M3.5
Tightening torque	Nm	1.2
Stripping length	mm	8
Tools		
Pozidriv screwdriver	Size	2

### Auxiliary and control circuits

Rated impulse withstand voltage	U <sub>imp</sub>	V	4000
Overvoltage category/pollution degree			III/3
Terminal capacities	mm <sup>2</sup>		
Solid	mm <sup>2</sup>		1 x (0.75 - 2.5)
Flexible with ferrule	mm <sup>2</sup>		1 x (0.75 - 2.5)
Terminal screw			M3.5
Tightening torque	Nm		0.8
Stripping length	mm		6
Tools			
Pozidriv screwdriver	Size		2
Standard screwdriver	mm		1 x 6
Rated insulation voltage	U <sub>i</sub>	V AC	690
Rated operational voltage	U <sub>e</sub>	V AC	690
Conventional thermal current	I <sub>th</sub>	A	10
Rated operational current	I <sub>e</sub>	A	
AC-15			
Make contact			
120 V	I <sub>e</sub>	A	1.5
220 V 230 V 240 V	I <sub>e</sub>	A	1.4
380 V 400 V 415 V	I <sub>e</sub>	A	1.9
500 V	I <sub>e</sub>	A	0.5
Break contact			
120 V	I <sub>e</sub>	A	1.5
220 V 230 V 240 V	I <sub>e</sub>	A	1.5
380 V 400 V 415 V	I <sub>e</sub>	A	1.9
500 V	I <sub>e</sub>	A	1.4
DC L/R ≤ 15 ms			
			Switch-on and switch-off conditions based on DC-13, time constant as specified.
24 V	I <sub>e</sub>	A	0.9
60 V	I <sub>e</sub>	A	0.75
110 V	I <sub>e</sub>	A	0.55
220 V	I <sub>e</sub>	A	0.27
Short-circuit rating without welding			
max. fuse		A gG/gL	6

### Notes

**Notes** Ambient air temperature: Operating range to IEC/EN 60947, PTB: -5°C to +55°C  
Main circuits terminal capacity solid and flexible conductors with ferrules: When using 2 conductors use equal cross-sections.

### Design verification as per IEC/EN 61439

Technical data for design verification		
Operating ambient temperature min.	°C	-25
Operating ambient temperature max.	°C	55

## Technical data ETIM 7.0

Low-voltage industrial components (EG000017) / Thermal overload relay (EC000106)

Electric engineering, automation, process control engineering / Low-voltage switch technology / Overload protection device / Thermal overload relay (ecl@ss10.0.1-27-37-15-01 [AKF075014])

Adjustable current range	A	24 - 32
Max. rated operation voltage U <sub>e</sub>	V	690
Mounting method		Direct attachment
Type of electrical connection of main circuit		Screw connection
Number of auxiliary contacts as normally closed contact		1
Number of auxiliary contacts as normally open contact		1
Number of auxiliary contacts as change-over contact		0
Release class		Other
Reset function input		No
Reset function automatic		Yes
Reset function push-button		Yes

## Approvals

Specially designed for North America

	No
--	----

## Dimensions

