



Control transformer, 0.06 kVA, Rated input voltage 100 – 690 ± 5 % V, Rated output voltage 12 – 250 V



Part no. STN0,06(*/*)
Catalog No. 204938
Alternate Catalog No. -

Delivery program

| | | |
|---|-----|--|
| Product range | | Single-phase control transformers ST... |
| Basic function | | Single-phase STN control transformers |
| Rated input voltage | V | 100 – 690 ± 5 % |
| Rated output voltage | V | 12 – 250 |
| Rated power | kVA | 0.06 |
| Short-time rating | kVA | 0.095 |
| Cu factor 0,20 | | |
| Notes | | |
| | | <ul style="list-style-type: none"> The STN transformers are suitable for use in control circuits to VDE 0113 or IEC/EN 60204. UL/CSA only up to primary and secondary 600 V (incl. tappings). When ordering, the type reference must include the following details: |
| STN0,1(*/*) | | |
| 1st wildcard ≙ Nominal input voltage | | |
| 2nd wildcard ≙ Rated output voltage | | |
| Ordering example | | |
| | | <ul style="list-style-type: none"> Desired part no.: STN0,1 Desired rated input voltage 200 V Desired rated output voltage 18.5 V |
| The correct type reference is | | |
| STN0,1(200/18,5) | | |
| Transformer-protective circuit-breaker →#088907 | | |

Technical data

General

| | | |
|---------------------|--|--|
| Standards | | |
| Built and tested to | | IEC/EN 61558-2-2 VDE 0570 Part 2-2 |
| Suitable for use to | | IEC/EN 60204-1, ÖVE-EN 13 VDE 0113, VDE 0100 Part 410 |
| Ambient temperature | | -25 - 40 |

Characteristics

| | | |
|--------------------------|------|-------------|
| Terminations | | ● (< 115 A) |
| Connection lugs | | ● (> 115 A) |
| Insulation class | | B |
| Rated frequency | Hz | 50 - 60 |
| Primary tapping | | ± 5 % |
| Degree of Protection | | IP00 |
| Separate windings | | ● |
| Fully vacuum-impregnated | | ● |
| Rated duty factor | % DF | 100 |

Electrical characteristics

| | | |
|----------------------|----|---|
| Note | | The following applies for the no-load loss, short-circuit loss (copper losses), short-circuit voltage and efficiency values: all details relate to a temperature of 20 °C |
| Total weight | kg | 1 |
| No-load losses | W | 7 |
| Short-circuit losses | W | 10 |

| | | | |
|----------------------|--|---|------|
| Shortcircuit voltage | | % | 11 |
| Efficiency | | | 0.79 |

Design verification as per IEC/EN 61439

| Technical data for design verification | | | |
|--|------------|----|--|
| Rated operational current for specified heat dissipation | I_n | A | 0 |
| Heat dissipation per pole, current-dependent | P_{vid} | W | 0 |
| Equipment heat dissipation, current-dependent | P_{vid} | W | 0 |
| Static heat dissipation, non-current-dependent | P_{vs} | W | 17 |
| Heat dissipation capacity | P_{diss} | W | 0 |
| Operating ambient temperature min. | | °C | -25 |
| Operating ambient temperature max. | | °C | 40 |
| IEC/EN 61439 design verification | | | |
| 10.2 Strength of materials and parts | | | |
| 10.2.2 Corrosion resistance | | | Meets the product standard's requirements. |
| 10.2.3.1 Verification of thermal stability of enclosures | | | Meets the product standard's requirements. |
| 10.2.3.2 Verification of resistance of insulating materials to normal heat | | | Meets the product standard's requirements. |
| 10.2.3.3 Verification of resistance of insulating materials to abnormal heat and fire due to internal electric effects | | | Meets the product standard's requirements. |
| 10.2.4 Resistance to ultra-violet (UV) radiation | | | Meets the product standard's requirements. |
| 10.2.5 Lifting | | | Does not apply, since the entire switchgear needs to be evaluated. |
| 10.2.6 Mechanical impact | | | Does not apply, since the entire switchgear needs to be evaluated. |
| 10.2.7 Inscriptions | | | Meets the product standard's requirements. |
| 10.3 Degree of protection of ASSEMBLIES | | | Does not apply, since the entire switchgear needs to be evaluated. |
| 10.4 Clearances and creepage distances | | | Meets the product standard's requirements. |
| 10.5 Protection against electric shock | | | Does not apply, since the entire switchgear needs to be evaluated. |
| 10.6 Incorporation of switching devices and components | | | Does not apply, since the entire switchgear needs to be evaluated. |
| 10.7 Internal electrical circuits and connections | | | Is the panel builder's responsibility. |
| 10.8 Connections for external conductors | | | Is the panel builder's responsibility. |
| 10.9 Insulation properties | | | |
| 10.9.2 Power-frequency electric strength | | | Is the panel builder's responsibility. |
| 10.9.3 Impulse withstand voltage | | | Is the panel builder's responsibility. |
| 10.9.4 Testing of enclosures made of insulating material | | | Is the panel builder's responsibility. |
| 10.10 Temperature rise | | | The panel builder is responsible for the temperature rise calculation. Eaton will provide heat dissipation data for the devices. |
| 10.11 Short-circuit rating | | | Is the panel builder's responsibility. The specifications for the switchgear must be observed. |
| 10.12 Electromagnetic compatibility | | | Is the panel builder's responsibility. The specifications for the switchgear must be observed. |
| 10.13 Mechanical function | | | The device meets the requirements, provided the information in the instruction leaflet (IL) is observed. |

Technical data ETIM 7.0


| Low-voltage industrial components (EG000017) / One-phase control transformer (EC002486) | | | |
|---|--|---|-----------|
| Electric engineering, automation, process control engineering / Transformer, converter, coil / Control transformer / One-phase control transformer (ecl@ss10.0.1-27-03-13-02 [AAB620015]) | | | |
| Built as safety transformer | | | No |
| Built as isolating transformer | | | No |
| Built as energy saving transformer | | | No |
| Primary voltage 1 | | V | 100 - 690 |
| Primary voltage 2 | | V | 0 - 0 |
| Primary voltage 3 | | V | 0 - 0 |
| Primary voltage 4 | | V | 0 - 0 |
| Primary voltage 5 | | V | 0 - 0 |
| Primary voltage 6 | | V | 0 - 0 |
| Primary voltage 7 | | V | 0 - 0 |
| Primary voltage 8 | | V | 0 - 0 |
| Primary voltage 9 | | V | 0 - 0 |

| | | |
|---|----|----------|
| Primary voltage 10 | V | 0 - 0 |
| Secondary voltage 1 | V | 12 - 250 |
| Secondary voltage 2 | V | 0 - 0 |
| Secondary voltage 3 | V | 0 - 0 |
| Secondary voltage 4 | V | 0 - 0 |
| Secondary voltage 5 | V | 0 - 0 |
| Secondary voltage 6 | V | 0 - 0 |
| Secondary voltage 7 | V | 0 - 0 |
| Secondary voltage 8 | V | 0 - 0 |
| Secondary voltage 9 | V | 0 - 0 |
| Secondary voltage 10 | V | 0 - 0 |
| Rated apparent power | VA | 60 |
| Type of insulation material acc. IEC 85 | | B |
| Short-circuit-proof | | No |
| Relative short circuit voltage | % | 11 |
| Width | mm | 85 |
| Height | mm | 91 |
| Depth | mm | 79 |
| Degree of protection (IP) | | IP00 |
| Ring core | | No |
| Suitable for mounting on PCB | | No |
| Modular version | | No |
| Conductor material | | Copper |

Approvals

| | | |
|--------------------------------------|--|---|
| Product Standards | | UL 506; UL5085-1; UL 5085-2; CSA-C22.2 No. 66; CSA-C22.2 No. 66.1-06; CSA-C22.2 No. 66.2-06; IEC/EN 61558-2-2; CE marking |
| UL File No. | | E167225 |
| UL Category Control No. | | XPTQ2, XPTQ8 |
| CSA File No. | | UL report applies to both US and Canada |
| CSA Class No. | | - |
| North America Certification | | UL recognized, certified by UL for use in Canada |
| Specially designed for North America | | No |
| Suitable for | | Branch circuits |
| Max. Voltage Rating | | 600 V AC |
| Degree of Protection | | IEC: IP00, UL/CSA Type: - |

Dimensions



- ① Connection lugs
- ② Maximum space requirement
- ③ with STN0,06-02 ground connection at bottom