

**Changeoverswitches, T0, 20 A, surface mounting, 3 contact unit(s),
Contacts: 6, 45 °, momentary, With 0 (Off) position, with spring-return from
both directions to 0, 2>0<1, Design number 8216**



**Part no. T0-3-8216/I1
207434
EL Number 1417174
(Norway)**

| General specifications | | |
|--|--|--|
| Product name | | Eaton Moeller® series T0 Changeover switch |
| Part no. | | T0-3-8216/I1 |
| EAN | | 4015082074340 |
| Product Length/Depth | | 137 millimetre |
| Product height | | 122 millimetre |
| Product width | | 80 millimetre |
| Product weight | | 0.288 kilogram |
| Certifications | | IEC/EN 60947 IEC/EN 60204 VDE 0660 IEC/EN 60947-3 |
| Product Tradename | | T0 |
| Product Type | | Changeover switch |
| Product Sub Type | | None |
| Catalog Notes | | Rated Short-time Withstand Current (Icw) for a time of 1 second |
| Features & Functions | | |
| Enclosure material | | Plastic |
| Features | | Complete device in housing |
| Fitted with: | | Black thumb grip and front plate Retraction in 0-position 0 (off) position |
| Inscription | | 2>0<1 |
| Number of poles | | 3 |
| General information | | |
| Degree of protection | | IP65 |
| Degree of protection (front side) | | IP65 NEMA 12 |
| Lifespan, mechanical | | 400,000 Operations |
| Model | | Reverser |
| Mounting method | | Surface mounting |
| Mounting position | | As required |
| Number of contact units | | 3 |
| Operating frequency | | 1200 Operations/h |
| Overvoltage category | | III |
| Pollution degree | | 3 |
| Rated impulse withstand voltage (Uimp) | | 6000 V AC |
| Safe isolation | | 440 V AC, Between the contacts, According to EN 61140 |
| Safety parameter (EN ISO 13849-1) | | B10d values as per EN ISO 13849-1, table C.1 |
| Shock resistance | | 15 g, Mechanical, According to IEC/EN 60068-2-27, Half-sinusoidal shock 20 ms |
| Suitable for | | Ground mounting |
| Switching angle | | 45 ° |
| Type | | Changeover switch |
| Climatic environmental conditions | | |
| Ambient operating temperature - min | | -25 °C |
| Ambient operating temperature - max | | 40 °C |
| Ambient operating temperature (enclosed) - min | | -25 °C |
| Ambient operating temperature (enclosed) - max | | 40 °C |

| | | |
|--|--|---|
| Climatic proofing | | Damp heat, constant, to IEC 60068-2-78 Damp heat, cyclic, to IEC 60068-2-30 |
| Terminal capacities | | |
| Terminal capacity (flexible with ferrule) | | 2 x (0.75 - 2.5) mm ² , ferrules to DIN 46228 1 x (0.75 - 2.5) mm ² , ferrules to DIN 46228 |
| Terminal capacity (solid/stranded) | | 2 x (1 - 2.5) mm ² 1 x (1 - 2.5) mm ² |
| Screw size | | M3.5, Terminal screw |
| Tightening torque | | 8.8 lb-in, Screw terminals 1 Nm, Screw terminals |
| Electrical rating | | |
| Rated breaking capacity at 220/230 V (cos phi to IEC 60947-3) | | 100 A |
| Rated breaking capacity at 400/415 V (cos phi to IEC 60947-3) | | 110 A |
| Rated breaking capacity at 500 V (cos phi to IEC 60947-3) | | 80 A |
| Rated breaking capacity at 660/690 V (cos phi to IEC 60947-3) | | 60 A |
| Rated operational current (Ie) | | 8.5 A at AC-3, 690 V star-delta 15.6 A at AC-3, 500 V star-delta 20 A at AC-3, 400 V star-delta 20 A at AC-3, 230 V star-delta |
| Rated operational current (Ie) at AC-3, 220 V, 230 V, 240 V | | 11.5 A |
| Rated operational current (Ie) at AC-3, 380 V, 400 V, 415 V | | 11.5 A |
| Rated operational current (Ie) at AC-3, 500 V | | 9 A |
| Rated operational current (Ie) at AC-3, 660 V, 690 V | | 4.9 A |
| Rated operational current (Ie) at AC-21, 440 V | | 20 A |
| Rated operational current (Ie) at AC-23A, 230 V | | 13.3 A |
| Rated operational current (Ie) at AC-23A, 400 V, 415 V | | 13.3 A |
| Rated operational current (Ie) at AC-23A, 500 V | | 13.3 A |
| Rated operational current (Ie) at AC-23A, 690 V | | 7.6 A |
| Rated operational current (Ie) at DC-1, load-break switches I/r = 1 ms | | 10 A |
| Rated operational current (Ie) at DC-13, control switches L/R = 50 ms | | 10 A |
| Rated operational current (Ie) at DC-21, 240 V | | 1 A |
| Rated operational current (Ie) at DC-23A, 24 V | | 10 A |
| Rated operational current (Ie) at DC-23A, 48 V | | 10 A |
| Rated operational current (Ie) at DC-23A, 60 V | | 10 A |
| Rated operational current (Ie) at DC-23A, 120 V | | 5 A |
| Rated operational current (Ie) at DC-23A, 240 V | | 5 A |
| Rated operational power at AC-3, 380/400 V, 50 Hz | | 4 kW |
| Rated operational power at AC-3, 415 V, 50 Hz | | 5.5 kW |
| Rated operational power at AC-3, 690 V, 50 Hz | | 4 kW |
| Rated operational power at AC-23A, 220/230 V, 50 Hz | | 3 kW |
| Rated operational power at AC-23A, 400 V, 50 Hz | | 5.5 kW |
| Rated operational power at AC-23A, 500 V, 50 Hz | | 7.5 kW |
| Rated operational power at AC-23A, 690 V, 50 Hz | | 5.5 kW |
| Rated operational power star-delta at 220/230 V, 50 Hz | | 5.5 kW |
| Rated operational power star-delta at 380/400 V, 50 Hz | | 7.5 kW |
| Rated operational power star-delta at 500 V, 50 Hz | | 7.5 kW |
| Rated operational power star-delta at 690 V, 50 Hz | | 5.5 kW |
| Rated operational voltage (Ue) at AC - max | | 690 V |
| Rated uninterrupted current (Iu) | | 20 A |
| Uninterrupted current | | Rated uninterrupted current Iu is specified for max. cross-section. |
| Short-circuit rating | | |
| Rated conditional short-circuit current (Iq) | | 6 kA |
| Rated short-time withstand current (Icw) | | 320 A, Contacts, 1 second |
| Short-circuit protection rating | | 20 A gG/gL, Fuse, Contacts |
| Switching capacity | | |
| Load rating | | 2 x I# (with intermittent operation class 12, 25 % duty factor) 1.3 x I# (with intermittent operation class 12, 60 % duty factor) 1.6 x I# (with intermittent operation class 12, 40 % duty factor) |

| | | |
|--|--|--|
| Number of contacts in series at DC-21A, 240 V | | 1 |
| Number of contacts in series at DC-23A, 24 V | | 1 |
| Number of contacts in series at DC-23A, 48 V | | 2 |
| Number of contacts in series at DC-23A, 60 V | | 3 |
| Number of contacts in series at DC-23A, 120 V | | 3 |
| Number of contacts in series at DC-23A, 240 V | | 5 |
| Rated making capacity up to 690 V (cos phi to IEC/EN 60947-3) | | 130 A |
| Voltage per contact pair in series | | 60 V |
| Contacts | | |
| Control circuit reliability | | 1 failure per 100,000 switching operations statistically determined, at 24 V DC, 10 mA) |
| Number of auxiliary contacts (change-over contacts) | | 0 |
| Number of auxiliary contacts (normally closed contacts) | | 0 |
| Number of auxiliary contacts (normally open contacts) | | 0 |
| Number of contacts | | 6 |
| Actuator | | |
| Actuator function | | Spring-return from both directions to 0 Momentary With 0 (Off) position |
| Actuator type | | Short thumb-grip |
| Design verification | | |
| Equipment heat dissipation, current-dependent Pvid | | 0 W |
| Heat dissipation capacity Pdis | | 0 W |
| Heat dissipation per pole, current-dependent Pvid | | 0.6 W |
| Rated operational current for specified heat dissipation (In) | | 20 A |
| Static heat dissipation, non-current-dependent Pvs | | 0 W |
| 10.2.2 Corrosion resistance | | Meets the product standard's requirements. |
| 10.2.3.1 Verification of thermal stability of enclosures | | Meets the product standard's requirements. |
| 10.2.3.2 Verification of resistance of insulating materials to normal heat | | Meets the product standard's requirements. |
| 10.2.3.3 Resist. of insul. mat. to abnormal heat/fire by internal elect. effects | | Meets the product standard's requirements. |
| 10.2.4 Resistance to ultra-violet (UV) radiation | | UV resistance only in connection with protective shield. |
| 10.2.5 Lifting | | Does not apply, since the entire switchgear needs to be evaluated. |
| 10.2.6 Mechanical impact | | Does not apply, since the entire switchgear needs to be evaluated. |
| 10.2.7 Inscriptions | | Meets the product standard's requirements. |
| 10.3 Degree of protection of assemblies | | Does not apply, since the entire switchgear needs to be evaluated. |
| 10.4 Clearances and creepage distances | | Meets the product standard's requirements. |
| 10.5 Protection against electric shock | | Does not apply, since the entire switchgear needs to be evaluated. |
| 10.6 Incorporation of switching devices and components | | Does not apply, since the entire switchgear needs to be evaluated. |
| 10.7 Internal electrical circuits and connections | | Is the panel builder's responsibility. |
| 10.8 Connections for external conductors | | Is the panel builder's responsibility. |
| 10.9.2 Power-frequency electric strength | | Is the panel builder's responsibility. |
| 10.9.3 Impulse withstand voltage | | Is the panel builder's responsibility. |
| 10.9.4 Testing of enclosures made of insulating material | | Is the panel builder's responsibility. |
| 10.10 Temperature rise | | The panel builder is responsible for the temperature rise calculation. Eaton will provide heat dissipation data for the devices. |
| 10.11 Short-circuit rating | | Is the panel builder's responsibility. The specifications for the switchgear must be observed. |
| 10.12 Electromagnetic compatibility | | Is the panel builder's responsibility. The specifications for the switchgear must be observed. |
| 10.13 Mechanical function | | The device meets the requirements, provided the information in the instruction leaflet (IL) is observed. |

Technical data ETIM 9.0

| | | |
|---|--|----------|
| Low-voltage industrial components (EG000017) / Off-load switch (EC001105) | | |
| Electric engineering, automation, process control engineering / Low-voltage switch technology / Off-load switch, circuit breaker, control switch / Load-break switch (ecl@ss13-27-37-14-05 [AKF062018]) | | |
| Model | | Reverser |
| Number of poles | | 3 |

| | | |
|---|----|------------------|
| With zero (off) position | | Yes |
| With retraction in 0-position | | Yes |
| Rated permanent current I _u | A | 20 |
| Rated operation current I _e at AC-3, 400 V | A | 11.5 |
| Rated operation power at AC-3, 400 V | kW | 4 |
| Degree of protection (IP), front side | | IP65 |
| Degree of protection (NEMA), front side | | 12 |
| Number of auxiliary contacts as normally closed contact | | 0 |
| Number of auxiliary contacts as normally open contact | | 0 |
| Number of auxiliary contacts as change-over contact | | 0 |
| Suitable for floor mounting | | Yes |
| Suitable for front mounting | | No |
| Suitable for distribution board installation | | No |
| Suitable for intermediate mounting | | No |
| Complete device in housing | | Yes |
| Housing material | | Plastic |
| Type of control element | | Short thumb-grip |
| Type of electrical connection of main circuit | | Screw connection |