




LED, yellow, BA15d, 24VAC/DC

**Part no.** SL-LED-Y  
**Catalog No.** 215281  
**Alternate Catalog No.** SL-LED-Y

### Delivery program

Product range			SL signal towers
Single unit/Complete unit			Stand-alone device
			Socket size BA-15d
Lifespan to EN 60064 at $t_a = +25\text{ °C}$	$t_{\text{mean}}$ (AC)	h	100000
Rated operational voltage	$U_e$	V	18 - 30 V AC 50/60 Hz 18 - 30 V DC
Rated operational current	$I_e$	mA	13 - 50
<b>Colour</b>			
			
Connection to SmartWire-DT			no

### Design verification as per IEC/EN 61439

Technical data for design verification			
Operating ambient temperature min.		°C	-25
Operating ambient temperature max.		°C	55

### Approvals

Product Standards			IEC/EN 60947-5; UL 508; CSA-C22.2 No. 14-05; CSA-C22.2 No. 94-91; CE marking
UL File No.			E29184
UL Category Control No.			NKCR
CSA File No.			012528
CSA Class No.			3211-03
North America Certification			UL listed, CSA certified

### Additional product information (links)

<b>IL04716024Z (AWA1160-1685) Pillar lamps</b>		
IL04716024Z (AWA1160-1685) Pillar lamps		<a href="https://es-assets.eaton.com/DOCUMENTATION/AWA_INSTRUCTIONS/IL04716024Z2018_05.pdf">https://es-assets.eaton.com/DOCUMENTATION/AWA_INSTRUCTIONS/IL04716024Z2018_05.pdf</a>